

Product data sheet

Specifications



17" Rack LCD Console with Integrated 16 Port Analog KVM Switch

AP5816

Overview

Presentation The Rack LCD Console with Integrated KVM Switch combines the functionality of Rack LCD Console and Analog KVM switches in one convenient package optimizing U space in the rack environment, eliminating cable clutter, and offering a value of two products functionality in one package. Keyboard is a US English keyboard layout.

Lead time Usually in Stock

Main

Main Input Voltage 120 V
240 V

Input Connection Type IEC 60320 C14

Number of rack unit 1U

Cable length 6 ft (1.8 m)

Number of cables 1

Provided equipment USB KVM cable
Single user rack mount kit
PS2 KVM cable
NEMA 5-15 power cord
Installation guide
Firmware upgrade cable
Documentation CD
C13-C14 power cord

Physical

Colour Black

Height 1.7 in (4.3 cm)

Width 19.02 in (48.3 cm)

Depth 28.0 in (71.1 cm)

net weight 30.9 lb(US) (14 kg)

mounting location Front

Mounting preference No preference

mounting mode Rack-mounted

Maximum mounting depth 41.33 in (104.98 cm)

minimum mounting depth 26.8 in (68 cm)

Input

Network frequency 50/60 Hz

Conformance

Product certifications	cUL listed C-Tick CE Industry Canada KCC UL listed VDE TAA compliance
-------------------------------	--------------------------------------------------------------------------------------------

Standards	EN 60950 FCC part 15 class A IEC 60950
------------------	----------------------------------------------

Environmental

Ambient air temperature for operation	32.0000000000...104.0000000000 °F (0...40 °C)
----------------------------------------------	-----------------------------------------------

Supported Hardware

Display colour	16 colours
-----------------------	------------

display size	337.9 (H) x 270.3 (V) 17 inch
---------------------	----------------------------------

Trackball type	PS/2 touchpad USB mouse
-----------------------	----------------------------

Display type	LCD display
---------------------	-------------

Packing Units

Unit Type of Package 1	PCE
-------------------------------	-----

Number of Units in Package 1	1
-------------------------------------	---

Package 1 Height	5.1 in (13 cm)
-------------------------	----------------

Package 1 Width	32.7 in (83 cm)
------------------------	-----------------

Package 1 Length	26.2 in (66.5 cm)
-------------------------	-------------------

Package 1 Weight	44.40 lb(US) (20.14 kg)
-------------------------	-------------------------

Contractual warranty

Warranty	2 years repair or replace
-----------------	---------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)





Take-back Transparency RoHS/REACH


Resource performance


 Take-Back Program Available

Well-being performance

 Reach Free Of Svhc

 Lead Free

 Mercury Free

 Rohs Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

Environmental Disclosure [Product Environmental Profile](#)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile [End of Life Information](#)