

Product data sheet

Specifications



APC Smart-UPS On-Line,
1500VA, Rackmount 3U, 230V, 8x
C13 IEC outlets, Network Card,
Extended runtime, W/ rail kit, W/
Lithium-ion external battery

SRTL1500RMXLI-NC

Overview

Presentation	High density, double-conversion on-line power protection with scalable runtime.
Lead time	Usually in Stock

Main

Main Input Voltage	230 V
Product or component type	Uninterruptible power supply (UPS)
Other Input Voltage	220 V 240 V
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Rated power in W	1350 W
Rated power in VA	1500 VA
Input Connection Type	IEC 60320 C14
output connection type	8 IEC 60320 C13
Number of rack unit	3U
Cable length	1.8 m
Number of cables	1
Provided equipment	CD with software Communication cable Documentation CD Installation guide Removable support feet USB cable Warranty card
Range of product	Smart-UPS On-Line

Batteries & Runtime

Run Time	View Runtime Graph
Battery type	Li-Ion (Lithium-Ion)
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	6 h
Battery voltage	48 V

Battery charger power	103 W rated
Battery life	5...10 year(s)
Extended runtime	1

General

UPS type	Double conversion online
product web sub-family	Lithium-Ion
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

Colour	Black with silver front bezel
Height	8.5 cm
Width	43.2 cm
Depth	56 cm
Net weight	13.7 kg
Mounting preference	No preference
mounting mode	Rack-mounted with kit
Two post mountable	0
USB compatible	Yes
Mounting position	Horizontal Vertical

Input

Network frequency	40...70 Hz auto-sensing
Input voltage limits	160...275 V

Output

Maximum configurable power in VA	1500 VA
Maximum configurable power in W	1350 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Wave type	Sine wave
Harmonic distortion	Less than 2 %
Crest factor	3 : 1
Bypass type	Built-in bypass

Conformance

Product certifications	CE EAC RCM VDE UK PSTI
Marking	CE Mark

Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
------------------	--

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0.0000000000...15240.0000000000 m
Acoustic level	50 dBA
Heat dissipation	450 Btu/h
IP degree of protection	IP20

Communications & Management

Free slots	0
Preinstalled device	Network management card 3 with environmental monitoring
Alarm	Audible and visible alarms : prioritized by severity
Emergency power off	Yes

Surge Protection and Filtering

Surge energy rate	340 J
--------------------------	-------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24.5 cm
Package 1 Width	60 cm
Package 1 Length	81 cm
Package 1 Weight	21 kg

Contractual warranty

Warranty	5 year repair or replace
-----------------	--------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Energy Efficient Take-back Transparency RoHS/REACH

Resource performance

Energy Efficient Product

Take-Back Program Available

Well-being performance

Mercury Free

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)
