

APC NetShelter Rack PDU Advanced, Switched, 3Phase, 43.5kW 400V 63A or 34.6kW 415V 60A, 42 Outlets, IEC309

APDU10450SW

Overview

Lead time Usually in Stock

Main

Colour	Black
product or component type	PDU
PDU type	Switched
Cord length	5.9 ft (1.8 m)

Complementary

Input Voltage	415 V 3 phases	
Height	71.9 in (182.6 cm)	
Width	2.2 in (5.6 cm)	
Output Voltage	240 V	
Depth	3.0 in (7.5 cm)	
net weight	27.3 lb(US) (12.4 kg)	
mounting location	Side	
Mounting preference	No preference	
Input Plug Type	IEC 60309 60 A 3P + N + PE	
mounting mode	Rack-mounted	
Rack units	0U	
Mounting position	Vertical	
Communication port protocol	1000BASE-T 10/100BASE-T	
[In] rated current	48 A	
Permissible voltage	200240 V 346415 V	
Input current limits	60 A	
Load capacity	34600 VA	
Network frequency	50/60 Hz	
Outlet type and quantity	21 C13/C15/C19/C21 21C13/C15	

Environment

Product certifications	TAA compliance
Standards	UL 62368-1
	CSA C22.2 No 62368-1
	FCC part 15 Subpart B
IP degree of protection	IP44
Ambient air temperature for operation	23.0000000000140.0000000000 °F (-560 °C)
Relative humidity	595 %
Operating altitude	010000 ft
Ambient air temperature for storage	-13.0000000000149.0000000000 °F (-2565 °C)
Storage Relative Humidity	595 %
Storage altitude	050000 ft (0.000000000015240.000000000 m)

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	83.07 in (211 cm)
Package 1 Width	5.2 in (13.2 cm)
Package 1 Length	10.3 in (26.2 cm)
Package 1 Weight	41.9 lb(US) (19 kg)

Contractual warranty

Warranty 3 years repair or replace



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Reach Free Of Svhc



Rohs Exemption Information

Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information