

Flat Panel Monitors - US model		Features
Name	L171 Flat Panel Monitor	<ul style="list-style-type: none"> • All-purpose 17-inch flat panel LCD monitor • EPEAT™ Gold rating • Slim 14mm (0.55") side bezel • Resolution of 1280x1024 provides crisp screen images • Stand tilts for comfortable viewing • Direct access for automatic image setup and brightness • Quick and easy monitor adjustments using on-screen-display • A great replacement for a 17" or 19" CRT monitor • Scaling allows full screen viewing of resolutions less than 1280x1024 • Integrated power supply eliminates the bulky power adapter for improved cable management • Lockable digital controls • Matching design to ThinkPad® and ThinkCentre® systems
Case color	Business black	
Type-model	9227-AD1	
US Govt model (TAA) ¹⁰	No	
Stand	Tilt stand	
Screen	LCD Active Matrix TFT (Thin Film Transistor)	
Viewable image size (diag)	17.0" / 432mm (diagonal)	
Aspect ratio	5:4	
Pixel pitch (mm)	.264mm	
Max view area (inches)	13.3" x 10.6" (horizontal x vertical)	
Max view area (mm)	340mm x 272mm (horizontal x vertical)	
Viewing angle at 10:1 CR	130° (+67°/- 63°) vertical, 140° (+/- 70°) horizontal	
Video input	Analog	
Dual input	No	
Optimum resolution	1280x1024 at 60Hz	
Maximum resolution	1280x1024 at 76Hz (140MHz maximum pixel rate)	
Vertical frequency	55 to 75Hz	
Horizontal frequency	30 to 83kHz	
Preset display modes	VGA: 640x480 60, 72, 75Hz 640x350 70Hz 720x400 70Hz SVGA: 800x600 60, 72, 75Hz XGA: 1024x768 60, 70, 75 Hz SXGA: 1280x1024 60, 70, 75, 76 (Sun) Hz	
Presets / user settings	Standard presets: 15; user settings: 20	
Brightness	300 nits or cd/m ² (typical)	
Contrast ratio	700:1 (typical)	
Pixel response time	5ms (typical)	
Scaling	Can expand image of lower resolution to full screen of 1280x1024	
On screen display	On screen display with digital user controls (7 languages)	
Control features	Direct access (buttons on front) for auto adjustment and brightness; contrast; image horizontal and vertical position; user color settings (3 preset + 1 user); on screen display (OSD) language selection; menu position; information screen; image setup; image size to show normal or expanded format; reset of geometry and color point to factory default settings; lockable settings	
Monitor connector	One connector: analog VGA 15-pin D-shell [blue]	
Signal cable	Analog cable, detachable, VGA 15-pin D-shell at each end (for analog connector), 1.8 meter, matches color of monitor	
Anti-reflective	Anti-reflective, anti-glare	
Dimensions	15.2"H x 14.6"W x 6.8"D / 387mm height x 371mm width x 173mm depth	
Weight	9.1 lb / 4.2kg	
Viewing adjustments	Tilt: 30° back, 4° forward, no swivel, no lift, detachable stand	
Mounting features	Wall or desk mounting using the TFT Radial Arm ⁹ or third-party accessories meeting the VESA FPMPI [®] (100mm mount)	
Security	Security keyhole for attachment of optional cable lock (Kensington [®] lock-compatible)	
VESA-compliant ²	VESA DDC2B/CI, VESA DPMS-compliant	
Power management	ENERGY STAR ^{®3} 4.0	
Ergonomics	ISO 13406 Part 2 ¹	
Pixel defect	ISO 13406-2 Class II pixel defect standard	
Emission standards	MPR-2, MPR-3A, FCC Class B	
Environmental	TCO 99, WEEE, RoHS (EU Directive 2002/95/EC), EPEAT™ Gold rating	
Ship group	Monitor, attached stand, customer installable base, Setup Guide, Safety and Warranty Information, CD with multilingual User's Guide and monitor installation files, analog signal cable, 1.8m black power cord	
Power supply	100-240Vac (universal), integrated (no external brick-like power supply), 28 watts typical, <2 watts standby/suspend	
Limited warranty ⁴	3 year (includes backlight)	
Available date	November 2007	

Limited Warranty	Accessories										
<ul style="list-style-type: none"> ↪ 3-year limited warranty⁴ ↪ International Warranty Service⁵ ↪ Rapid Replacement Service at 1-800-IBM-SERV (426-7378) ↪ Replacement normally arrives in two business days, excluding holidays ↪ Lenovo pays all shipping costs for valid warranty claims⁵ ↪ Service upgrade options:⁷ <ul style="list-style-type: none"> • 3 year, on site exchange, Mon-Fri 9-5 with next day response (ThinkPlus™ part number 41C9209) • 3 year, on site exchange, 7 day x 24 hr with 4 hour response (41C9212) • 4 year, on site exchange, Mon-Fri 9-5 with next day response (41C9233) • 4 year, on site exchange, 7 day x 24 hr with 4 hour response (41C9234) ↪ 24x7⁸ day toll-free support for warranty issues during the warranty period⁴ 	<table border="0"> <tr> <td>ThinkVision® USB Soundbar</td> <td>40Y7616</td> </tr> <tr> <td>Kensington® MicroSaver® Security Cable Lock</td> <td>73P2582</td> </tr> <tr> <td>Kensington Twin Head Cable Lock</td> <td>45K1620</td> </tr> <tr> <td>ThinkPad Convertible Monitor Stand</td> <td>40Y7620</td> </tr> <tr> <td>ThinkVision TFT Radial Arm⁹</td> <td>19K4464</td> </tr> </table> <p>See details at www.lenovo.com/support/monitoraccessories</p> <p>See all monitors at www.lenovo.com/thinkvision</p>	ThinkVision® USB Soundbar	40Y7616	Kensington® MicroSaver® Security Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620	ThinkPad Convertible Monitor Stand	40Y7620	ThinkVision TFT Radial Arm ⁹	19K4464
ThinkVision® USB Soundbar	40Y7616										
Kensington® MicroSaver® Security Cable Lock	73P2582										
Kensington Twin Head Cable Lock	45K1620										
ThinkPad Convertible Monitor Stand	40Y7620										
ThinkVision TFT Radial Arm ⁹	19K4464										

See footnotes for important warranty information
 US model announced October 23, 2006
 US model withdrawn effective February 2009