Alienware m15 R7 AMD Setup and Specifications

Notes, cautions, and warnings

1	NOTE: A NOTE indicates important information that helps you make better use of your product.
	CAUTION: A CAUTION indicates either potential damage to hardware or loss of data and tells you how to avoid the problem.

 $\underline{\wedge}$ WARNING: A WARNING indicates a potential for property damage, personal injury, or death.

© 2022 Dell Inc. or its subsidiaries. All rights reserved. Dell Technologies, Dell, and other trademarks are trademarks of Dell Inc. or its subsidiaries. Other trademarks may be trademarks of their respective owners.

Contents

Chapter 1: Set up your Alienware m15 R7 AMD	
Chambar 2: Vianus of Aliannana m. 15 D7 AMD	E
Chapter 2: Views of Alienware m15 R7 AMD	
Right	
Left	
Тор	
тор Back	
Bottom	
DOLLOM	
Chapter 3: Specifications of Alienware m15 R7 AMD	
Dimensions and weight	
Processor	
Chipset	
Operating system	
Memory	
External ports	
Internal slots	
Ethernet	
Wireless module	12
Audio	
Storage	13
Keyboard	
Camera	
Touchpad	14
Power adapter	
Battery	
Display	16
GPU—Integrated	17
GPU—Discrete	17
Operating and storage environment	18
Chapter 4: Keyboard shortcuts of Alienware m15 R7 A	MD19
Chapter 5: Low blue light	
Chapter 6: Alienware Command Center	22
Chapter 7: Getting help and contacting Alienware	23

Set up your Alienware m15 R7 AMD

(i) NOTE: The images in this document may differ from your computer depending on the configuration you ordered.

Connect the power adapter and press the power button.



Views of Alienware m15 R7 AMD

Front



1. Left microphone

Provides digital sound input for audio recording and voice calls.

2. RGB-infrared camera

This combined camera supports both infrared Windows Hello facial recognition and standard RGB imaging for photos and videos.

(i) NOTE: Depending on the display configuration ordered your computer may ship with a HD RGB camera that enables you to video chat, capture photos, and record videos. For this configuration, the infrared emitters will not be featured in the camera module.

3. Camera-status light

Turns on when the camera is in use.

4. Right microphone

Provides digital sound input for audio recording and voice calls.

Right



1. USB 3.2 Gen 1 port

Connect devices such as external storage devices and printers. Provides data transfer speeds up to 5 Gbps.

2. USB 3.2 Gen 1 port with PowerShare

Connect devices such as external storage devices and printers.

Provides data transfer speeds up to 5 Gbps. PowerShare enables you to charge your USB devices even when your computer is turned off.

- NOTE: If your computer is turned off or in hibernate state, you must connect the power adapter to charge your devices using the PowerShare port. You must enable this feature in the BIOS setup program.
- NOTE: Certain USB devices may not charge when the computer is turned off or in sleep state. In such cases, turn on the computer to charge the device.

Left



1. Network port

Connect an Ethernet (RJ45) cable from a router or a broadband modem for network or Internet access.

2. Universal audio jack

Connect headphones or a headset (headphone and microphone combo).

Top



1. Touchpad

Move your finger on the touchpad to move the mouse pointer. Tap to left-click and two fingers tap to right-click.

2. Left-click button

Press to left-click.

3. Right-click button

Press to right-click.

4. Power button (Alien head)


Press to turn on the computer if it is turned off, in sleep state, or in hibernate state.

Press to put the computer into sleep state if it is turned on.

When the computer is turned on, press and hold the power button for four seconds to force shut-down the computer.

- NOTE: You can customize power-button behavior in Windows. For more information, see *Me and My Dell* at www.dell.com/support/manuals.
- NOTE: This computer supports AlienFX, which lets you choose from an array of color and transition effects across multiple zones on the computer, including the keyboard and power button. For more information, see <u>Alienware Command Center</u>.

Back



1. USB 3.2 Gen 2 (Type-C) port with DisplayPort

Connect devices such as external storage devices, printers, and external displays. Provides data transfer rate of up to 10 Gbps. Supports DisplayPort 1.4 and also enables you to connect an external display using a display adapter.

(i) NOTE: A USB Type-C to DisplayPort adapter (sold separately) is required to connect a DisplayPort device.

2. USB 3.2 Gen 1 port

Connect devices such as external storage devices and printers. Provides data transfer speeds up to 5 Gbps.

3. HDMI 2.1 port

Connect to a TV, external display or another HDMI-in enabled device. Provides video and audio output.

4. Power-adapter port

Connect a power adapter to provide power to your computer and charge the battery.

Bottom



1. Left speaker

Provides audio output.

2. Service Tag label

The Service Tag is a unique alphanumeric identifier that enables Dell service technicians to identify the hardware components in your computer and access warranty information.

3. Right speaker

Provides audio output.

Specifications of Alienware m15 R7 AMD

Dimensions and weight

The following table lists the height, width, depth, and weight of your Alienware m15 R7 AMD.

Table 1. Dimensions and weight

Description	Values	
Height:		
Front height	12.90 mm (0.51 in.)	
Rear height	20.60 mm (0.81 in.)	
Width	356.20 mm (14.02 in.)	
Depth	272.50 mm (10.73 in.)	
Weight (i) NOTE: The weight of your computer depends on the configuration ordered and manufacturing variability.		

Processor

The following table lists the details of the processors supported by your Alienware m15 R7 AMD.

Table 2. Processor

Description	Option one	Option two
Processor type	AMD Ryzen 7 6800H	AMD Ryzen 9 6900HX
Processor wattage	45 W	45 W
Processor core count	8	8
Processor thread count	16	16
Processor speed	Up to 4.70 GHz	Up to 4.90 GHz
Processor cache	20 MB	20 MB
Integrated graphics	AMD Radeon Graphics	AMD Radeon Graphics

Chipset

The following table lists the details of the chipset supported by your Alienware m15 R7 AMD.

Table 3. Chipset

Description	Values
Chipset	Integrated in the processor

Table 3. Chipset (continued)

Description	Values
Processor	AMD Ryzen 7/9
DRAM bus width	64-bit
Flash EPROM	32 MB
PCle bus	Up to Gen4

Operating system

Your Alienware m15 R7 AMD supports the following operating systems:

- Windows 11 Home, 64-bit
- Windows 11 Pro, 64-bit

Memory

The following table lists the memory specifications of your Alienware m15 R7 AMD.

Table 4. Memory specifications

Description	Values
Memory slots	Two-SODIMM slots
Memory type	DDR5
Memory speed	4800 MHz
Maximum memory configuration	64 GB
Minimum memory configuration	8 GB
Memory size per slot	8 GB, 16 GB, and 32 GB
Memory configurations supported	For computers shipped with a NVIDIA GeForce 3050 Ti graphics card: • 8 GB, 1 x 8 GB, DDR5, 4800 MHz • 16 GB, 1 x 16 GB, DDR5, 4800 MHz • 16 GB, 2 x 8 GB, DDR5, 4800 MHz, dual-channel For computers shipped with a NVIDIA GeForce 3060/3070 Ti/3080 Ti graphics card: • 8 GB, 1 x 8 GB, DDR5, 4800 MHz • 16 GB, 1 x 16 GB, DDR5, 4800 MHz • 16 GB, 2 x 8 GB, DDR5, 4800 MHz, dual-channel • 32 GB, 1 x 32 GB, DDR5, 4800 MHz • 32 GB, 2 x 16 GB, DDR5, 4800 MHz, dual-channel • 64 GB, 2 x 32 GB, DDR5, 4800 MHz, dual-channel

External ports

The following table lists the external ports of your Alienware m15 R7 AMD.

Table 5. External ports

Description	Values
Network port	One RJ45 port
USB ports	 Two USB 3.2 Gen 1 ports One USB 3.2 Gen 1 port with PowerShare One USB 3.2 Gen 2 Type-C port with DisplayPort
Audio port	One universal audio jack
Video port	One HDMI 2.1 port
Media-card reader	Not supported
Power-adapter port	One 7.4 mm x 5.1 mm DC-in
Security-cable slot	Not supported

Internal slots

The following table lists the internal slots of your Alienware m15 R7 AMD.

Table 6. Internal slots

Description	Values
M.2	 One M.2 2230 slot for WiFi and Bluetooth combo card One M.2 2230/2280 slot for solid-state drive, for computers with a NVIDIA GeForce RTX 3050 Ti graphics card Two M.2 2230/2280 slots for solid-state drives, for computers with a NVIDIA GeForce RTX 3060/3070 Ti/3080 Ti graphics card NOTE: To learn more about the features of different types of M.2 cards, search in the Knowledge Base Resource at www.dell.com/support.

Ethernet

The following table lists the wired Ethernet Local Area Network (LAN) specifications of your Alienware m15 R7 AMD.

Table 7. Ethernet specifications

Description	Values
Model number	Realtek RTL8111H-CG, for computers with a NVIDIA GeForce RTX 3050 Ti graphics card Realtek RTL8125BGS, for computers with a NVIDIA GeForce RTX 3060/3070 Ti/3080 Ti graphics card

Table 7. Ethernet specifications (continued)

Description	Values
Transfer rate	 10/100/1000 Mbps, for computers with a NVIDIA GeForce RTX 3050 Ti graphics card 10/100/1000/2500 Mbps, for computers with a NVIDIA GeForce RTX 3060/3070 Ti/3080 Ti graphics card

Wireless module

The following table lists the Wireless Local Area Network (WLAN) module supported on your Alienware m15 R7 AMD.

Table 8. Wireless module specifications

Description	Values
Model number	MediaTek MT7921
Transfer rate	Up to 1200 Mbps
Frequency bands supported	2.4 GHz/5 GHz
Wireless standards	 WiFi 802.11a/b/g Wi-Fi 4 (WiFi 802.11n) Wi-Fi 5 (WiFi 802.11ac) Wi-Fi 6 (WiFi 802.11ax)
Encryption	64-bit/128-bit WEPAES-CCMPTKIP
Bluetooth	Bluetooth 5.2

Audio

The following table lists the audio specifications of your Alienware m15 R7 AMD.

Table 9. Audio specifications

Description	Values
Audio controller	Realtek ALC3254
Stereo conversion	Supported
Internal audio interface	High definition audio interface
External audio interface	One universal audio jackOne HDMI 2.1 port
Number of speakers	2
Internal-speaker amplifier	Supported
External volume controls	Keyboard shortcut controls
Speaker output:	

Table 9. Audio specifications (continued)

Description		Values	
Average speaker output		2 W	
	Peak speaker output	2.5 W	
Subwoofer output		Not supported	
Microphone		Digital-array microphones in camera assembly	

Storage

This section lists the storage options on your Alienware m15 R7 AMD.

Your Alienware m15 R7 AMD supports one of the following storage configurations:

- One M.2 2230/2280 slot for solid-state drive, for computers with a NVIDIA GeForce RTX 3050 Ti graphics card
- Two M.2 2230/2280 slots for solid-state drives, for computers with a NVIDIA GeForce RTX 3060/3070 Ti/3080 Ti graphics card

The primary drive of your Alienware m15 R7 AMD varies with the storage configuration. For computers with an M.2 drive, the primary drive is the M.2 drive where the operating system is installed.

Table 10. Storage specifications

Storage type	Interface type	Capacity
M.2 2230 solid-state drive	PCle Gen4 x4 NVMe, up to 64 Gbps	Up to 256 GB
M.2 2280 solid-state drive	PCle Gen4 x4 NVMe, up to 64 Gbps	M.2 card slot 1: Up to 4 TBM.2 card slot 2: Up to 2 TB

Keyboard

The following table lists the keyboard specifications of your Alienware m15 R7 AMD.

Table 11. Keyboard specifications

Description	Values
Keyboard type	 1-zone RGB RGB per key RGB per key, backlit Cherry mechanical keyboard
Keyboard layout	QWERTY
Number of keys	 United States and Canada: 85 keys United Kingdom: 86 keys Japan: 89 keys
Keyboard size	X=19.05 mm key pitch Y=19.05 mm key pitch
Keyboard shortcuts	Some keys on your keyboard have two symbols on them. These keys can be used to type alternate characters or to perform secondary functions. To type the alternate character, press Shift and the desired key. To perform secondary functions, press Fn and the desired key.

Table 11. Keyboard specifications (continued)

Description	Values	
	NOTE: You can define the primary behavior of the function keys (F1–F12) changing Function Key Behavior in BIOS setup program. For more information, see Keyboard shortcuts.	

Camera

The following table lists the camera specifications of your Alienware m15 R7 AMD.

Table 12. Camera specifications

Values	
One	
 For computers with a 165 Hz display: one HD RGB camera For computers with a 240 Hz and 360 Hz display: one HD RGB-Infrared camera 	
Front	
CMOS sensor technology	
0.92 megapixel	
1280 x 720 (HD) at 30 fps	
0.23 megapixel	
640 x 360 at 30 fps	
75.8 degrees	
75.8 degrees	

Touchpad

The following table lists the touchpad specifications of your Alienware m15 R7 AMD.

Table 13. Touchpad specifications

Description		Values
Touchpad re	solution:	
	Horizontal	1217
	Vertical	681
Touchpad dimensions:		

Table 13. Touchpad specifications (continued)

Description		Values	
	Horizontal	105 mm (4.13 in.)	
	Vertical	60 mm (2.36 in.)	
Touchpad ge	stures	For more information about touchpad gestures available on Windows, see the Microsoft knowledge base article at support.microsoft.com .	

Power adapter

The following table lists the power adapter specifications of your Alienware m15 R7 AMD.

Table 14. Power adapter specifications

Description Option		Option one	Option two	Option three
Тур	е	180 W AC adapter	240 W AC adapter	240 W SFF AC adapter
Con	nector dimensions:			
	External diameter	7.40 mm	7.40 mm	7.40 mm
	Internal diameter	5.10 mm	5.10 mm	5.10 mm
Inpu	it voltage	100 VAC-240 VAC	100 VAC-240 VAC	100 VAC-240 VAC
Input frequency		50 Hz-60 Hz	50 Hz-60 Hz	50 Hz-60 Hz
Inpu	it current (maximum)	2.34 A	3.50 A	3.50 A
Out	put current (continuous)	9.23 A	12.31 A	12.31 A
Rated output voltage		19.50 VDC	19.50 VDC	19.50 VDC
Temperature range:				
Operating		0°C to 40°C (32°F to 104°F)	0°C to 40°C (32°F to 104°F)	0°C to 40°C (32°F to 104°F)
	Storage	-40°C to 70°C (-40°F to 158°F)	-40°C to 70°C (-40°F to 158°F)	-40°C to 70°C (-40°F to 158°F)

CAUTION: Operating and storage temperature ranges may differ among components, so operating or storing the device outside these ranges may impact the performance of specific components.

Battery

The following table lists the battery specifications of your Alienware m15 R7 AMD.

Table 15. Battery specifications

Description	Option one	Option two	
Battery type	6-cell "smart" lithium-ion, 56 Wh		
Battery voltage	13.20 VDC	13.20 VDC13.35 VDC	

Table 15. Battery specifications (continued)

Description		Option one	Option two	
Battery weight (maximur	n)	0.26 kg (0.57 lb)	0.34 kg (0.75 lb)	
Battery dimensions:				
	Height	77.70 mm (3.06 in.)	7.56 mm (0.30 in.)	
	Width	295.20 mm (11.62 in.)	295.20 mm (11.62 in.)	
	Depth	7.56 mm (0.30 in.)	77.70 mm (3.06 in.)	
Temperature range:	•			
Operating		0°C to 70°C (32°F to 158°F)	0°C to 70°C (32°F to 158°F)	
	Storage	-20°C to 65°C (-4°F to 149°F)	-20°C to 65°C (-4°F to 149°F)	
Battery operating time		Varies depending on operating conditions and can significantly reduce under certain power-intensive conditions.	Varies depending on operating conditions and can significantly reduce under certain power-intensive conditions.	
Battery charging time (approximate) (i) NOTE: Control the charging time, duration, start and end time, and so on using the Dell Power Manager application. For more information on the Dell Power Manager see, Me and My Dell on www.dell.com.		 Standard charging: 3 hours, when computer is turned off ExpressCharge: 2 hours, when computer is turned off 	 Standard charging: 3 hours, when computer is turned off ExpressCharge: 2 hours, when computer is turned off 	
Coin-cell battery		CR2032	CR2032	
		1	<u> </u>	

CAUTION: Operating and storage temperature ranges may differ among components, so operating or storing the device outside these ranges may impact the performance of specific components.

Display

The following table lists the display specifications of your Alienware m15 R7 AMD.

Table 16. Display specifications

Descripti	ion	Option one	Option two	Option three
Display type		15.6-inch, Full-High Definition (FHD)	15.6-inch, Full-High Definition (FHD)	15.6-inch, Quad-High Definition (QHD)
Display-p	panel technology	Wide-Viewing Angle (WVA)	Wide-Viewing Angle (WVA)	Wide-Viewing Angle (WVA)
Display-p (active ar	panel dimensions rea):			
	Height	193.59 mm (7.62 in.)	193.59 mm (7.62 in.)	193.62 mm (7.62 in.)
	Width	344.16 mm (13.55 in.)	344.16 mm (13.55 in.)	344.22 mm (13.55 in.)
	Diagonal	394.87 mm (15.55 in.)	394.87 mm (15.55 in.)	394.94 mm (15.55 in.)
Display-p	panel native resolution	1920 x 1080	1920 x 1080	2560 x 1440

Table 16. Display specifications (continued)

Description	Option one	Option two	Option three
Luminance (typical)	300 nits	300 nits	400 nits
Megapixels	2.07	2.07	3.69
Color gamut	100% sRGB	100% sRGB	99% DCI-P3
Pixels Per Inch (PPI)	141	141	188.3
Contrast ratio (typ)	1000:1	1000:1	1000:1
Response time (max)	With Overdrive: 3 msWithout Overdrive: 8 ms	With Overdrive: 1 ms Without Overdrive: 3 ms	With Overdrive: 2 msWithout Overdrive: 6 ms
Refresh rate	165 Hz	360 Hz	240 Hz
Horizontal view angle	+/- 85 degrees	+/- 85 degrees	+/- 85 degrees
Vertical view angle	+/- 85 degrees	+/- 85 degrees	+/- 85 degrees
Pixel pitch	0.18 mm	0.18 mm	0.13 mm
Power consumption (maximum)	6 W	7.60 W	8.55 W
Anti-glare vs glossy finish	Anti-glare	Anti-glare	Anti-glare
Touch options	Not supported	Not supported	Not supported
Adaptive sync support	G-SYNC, FreeSync, Advanced Optimus	G-SYNC, FreeSync, Advanced Optimus	G-SYNC, FreeSync, Advanced Optimus

GPU—Integrated

The following table lists the specifications of the integrated Graphics Processing Unit (GPU) supported by your Alienware m15 R7 AMD.

Table 17. GPU—Integrated

Controller	Memory size	Processor
AMD Radeon Graphics	Shared system memory	AMD Ryzen 7/9

GPU—Discrete

The following table lists the specifications of the discrete Graphics Processing Unit (GPU) supported by your Alienware m15 R7 AMD.

Table 18. GPU—Discrete

Controller	Memory size	Memory type
NVIDIA GeForce RTX 3050 Ti	4 GB	GDDR6
NVIDIA GeForce RTX 3060	6 GB	GDDR6
NVIDIA GeForce RTX 3070 Ti	8 GB	GDDR6

Table 18. GPU—Discrete (continued)

Controller	Memory size	Memory type
NVIDIA GeForce RTX 3080 Ti	16 GB	GDDR6

Operating and storage environment

This table lists the operating and storage specifications of your Alienware m15 R7 AMD.

Airborne contaminant level: G1 as defined by ISA-S71.04-1985

Table 19. Computer environment

Description	Operating	Storage
Temperature range	0°C to 35°C (32°F to 95°F)	-40°C to 65°C (-40°F to 149°F)
Relative humidity (maximum)	10% to 90% (non-condensing)	0% to 95% (non-condensing)
Vibration (maximum)*	0.66 GRMS	1.30 GRMS
Shock (maximum)	110 G†	160 G†
Altitude range	-15.2 m to 3048 m (-49.87 ft to 10000 ft)	-15.2 m to 10668 m (-49.87 ft to 35000 ft)

CAUTION: Operating and storage temperature ranges may differ among components, so operating or storing the device outside these ranges may impact the performance of specific components.

^{*} Measured using a random vibration spectrum that simulates user environment.

[†] Measured using a 2 ms half-sine pulse.

Keyboard shortcuts of Alienware m15 R7 AMD

NOTE: Keyboard characters may differ depending on the keyboard language configuration. Keys that are used for shortcuts remain the same across all language configurations.

Some keys on your keyboard have two symbols on them. These keys can be used to type alternate characters or to perform secondary functions. The symbol shown on the lower part of the key refers to the character that is typed out when the key is pressed. If you press shift and the key, the symbol shown on the upper part of the key is typed out. For example, if you press **2**, **2** is typed out; if you press **Shift + 2**, @ is typed out.

The keys F1-F12 at the top row of the keyboard are function keys for multi-media control, as indicated by the icon at the bottom of the key. Press the function key to invoke the task represented by the icon. For example, pressing F1 mutes the audio (refer to the table below).

However, if the function keys F1-F12 are needed for specific software applications, multi-media functionality can be disabled by pressing $\mathbf{fn} + \mathbf{Esc.}$ Subsequently, multi-media control can be invoked by pressing \mathbf{fn} and the respective function key. For example, mute audio by pressing $\mathbf{fn} + \mathbf{F1}$.

NOTE: You can also define the primary behavior of the function keys (F1-F12) by changing **Function Key Behavior** in BIOS setup program.

Table 20. List of keyboard shortcuts

Keys	Description
FN + Fl	Disable/enable Full Speed Mode
$\begin{bmatrix} FN \end{bmatrix} + \begin{bmatrix} F7 & \\ & & \end{bmatrix}$	Adjust keyboard backlight brightness
FN + F8	Switch to external display
FN + F9 *	Launch the Windows Connect app to display Bluetooth devices
FN + FIO	Decrease display brightness
FN + FII ★	Increase display brightness
FN + F12	Disable/enable touchpad

Your computer comes with pre-programmable macro keys that enable you to perform multiple actions with a single key press.

Table 21. List of Macro keys

Keys	Description
F2 F	
F3 E	
F4 =	Macro keys NOTE: You can configure modes and assign multiple tasks for the macro keys on the keyboard.
F5_	
F6 ■	

Your computer comes with dedicated keys that enable you to control audio features of the computer with a single key press.

Table 22. List of keys to control audio features

Keys	Description
	Mute microphone
	Mute speakers
	Increase volume
	Decrease volume

Low blue light

WARNING: Prolonged exposure to blue light from the display may lead to long-term effects such as eye strain, eye fatigue, or damage to the eyes.

Blue light is a color in the light spectrum which has a short wavelength and high energy. Chronic exposure to blue light, particularly from digital sources, may disrupt sleep patterns and cause long-term effects such as eye strain, eye fatigue, or damage to the eyes.

The display on this computer is designed to minimize blue light and complies with TÜV Rheinland's requirement for low blue light displays.

Low blue light mode is enabled at the factory, so no further configuration is necessary.

To reduce the risk of eye strain, it is also recommended that you:

- Position the display at a comfortable viewing distance between 20 and 28 inches (50 and 70 cm) from your eyes.
- Blink frequently to moisten your eyes, wet your eyes with water, or apply suitable eye drops.
- Look away from your display, and gaze at a distant object at 20 ft (609.60 cm) away for at least 20 seconds during each break.
- Take an extended break for 20 minutes every two hours.

Alienware Command Center

Alienware Command Center (AWCC) provides a single interface to customize and enhance the gaming experience. The AWCC dashboard displays most recently played or added games, and provides game-specific information, themes, profiles, and access to computer settings. You can quickly access settings such as game-specific profiles and themes, lighting, macros, and audio that are critical to the gaming experience.

AWCC also supports AlienFX 2.0. AlienFX enables you to create, assign, and share game-specific lighting maps to enhance the gaming experience. It also enables you to create your own individual lighting effects and apply them to the computer or attached peripherals. AWCC embeds Peripheral Controls to ensure a unified experience and the ability to link these settings to your computer or game.

This computer features the following AlienFX Lighting Zones:

- keyboard
- AlienHead power button
- AlienHead LED on the back of the display
- (i) **NOTE:** AlienFX lighting supports up to 16.8 million distinct colours.
- (i) NOTE: Information about the location of AlienFX Lighting Zones on your computer is available in AWCC.

AWCC supports the following features:

- FX: Create and manage the AlienFX zones.
- Fusion: Includes the ability to adjust game-specific Power Management, Sound Management, and Thermal Management features.
- Peripheral Management: Enables peripherals to appear in and be managed in Alienware Command Center. Supports key
 peripheral settings and associates with other functions such as profiles, macros, AlienFX, and game library.

AWCC also supports Sound Management, Thermal Controls, CPU, GPU, Memory (RAM) monitoring. For more information about AWCC, see the *Alienware Command Center Online Help* or search in the Knowledge Base Resource at www.dell.com/support.

Getting help and contacting Alienware

Self-help resources

You can get information and help on Alienware products and services using these online self-help resources:

Table 23. Alienware products and online self-help resources

Self-help resources	Resource location	
Information about Alienware products and services	www.alienware.com	
My Dell app	Dell	
Tips		
Contact Support	In Windows search, type Contact Support , and press Enter .	
Online help for operating system	www.dell.com/support/windows	
Access top solutions, diagnostics, drivers and downloads, and learn more about your computer through videos, manuals and documents.	Your Alienware computer is uniquely identified by a Service Tag or Express Service Code. To view relevant support resources for your Dell computer, enter the Service Tag or Express Service Code at www.dell.com/support . For more information on how to find the Service Tag for your computer, see Locate the Service Tag on your computer .	
Videos providing step-by-step instructions to service your computer	www.youtube.com/alienwareservices	

Contacting Alienware

To contact Alienware for sales, technical support, or customer service issues, see www.alienware.com.

- (i) NOTE: Availability varies by country/region and product, and some services may not be available in your country/region.
- (i) NOTE: If you do not have an active Internet connection, you can find contact information about your purchase invoice, packing slip, bill, or Dell product catalog.