



APC Service Bypass Unit for SRYL, 200/208/230/240V, 125A, MBB, Hardwire Input/Output

SRYLSBP20KP

_			•	
()	VР	rvi	ı٩١	M

Lead time Usually in Stock

Main

product or component type Bypass module

Physical

Colour	Black and silver
Height	6.9 in (175 mm)
Width	17.008 in (432 mm)
Depth	29.7 in (755 mm)
net weight	50.7 lb(US) (23 kg)
mounting mode	Rack-mounted

Input

Max line current 125 A

Environmental

Ambient air temperature for operation	32.0000000000104.0000000000 °F (040 °C)
Operating altitude	03000 m
Ambient air temperature for storage	-22.0000000000158.00000000000 °F (-3070 °C)
Storage altitude	0.00000000049212.6 ft (015000 m)

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11.8 in (30 cm)
Package 1 Width	22.8 in (58 cm)
Package 1 Length	38.2 in (97 cm)
Package 1 Weight	71.7 lb(US) (32.5 kg)

Contractual warranty

Warranty 5 YR

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance



Rohs Exemption Information

Yes

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information