



### Overview

- 4-megapixel resolution
- 3D DNR
- WDR of 120dB
- PoE (Power over Ethernet)
- IR Range up to 30m
- H.265
- Weather Proof Rating: IP67
- Analytics: Line Cross & intrusion detection
- Vandal Proof: IK 10 Rated
- Built-in Micro SD card slot
- Video Insight VMS license included








### Technical Specifications

<b>Device</b>	
Image Sensor:	1/3" Progressive Scan CMOS
Min Illumination:	0.01 lux@F1.2: AGC ON   0 lux with IR
Shutter Time:	1/30s ~ 1/100,000s
Lens:	2.8mm
WDR:	WDR 120dB
Angle of View:	103.0°H, 58.0°V, 123.0°DIAG
Lens Mount:	M12
Angle Adjustment:	Pan: 0° ~ 355°, tilt: 0° ~ 75° rotate: 0° to 355°
3-Axis Adjustment :	Yes
Day & Night:	IR cut filter with auto switch   Wavelength: 850nm
<b>Compression Standard</b>	
Video Compression:	H.265, H.264+, H.264
Bit Rate:	256 Kbps ~ 16 Mbps
Three Stream:	Yes
Analytics:	Line Cross and Intrusion detection
<b>Image</b>	
Max. Image Resolution:	2688 × 1520@30fps
Frame Rate: Main Stream	30fps (2688 × 1520, 2560 × 1440, 2304 × 1296, 1920 × 1080)
ROI Codec:	Supported
Image Setting:	BLC, Rotate Mode, Saturation, Brightness, Contrast, Sharpness adjust by VI software or Camera Firmware
<b>Network</b>	
Alarm Trigger:	Tampering alarm, Network disconnect, IP address conflict, Storage exception
Protocols:	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos (SIP, SRTP, IPv6, Bonjour)
Security:	User authentication, watermark
<b>Interface</b>	
Communication Interface:	1 RJ45 10 M/100 M Ethernet interface
System Compatibility:	ONVIF, PSIA
Local Storage:	Built-in Micro SD card slot, up to 128GB
<b>General</b>	
Operating Conditions:	-22° F – 140° F (-30°C ~ 60°C ) Humidity 95% or less
Power Consumption:	MAX: 6 W



### Technical Specifications

Impact Protection:	IK10		
Power Supply:	12 VDC ± 25%, PoE (802.3af)		
IR Range:	(Up To: 30 meters)		
DNR:	3D DNR		
Dimensions:	Φ111 × 82 (4.4" × 3.2")		
Weight:	1.3 lbs. (500g)		
Software:	Includes Video Insight VMS License		
Warranty:	4 Year Advanced Replacement		
Accessories:	<p>A-MD-ICM</p> 	<p>A-MD-WM</p> 	<p>A-MWM-Mini</p> 
	<p>A-34-Cap Metal</p> 	<p>A-MD-GBA</p> 	<p>A-Pole Mount</p> 