

Cyber-shot® Digital Still Camera

DSC-HX1

PRELIM

The Sony® Cyber-shot® DSC-HX1 camera with Exmor™ CMOS technology offers up to 10fps shooting and features Sweep Panorama mode – that can seamlessly combine multiple shots to produce striking images, advance modes that reduce noise by approximately 50% even in difficult shooting situations, as well as 1080p movie recording6. Additionally it features professional quality 20x wide angle G-lens, 3″ titable LCD¹ and Intelligent Auto mode

- 9.1 Megapixel Super Exmor[™] CMOS Image Sensor: The HX1 features a 9.1 megapixel Exmor[™] CMOS image sensor that brings out the full resolving power of the camera's precision G-Lens to deliver extremely fast speed, high resolution, and stunning low-light sensitivity with improved image clarity and drastically reduced noise. With 9.1 megapixels, you can create stunning, photo-quality prints up to A3+ (13x19[°]) size, or crop your images and still come away with high resolution shots.
- Professional Quality G-Lens: Designed and manufactured to the highest standards of optical performance, the Sony G-Lens is optimized to perfectly complement the advanced image sensors and image processing technology in Sony's cameras. G lenses are used in top of the line digital single lens reflex (DSLR) cameras and advanced pro-sumer HD Camcorders. Capture the action up close with the 20x optical zoom, and with the 28mm wide angle lens the HX1 even allows you to capture more of the scenes in landscape or group portraits. The HX1's G Lens has a six blade aperture capable of producing a beautiful bokeh (beautifully defocused backgrounds with a soft natural feel). The aspherical lens elements made from ED (extra-low dispersion) minimize chromatic aberration common to highmagnification lenses.
- 20x High Zoom:
 20x optical zoom extends your reach and helps bring you closer to the action

 a real benefit for sporting events,
 wildlife, distant landscape views and dramatic portrait shots.
- 28mm Wide Angle Lens: Widen your view and capture more of the city, landscape, or group with a 28mm wide angle G lens.

 = 3.0" Clear Photo LCD[™] tilt display (230k pixels): Compose and show off your images

on the large 3.0"¹ (230K) Clear Photo LCD Plus[™] display, which tilts up or down approximately 90 degrees for easier high and low angle shooting and features a special anti-reflective coating for sharp visibility, even in bright sunlight.

- CMOS Sensor: Enjoy extremely high resolution, fine tonal gradation and fast speed that faithfully reproduces every detail of your subject and reduces visual noise. The Exmor[™] CMOS sensor brings out the full potential of the lens to ensure clear, high-precession image quality.
- BIONZ[™] image processor: The BIONZ[™] image processor delivers the high resolution and fast performance you expect from a Sony[®] digital camera.
- Colors available in: The Cyber-shot® DSC-HX1 camera is available in black.
- High Speed Shooting (10fps): The HX1 is the world's first digital still camera that can capture full 9.1 megapixel resolution images at up to 10 fps, helping to ensure you never miss the decisive moment. What's more, the HX1 employs a mechanical shutter that helps reduce distortion when continuously shooting moving subjects.

ADDITIONAL FEATURES

- Sweep Panorama Mode:
- Handheld Twilight Mode:
- Anti-Motion Blur Mode:
- HD Movie (1080p):
- Intelligent Auto Mode:
- Intelligent Scene Recognition:
- Face Detection technology:

- Selected Face Memory:
- Anti-blink Function:
- Red-eye Reduction:
- Smile Shutter™ Technology:
- Double Anti-blur Solution:
- Optical SteadyShot[™] Image Stabilization:
- High Sensitivity Mode (ISO 3200):
- Dynamic Range Optimizer Standard and Plus:
- Convenient Photo Modes:
- 9-Point Auto Focus:
- Function Guide:
- Intelligent Auto Focus:
- Functional Button Layout:
- Simplified Buttons:
- Easy Shooting Mode:
- = 16:9 High Resolution Mode:
- Memory Stick Duo[™] Media Convenience:
- Stamina® Battery Power:
- Easy Image Management:
- HDTV Compatibility:
- BRAVIA® Sync[™] :
- PhotoTV HD:
- Wide Zoom tilt display:
- PHOTOMUSIC feature:
- In-Camera Retouching Tools:
- Multi-purpose Resize function:
- Picture Motion Browser ver. 4.2.02:











SONY

Cyber-shot® Digital Still Camera

DSC-HX1

Specifications

- Megapixel: 9.1 MP Imaging Device: 1/2.4 type(7.63mm) Exmor CMOS
- Sensor Recording Media: 11MB internal Flash Memory, optional Memory Stick Duo[™] Media, optional Memory Stick PRO Duo[™] Media

- White Balance: Auto / Davlight / Cloudy / Fluorescent 1 (White Fluorescent Lighting) / Fluorescent 3 (Day White Fluorescent Lighting) / Fluorescent 3 (Day White Fluorescent Lighting) / Incandescent / Flash / Underwater White Balance Mode - Auto, Underwater
- Memory Stick PRO[™] Media Compatibility: Tested to support up to 16GB Memory Stick DUO PRO[™] media capacity¹; does not support Access Control security function.
- Still Image Mode(s): Normal/High Speed Burst (High/Med/Low)/Bracketing(JPEG)-AE (Plus/Minus0.3EV/0.7EV/1.0EV)/WB/Color
- Red-Eye Reduction: Auto / On / Off Burst Mode: Approx 10 fps (10 shots) Date/TimeStamp: Available in the included PMB
- software. Media/BatteryIndicator: Yes/Yes
- Color Mode(s): Normal / Vivid / Sepia / B&W / Real

Histogram Display: Yes

- Real Imaging Processor™ Technology: BIONZ™ AF Illuminator Light: Auto / Off PictBridge Compatible: Yes Multi-Pattern Measuring: Yes SteadyShot® Image Stabilization: Optical NightShot® Infrared System: No
- NightFramingSystem: No
- Clear RAW NR: Yes
- Scene Mode(s): iAuto, Easy, Program, Handheld Twilight, Anti-Motion Blur, Sweep Panorama, Manual Exposure, Aperture Priority, Shutter Speed Priority and Scene Selection such as High Sensitivity, Landscape, Soft Snap, Advanced Sports Shooting, Twilight Portrait, Twilight, Beach, Snow, Fireworks, and Gourmet
- Movie Mode(s): 1280 x 720 (Standard) (Approx.30 fps, Progressive) / 1280 x 720(Approx.30fps, Progressive) / 1440 x 1080(Fine) (Approx.30fps, Progressive) / 1440 x 1080(Standard) (Approx.30fps, Progressive) / VGA (640 x 480, Approx.30fps, Progressive)
- Power Save Mode: Yes (after approx. 3 min. of inactivity) In-Camera Editing: Trimming / Red Eye Correction / Soft Focus / Partial Color / Fisheye Lens / Cross Filter / Retro / Radial Blur / Unsharp Masking / Smile Dynamic Range Optimizer: Standard / Off / Plus

Inputs and Outputs

Accessory Terminal: Multi connector Audio/Video Output(s): Yes via Mutli-Use Connector USBPort(s): Yes · USB2.0 Hi-Speed HD Output: Yes (1080i)

LCD: 3.0"1 Clear Photo LCD Plus (230,400 pixels) Viewfinder: Yes · Electrical Lens Construction: 13 elements in 10 groups (including 1ED glass element and 1aspheric element)

Microphone/Speaker: Stereo / Mono Lens Type: Sony G-Lens

Operating Conditions

- Flash Effective Range: ISO Auto: Approx. 0.3 Approx. 9.2m (Approx. 0.98' Approx. 30.2') (W) / Approx. 1.5 -Approx.5.1m (Approx. 4.92' Approx. 16.7') (I), ISO3200: up to Approx.16m(Approx. 32.5') (W) / Approx.10m(Approx.32.8') (D')
- Flash Mode(s): Auto / Flash On / Slow Syncro / Flash Off

FocalLength: 5.0-100.0mm

35mm Equivalent: Still shots: 28-560mm / Movie 16:9: 31-620mm / Movie 4:3 :38-760

- Focus: 9 points / Center Weighted AF / Flexible Spot / Semi Manual / Manual
- Aperture Range: Auto(F2.8-F8.0) / Program Auto(F2.8-F8.0) / Manual(F2.8-F8.0)
- Shutter Speed: Auto (2" · 1/4,000) / Program Auto (1" · 1/4,000) / Shutter Priority (30" · 1/4000) / Aperture Priority (8" · 1/2000) / Manual (30" · 1/4000)
- Exposure Compensation: Plus / Minus 2.0EV, 1 / 3EV step ISO: Auto / 125 / 200 / 400 / 800 / 1600 / 3200 Smart Zoom® Technology: 5M:Approx.26x(Total)
- 3M:Approx.33x(Total), VGA:Approx.108x(Total), 16:9 (2M):Approx.36x(Total)
- Digital Zoom: Smart Zoom / Precision Digital Zoom / Off Optical Zoom: 20x
- Macro Mode: Macro On/Auto: W:Approx.1cm(0.03') to Infinity, T:Approx.150cm(4.92') to Infinity Total Zoom: Approx. 40x

Face Detection: Detects up to 8 Faces - with Touch Priority / Auto Priority / Child Priority / Adult Priority

BatteryType: InfoLITHIUM H type 6.8V BatteryCapacity: Approx. 195 minutes / Approx. 390 images

Supplied Software: Picture Motion Browser Vers 4.2.02 + USB Driver (Not supported by Macintosh® Operating Systems)

Operating System Compatibility: Microsoft® 2000 Professional, XP Home and Professional; Macintosh® OS 9.1/9.2/OS X (10.1-10.5)

Bionz[™] Engine: Yes

- Weight: Approx. 1.8oz. (504g) · With battery and Memory Stick media.
- Measurements: W x H x D: 114.5mm x 82.8mm x 91.8mm (45/8" x 33/8" x 35/8")

Service and Warranty Information

Limited Warranty Term: Limited 1 Year Parts & Labor

Supplied Accessorie

RechargeableBattery · NP·FH50 Battery Charger - BC-VH1 Multi Connector Cable - USB, AV Power Cord Shoulder strap Lens Cap Lens Cap Strap HDMI Adaptor CD-ROM Software Note: No Memory Stick PRO Duo[™] Media or adaptors are included.

Optional Acce

GPS Unit Kit (GPS-CS1KA Memory Stick PRO Duo[™] Media (MS-MT2G) Memory Stick PRO Duo[™] Media (MS-MT4G) Memory Stick PRO Duo[™] Media (MS-MT8G) Memory Stick PRO Duo™ Media (MS-MT16G) Memory Stick Duo[™] Adaptor (MSAC-M2) Memory Stick Duo[™] USB Adaptor (MSAC-US40) Color: Black

UPC Code: 027242767171



- Viewable area, measured diagonally
 Compatible BRAVIA® HDTV, and component cable (sold separately) required for PhotoTV HD viewing.
- Companies extracks stored in internal memory. Imported music tracks can be up to five minutes long. When using Music Transfer to download music, tracks longer than five minutes will be reduced to five minutes will be loading to the Cybershold camera.
 Requires Windows 2000 Professional SP4, Windows XP SP2, or Windows Vista. Not supported by Mac 200
- OS
- 5.D. 5.D. Viewing requires an HD output adapter cable (VMC-MHC2), sold separately. 6.Maximum of 29 minutes continuous recording per video clips, limited to available capacity on
- storage media.
- 3. Nuder average conditions; when fully charged, actual results may vary based on camera settings and conditions of use. 8. Requires BRAVIA® Sync™ feature in each product. Please refer to BRAVIA and/or Remote owner's
- manual to determine compatibility. 11.For uploading movies to Internet sharing sites, movies can be converted to SD image quality with Picture Motion Browser, or record in VGA resolution (640 x 480, 3Mbps).

© 2009 Sony Electronics Inc. All rights reserved. Reproduction in whole or in part without written permission is prohibited. Sony, Cybershot, Xtra Fine LCD, BIONZ, Smile Shutter, Optical Steadyshot, Memory Stick PRO Duo, HDNA, Super HAD, Stamina, and the Sony, Cybershot, SteadyShot, Smile Shutter, Face Detection, BIONZ, and HDNA logos are trademarks of Sony. All other trademarks are trademarks of their respective owners. Non-metric weights and measurements are approximate and may vary.

> Please visit the Dealer Network for more information at www.sony.com/dn

1, Underwater 2, Flash SelfTimer: Yes (10 seconds, 2 seconds, Off)