


# 4XEM™ Product Data Sheet

## 20FT DisplayPort 1.4 to DisplayPort 1.4 M/M 8K@60Hz Cable



*Expertly engineered to deliver dependable 8K video clarity and consistent performance in professional, AV, and multi-display environments.*

### Key Features



Latching DP Connectors




32.4Gbps Max Bandwidth



Max 8K@60Hz resolution (DSC)



HDCP 2.2 support and 3D video



Backward compatible



MST and DSC supported

### Technical Highlights

|                      |  |
|----------------------|--|
| SKU Name             | 4XDPDPCBL20                                      |
| Warranty             | Lifetime   |
| DisplayPort Standard | DisplayPort 1.4                                  |
| Certifications       | Certified RoHS, REACH, CE, UL VESA 1.4 Compliant |

### Application(s)

Designed for corporate offices, control rooms, and professional AV environments, this cable supports dependable 8K video transmission between workstations, monitors, and display systems.

Visit [4XEM.com](http://4XEM.com)

Contact Brandon Hegarty 4XEM Sales Manager  
1-866-999-4936 ext.113 [bhegarty@4xem.com](mailto:bhegarty@4xem.com)

# 4XEM™ Product Data Sheet

## Technical Specifications

|                          |   |  |
|--------------------------|---|--|
| Warranty Information     | Warranty  | Lifetime   |
| Hardware                 | Active or Passive cable<br>Chip ID<br>Direction<br>Cable Jacket Type<br>Cable Shield Type<br>Connector Plating<br>Fire Rating<br><br>Number of Conductors<br>Certifications   | Passive<br>N/A<br>Bidirectional<br>PVC - Polyvinyl Chloride<br>Triple Aluminum-Mylar Foil with Braid<br>Gold<br>CMG Rated (General Purpose)<br>VW-1 (Vertical Wire Flame Test)<br>20<br>Certified RoHS, REACH, CE, UL<br>VESA 1.4 Compliant  |
| Connector(s)             | Connector A<br>Connector B  | 1x DisplayPort Male with latch<br>1x DisplayPort Male with latch   |
| Performance              | Standard<br>Bandwidth<br>Effective Data Rate<br>Backwards Compatibility<br>Display Stream Compression (DSC)<br>Supported Resolution(s)<br><br>Multi-Stream Transport (MST)<br>Audio Support<br>3D Support<br>HDCP Support | DisplayPort 1.4 (HBR3)<br>32.4 Gbps (DisplayPort 1.4)<br>25.92 Gbps<br>Supported<br>Supported (DSC 1.2)<br>8K @ 60Hz (7680 × 4320) with DSC]<br>4K @ 120Hz (with DSC)<br>4K @ 144Hz (with DSC)<br>5K @ 60Hz<br>Maintain existing lower resolutions<br>Supported (DP 1.4 compliant)<br>Up to 8-channel LPCM / Compressed Audio (device-dependent)<br>Yes<br>HDCP 2.2 (if supported by host) |
| Physical Characteristics | Color<br>Cable Length<br>Cable OD<br>Wire Gauge<br>Connector Style<br>Product Height<br>Product Length<br>Product Width<br>Weight of Product  | Black<br>20 ft [6.096 m]<br>0.3 in [6.5 mm]<br>28 AWG<br>Latching<br>0.5 in [12.7 mm]<br>4 in [101.6 mm]<br>4.75 in [120.65 mm]<br>13.00 oz [368.54 g]   |
| Packaging Information    | Packaging Type<br>Package Height<br>Package Width<br>Package Length<br>Shipping (Package) Weight  | Poly-bag<br>8.66 in [220 mm]<br>7.09 in [180 mm]<br>1.10 in [28 mm]<br>13.00 oz [368.54 g]   |
| What's in the Box        | Included in Package   | 1x DisplayPort Male to DisplayPort Male Cable  |

### Notes

- \* Product appearance and specifications are subject to change without notice.
- \* Weights and measurements are approximate.