Product data sheet

Specifications





APC Home Office SurgeArrest 12 Outlets, 120V

PH12

! Discontinued on: Apr 30, 2024

! To be discontinued

Overview

Lead time Usually in Stock

Main

Main Input Voltage	120 V
Input Connection Type	NEMA 5-15P
Cable length	6 ft (1.8 m)
Number of cables	1
Provided equipment	User Manual

Physical

Color	Black
Height	1.2 in (3 cm)
Width	3.03 in (7.7 cm)
Depth	12.09 in (30.7 cm)
Net Weight	1.48 lb(US) (0.67 kg)
Mounting preference	No preference
Mounting Mode	Not rack-mountable

Input

Maximum Line Current per phase	15 A
Input Frequency	50/60 Hz
Maximum Input Current per Phase	15 A
Switching current capacity	15 A

Output

Number of power socket outlets	12
Outlet standard	NEMA 5-15R

Conformance

Product Certifications	MET USA	
	MET Canada	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Jul 27, 2024 Life Is On Schneider 1

Standards	UL 1363 UL 1449
Equipment protection policy	Lifetime : \$150000

Environmental

Ambient Air Temperature for Operation	32.0000000000104.0000000000 °F (040 °C)
Relative Humidity	095 % non-condensing
Operating altitude	010000 ft
Ambient Air Temperature for Storage	5.0000000000113.0000000000 °F (-1545 °C)
Storage Relative Humidity	095 % non-condensing
Storage altitude	050000 ft (0.000000000015240.0000000000 m)

Surge Protection and Filtering

NM Surge Response Time (ns)	1 ns common mode
Common mode rejection	40 dB
Peak current	56 kAcommon mode 28 kAnormal mode
Surge energy rating	2160 J

Ordering and shipping details

GTIN 731304732860

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.9 in (4.8 cm)
Package 1 Width	13.2 in (33.5 cm)
Package 1 Length	5.7 in (14.5 cm)
Package 1 Weight	1.70 lb(US) (0.77 kg)
Number of Units in Package 2	6
Package 2 Height	12.6 in (320.04 mm)
Package 2 Width	6.3 in (160.02 mm)
Package 2 Length	13.78 in (350.01 mm)
Package 2 Weight	11.04 lb(US) (5.008 kg)
Number of Units in Package 3	324
SCC14	10731304335945

Contractual warranty

Warranty Lifetime



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	End of Life Information
California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov