

Key Features

SuperClear IPS | A More Comfortable Workspace | Environmentally Friendly Packaging | Convenient & Versatile Stand | Loaded with Connectivity



Product Description

Designed for the modern day office, the ViewSonic® VG2748 monitor delivers an efficient end-to-end enterprise experience. Featuring SuperClear® IPS panel technology and 1080p resolution, this 27" monitor delivers crisp and clear images from nearly any viewing angle. For enhanced productivity, an advanced ergonomic design offers a wide range of customizable adjustments for maximum comfort including pivot, swivel, height adjustment, and tilt. With the ability to tilt an impressive 40-degrees, the VG2748 is ideal for users who prefer to work while standing up, as well as for those who like to use their screen for group discussions. Versatile connectivity options include HDMI, DisplayPort, VGA, and USB 3.0. This monitor is also shipped in eco-friendly biodegradable packaging, along with an easy-to-install quick release stand that makes for simple out-of-the box setup. The quick release stand also includes an integrated client mount and cable management features, making this monitor perfect for deployment in cloud-based environments.



Contact Sales

- call: 888.881.8781
- email: salesinfo@viewsonic.com
- visit: viewsonic.com

Display:	
Display Size (in.):	27
Viewable Area (in.):	27
Panel Type:	IPS
Resolution:	1920 x 1080
Static Contrast Ratio:	1,000:1
Dynamic Contrast Ratio:	50,000,000:1
Light Source:	WLED
Brightness:	300 cd/m2
Colors:	16.7M
Color Space Support:	6 bits
Aspect Ratio:	16:9
Response Time (Typical GTG):	14ms
Response Time (GTG w/OD):	7ms
Viewing Angles:	178° horizontal, 178° vertical
Backlight Life (Hours):	30,000
Panel Surface:	Anti-glare, Hard coating (3H)

Compatibility:	
PC Resolution (max):	1920 x 1080
Mac® Resolution (max):	1920 x 1080

Connector:
USB 3.0 Type A(4), USB 3.0 Type B(1), VGA(1), HDMI 1.4(1), Display Port(1)

Audio:	
Internal Speakers:	2W (x2)

Power:	
Eco Mode (Conserve):	18.5W
Eco Mode (optimized):	23.1W
Consumption (typical):	29.2W
Consumption (max):	66.5W
Voltage:	AC 100-240V (universal), 50-60Hz
Stand-by:	0.5W
Power Supply:	Internal

Additional Hardware:	
Kensington Lock Slot:	1

Controls:	
Physical Controls:	1,2,3,4,5,Power
On Screen Display:	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)

Operating Conditions:	
Temperature:	32-104° F (0 - 40° C)
Humidity (non-condensing):	20-90%

Mount:	
VESA Compatible:	100 x 100 mm

Video Signal:	
Frequency Horizontal:	24 ~ 82KHz
Frequency Vertical:	50 ~ 75Hz

Video Input:	
Digital Sync:	TMDS for HDMI, PCI-E for DisplayPort

Ergonomics:	
Height Adjust (mm):	130
Swivel:	120°
Pivot (Right/Left):	90° / 90°
Tilt (Forward/Back):	40° / 5°

Weight (imperial):	
Net (lbs):	16.1
Net Without Stand (lbs):	10.8
Gross (lbs):	22.3

Weight (metric):	
Net (kg):	7.3
Net Without Stand (kg):	4.9
Gross (kg):	10.1

Dimensions (imperial) (WxHxD):	
Packaging (in.):	27.2 x 16.9 x 8.5
Physical (in.):	24.5 x 16.0 x 8.0
Physical Without Stand (in.):	24.5 x 14.4 x 2.0

Dimensions (metric) (WxHxD):	
Packaging (mm):	692.0 x 430.0 x 218.0
Physical (mm):	620.7 x 407.2 x 202.2
Physical Without Stand (mm):	620.7 x 366.1 x 51.1

General:
Regulations: CTUVus, FCC-B, ICES003, Energy Star 7.0 , EPEAT, TUV Mexico CoC, Mexico Energy
PACKAGE CONTENTS: VG2748 Display, Power Cable, DP to DP Cable, USB 3.0 Upstream Cable, Quick Start Guide
Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.
Warranty: Three-year limited warranty on parts, labor and backlight
UPC: 766907000764

Accessories:
CB-00008948, CB-00009950, CB-00010684, CB-00010958, LCD-CMK-001, LCD-EE-27-03, LCD-EEEW-27-01, LCD-EEEW-27-02, LCD-EW-27-01, LCD-EW-27-02, LCD-EW-27-03, LCD-WMK-001, ViewSplit