

ThinkStation P330 Tiny Platform Specifications

Product Specifications Reference (PSREF)

Components	Specification	Components	Specification		
Machine Type	MT 30CF for Transactional model and MT 30CE for Relationship model. For configuration of all 30CF EMEA and US models, please visit: http://psref.lenovo.com/Product/ThinkStation/ThinkStation_P330_Tiny	Intel vPro Technology	Supports vPro on models with the following processors: Core i7-8700T, Core i7-8700, Core i5-8600T, Core i5-8600, Core i5-8500T, Core i5-8500. vPro also requires Wireless-AC 9560 if Wi-Fi is needed		
Form factor	1L. Optional VESA mount bracket kit, supports VESA 75mm and 100mm. Optional floor stand for vertical orientation. Optional tool-less chassis open. Optional dust filter	Systems management	Intel Active Management Technology 12 on vPro models, Intel Standard Manageability on other models		
Dimensions	Height: 179 mm (7.0 in). Width: 36.5 mm (1.437 in). Depth: 182.9 mm (7.2 in)	Base warranty	US models comes with 3-year limited onsite service with 9x5/NBD. 1 or 3-year limited onsite service with 9x5/NBD in EMEA or other GEOs		
Weight	Maximum configuration: 3.08 lb (1.4kg)	HD Audio	Intel HD Audio interface with Realtek ALC233 Codec		
Supported TIO monitors	Tiny-in-One 23 (MT: 10DQ). Tiny-in-One 22 (MT: 10LK). Tiny-in-One 24 (MT: 10LL). Tiny-in-One22 Gen3 (MT: 10R1). Tiny-in-One22 Gen3 Touch (MT: 10R0). Tiny-in-One24 Gen3 (MT: 10QY). Tiny-in-One24 Gen3 Touch (MT: 10QX).	Front standard ports	1x USB 3.1 Gen 1 Type A (charging). 1x USB 3.1 Gen 1 Type-C. 1x Mic-in. 1x Combo jack		
		Rear standard ports	2x USB 3.1 Gen 2 Type A. 2x USB 3.1 Gen 1 Type-A. 1x RJ-45. 1x DP. 1x HDMI		
		Optional rear ports - via punch out cable	Up to two optional rear ports via punch out cable. Port 1 supports one of the following: 1x USB 3.1 Gen 1 Type-C, also supports DP function. 1x COM. 1x VGA. 1x DP. 1x HDMI. Port 2 supports one COM		
		Optional rear ports - via PCIe adapter	Supports one of the following: 4x miniDP with Quadro P620 or P1000, 35W processor models only 2x USB 3.1 Gen 1. 4x RJ-45 GbE with Intel I350-T4. 4x COM <i>Note: Punch out cable and PCIe adapter are mutually exclusive</i>		
		Temperature	Operating: 50 °F to 95 °F (10 °C to 35 °C) Non operating (with package): -40 °F to 140 °F (-40 °C to 60 °C)		
Processor	Up to one Intel Core family processor, i7, i5, or i3. Core i7 supports 65W or 35W, 6 cores, up to 3.2GHz, 12MB cache, DDR4-2666 memory speed. Core i5 supports 65W or 35W, 6 cores, up to 3.1GHz, 9MB cache, DDR4-2666 memory speed. Core i3 supports 65W, 62W, or 35W, 4 cores, up to 3.7GHz, 6MB or 8MB cache, DDR4-2400 memory speed.	Altitude	Operating: -15.2 m (-50 ft) to 3048 m (10 000 ft). Storage: -15.2 m (-50 ft) to 10, 668 m (35 000 ft)		
Chipset	Intel Q370 Chipset	Humidity	Operating: 20%~80%, non-condensing Storage (with package): 20%~90%, non-condensing		
Memory	2 DIMM sockets. DDR4-2666. SoDIMM. Non-ECC	Environmental certification	RoHS-compliant. GREENGUARD. EPEAT Gold rating and ENERGY STAR 7 qualified		
Expansion slots	One PCIe 3.0 x16 (negotiable link width x8) slot, low profile. When PCIe adapter is installed, a specific riser card is required	Power supply	Supports one 135W power adapter, 100V - 240V, 88% PSU		
Graphics	65W or 62W processor models supports processor graphics only. 35W processor models come with processor graphics plus a discrete graphics adapter	ISV certifications	Please visit www.thinkworkstations.com/isv-certifications/		
Graphics - Processor graphics	Integrated Intel UHD Graphics 630. Works along with discrete graphics to support multi-display				
Graphics - Discrete graphics card	One of the following discrete graphics cards on 35W processor models:				
	Adapter	Cores	Memory	Power	Connectors
	Quadro P620	512	2GB GDDR5	40W	4x miniDP
Quadro P1000	640	4GB GDDR5	47W	4x miniDP	
Storage controllers	Integrated Intel SATA AHCI controller in chipset, 6Gbps SATA, one onboard SATA port for 2.5" HDD				
Internal storage bay	Up to one 2.5" HDD on 65W processor models. 35W processor models cannot support HDD				
Disks	2.5" HDD supports up to 1TB, 6Gbps SATA, 7.2K or 5.4K				
M.2 slot for SSD	Two onboard M.2 slots for M.2 SSD, one for M.2 2280 SSD, one for M.2 2280 or 2242 SSD				
M.2 SSD	M.2 2280 SSD supports up to 1TB each, PCIe 3.0 x4, NVMe, optional Opal. M.2 2242 SSD supports up to 128GB, PCIe 3.0 x2, NVMe				
M.2 slot for Wi-Fi and Bluetooth	One dedicated M.2 2230 slot for optional Wi-Fi card, supports one of the following: Intel Wireless-AC 9560, 2x2, 2.4GHz/5GHz (160MHz channels), 802.11ac, Bluetooth 5, up to 1.73Gbps. Intel Wireless-AC 8265, 2x2, 2.4GHz/5GHz, 802.11ac, Bluetooth 4.2, up to 867Mbps. <i>Note: Wi-Fi card, or specific functions of Wi-Fi card may not be supported in some countries</i>				
Wi-Fi antenna	Optional Tiny 2.4GHz/5GHz SMA antenna kit				
Optical	Optional one 9.0mm optical drive via optical drive kit, DVD-ROM or DVD±RW. VESA mount is required				
Media reader	None. Using USB adapter				
Network interfaces	One onboard GbE port via integrated gigabit ethernet Intel i219LM, supports Wake-on-LAN. Optional Intel i350-T4 for 4x GbE ports, using PCIe slot				
Security features	Power-on and admin password. Trusted Platform Module, TCG 2.0 compliant. Chassis intrusion switch. Optional Kensington lock				