



APC Smart-UPS, Line Interactive, 2200VA, Tower, 120V, 8x NEMA 5-15R+2x NEMA 5-20R outlets, SmartSlot, AVR, LCD

SMT2200US

### Overview

Lead time	Usually Ships within 2 Weeks
Main	
Main Input Voltage	120 V
Main Output Voltage	120 V
Rated power in W	1920 W
Rated power in VA	1920 VA
product or component type	Uninterruptible power supply (UPS)
Input Connection Type	NEMA 5-20P
output connection type	8 NEMA 5-15R 2 NEMA 5-20R
Cable length	6 ft (1.8 m)
Number of cables	1
Battery type	Lead-acid battery
Provided equipment	CD with software

Documentation CD

USB cable

Smart UPS signalling RS-232 cable

### **Batteries & Runtime**

Run Time	View Runtime Graph ☐
Efficiency	View Efficiency Graph ☐
Extended runtime	0
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 h
Number of battery replacement quantity	1
Battery life	35 year(s)
Replacement battery	RBC55 □
Battery charger power	233 W rated

#### General

Number of power module filled

slots

Number of power module free slots	0
product web sub-family	TAA Compliant
Redundant	No

# **Physical**

•	
Colour	Black
Height	17.008 in (43.2 cm)
Width	7.7 in (19.6 cm)
Depth	21.4 in (54.4 cm)
net weight	112.24 lb(US) (50.91 kg)
mounting location	Front
Mounting preference	No preference
mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	Yes

# Input

Input voltage limits	75154 V adjustable 82144 V
Network frequency	50/60 Hz +/- 3 Hz auto-sensing

# Output

Harmonic distortion	Less than 5 %
Maximum configurable power in VA	2200 VA
Maximum configurable power in W	1980 W
Transfer time	4 ms typical : 8 ms maximum
UPS type	Line interactive
Wave type	Sine wave
Output frequency	50/60 Hz +/- 3 Hz sync to mains

### Conformance

Product certifications	CSA TAA compliance
Equipment protection policy	Lifetime : \$150000

### **Environmental**

Acoustic level	45 dBA
heat dissipation	275 Btu/h
Operating altitude	010000 ft
Ambient air temperature for operation	32.0000000000104.0000000000 °F (040 °C)
Ambient air temperature for storage	5.000000000113.0000000000 °F (-1545 °C)
Storage altitude	050000 ft (0.000000000015240.0000000000 m)

Relative humidity	095 %	
Storage Relative Humidity	0. 95 %	

## **Communications & Management**

control panel	Multifunction LCD status and control console
Emergency power off	Yes
Free slots	1
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

## **Surge Protection and Filtering**

Surge energy rate	530 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

## **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	22.008 in (55.9 cm)
Package 1 Width	30.0000000000 in (76.2 cm)
Package 1 Length	15.0000000000 in (38.1 cm)
Package 1 Weight	134.28 lb(US) (60.91 kg)

### **Contractual warranty**

Warranty

3 years repair or replace (excluding battery) and 2 years for battery, optional on-site warranties available, optional extended warranties available

## Sustainability Green Premium

**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >









Energy Efficient Take-back Transparency RoHS/REACh

### Resource performance

Energy Efficient Product

Take-Back Program Available

### Well-being performance

Mercury Free

Rohs Exemption Information

Yes

#### **Certifications & Standards**

Reach Regulation

Eu Rohs Directive

Compliant with Exemptions

Environmental Disclosure

Product Environmental Profile

Circularity Profile

End of Life Information

Jul 15, 2024