

Product datasheet

Specifications



Power Cord Kit (6 ea), Locking, C19 to C20, 1.8m, Blue

AP8716SX593

Overview

Lead time Usually in Stock

Main

Product or component type	Power cord
Input Connection Type	IEC 60320 C20
Cable length	1.8 m
Number of cables	6

Physical

Colour	Blue
Height	30 cm
Width	8 cm
Depth	7 cm
Net weight	2.16 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable

Input

Max line current	16 A
Input current limits	16 A

Output

Max current draw	16 A
Number of power socket outlets	1 IEC 60320 C19
Power cable length	1.8 m

Conformance

Product certifications	CCC CSA PSE UL listed VDE
------------------------	---------------------------------------

Environmental

Ambient air temperature for operation	0...75 °C
---------------------------------------	-----------

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Relative humidity	20...80 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...75 °C
Storage Relative Humidity	20...80 %
Storage altitude	0.0000000000...15240.0000000000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	30 cm
Package 1 Width	7 cm
Package 1 Length	8 cm
Package 1 Weight	2.16 kg
SCC14	10731304285011

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)




Take-back Transparency RoHS/REACH

Resource performance

 Take-Back Program Available

Well-being performance

 Lead Free

Certifications & Standards

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Compliant

[EU RoHS Declaration](#)

Environmental Disclosure

[Product Environmental Profile](#)

Weee

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile

[End of Life Information](#)