

GCS1602CC

2-Port 4K USB-C Desktop KVM with DisplayPort output and USB peripheral

USB-C KVMP - Switch Between Two USB-C Devices

Easily switch between two USB-C devices and control them with one keyboard, one mouse and view content on one 4K monitor. IOGEAR GCS1602CC requires no software and comes complete with the Power Delivery function, USB-C cables, and a 6-foot push-button remote switch.

Why spend extra money on features you don't need? The USB-C KVM offers the most efficient and affordable way to switch between two USB-C or Thunderbolt™ 3-equipped Mac® computers, PCs, iPad® or Android™ tablets and smartphones with a single-cable connection to each device without additional drivers or software.

Additional USB ports on GCS1602CC allows users to connect to more USB devices, such as USB printer, storage, camera, etc.

Requirements

Package Contents

Specifications

Function	GCS1602CC	Dimensions	GCS1602CC
Upstream Port		Unit Package Dimensions	
USB-C	2x USB-C for Laptops; data rate up to 5Gbps	Height	6.8 in. (17.3 cm)
Downstream Port		Length	11.2 in (28.3 cm)
DisplayPort	1x DP 1.4 compliant, up to 8k60Hz	Width	2.5 in. (6.2 cm)
USB-A	4x USB-A 3.2 Gen 1, data rate up to 5Gbps	Master Carton	
USB-C	1x USB-C for Power Delivery Pass-Thru	Height	7.6 in. (19.4 cm)
Power		Length	15.8 in. (40.2 cm)
Power Delivery Pass-Thru	Port 1: Supports 100W USB-C PD laptop charging at 5V, 9V, 15V, and 20V output Port 2: Supports max. 5V, 3A output	Width	11.8 in. (30 cm)
Input Rating	DC12V, 3.3A	Master Carton Qty.	6
Operating System Requirements		Weight	
Mac	Mac OS® X 9.0+	Master Carton Wt.	15.3 lb. (6.9 kg)
Windows	Windows® 10, 11 (32-bit / 64-bit) with 7th-Gen Intel Core Processor or above	Unit Pack Wt.	2.3 lb. (1.02 kg)
Android	Android 8+		
iOS	iPadOS 13.1 or later		
Environment			
Humidity	0?80% RH, Non-condensing		
Operation Temperature	32 - 104°F (0?40°C)		
Storage Temperature	-4 - 140°F (-20?60°C)		