

## 3.7kW Single-Phase 230V ATS/Monitored PDU, IEC309 16A Blue Outlet, 2 IEC309 16A Blue Inputs, 1U Rack-Mount

MODEL NUMBER: PDUMNH16HVAT



### Highlights

- Two IEC309 16A Blue (2P+E) inputs with 10 ft. cords
- IEC309 16A Blue outlet (2P+E) for connecting device or 0U PDU
- Automatic transfer switching within 1–5 ms
- Ethernet network interface for remote access
- Digital display with LEDs for real-time status monitoring

### Package Includes

- PDUMNH16HVAT 3.7kW Single-Phase 230V ATS/Monitored PDU
- Rack-mounting brackets
- Owner's manual

### Description

The PDUMNH16HVAT 3.7kW Single-Phase 230V ATS/Monitored PDU provides remote power monitoring and enables redundant power for network devices with non-redundant power supply configurations. Ideal for data centers and server rooms, it mounts in 1U of space in EIA-standard 19-inch racks and has an IEC309 16A Blue outlet for connecting a single device or a 0U 230V vertical PDU with IEC309 16A Blue plug.

Dual 10-foot input cords with IEC309 16A Blue plugs connect to separate primary and secondary single-phase power sources, including out-of-phase sources. The PDU constantly evaluates the power quality of both input sources. Dynamic solid-state(TRIAC) automatic transfer switching allows the PDU to switch to the secondary source within 1–5 milliseconds if the primary source fails or becomes unstable to ensure connected equipment remains powered.

Built-in Ethernet network interface allows remote access to the PDU for power monitoring, configuration, control and notifications via web browser, SSH, telnet or SNMP. Provides real-time load/current data with billing-grade accuracy(+/- 1 percent). Tiered access privileges allow both an administrator and a guest to log in. Automated alerts help prevent overloads, power loss and downtime. Digital display with LEDs indicates power availability, voltage, input status for both power sources, output load and power factor, as well as temperature and humidity conditions with the optional [ENVIROSENSE](#) module(sold separately).

### Features

#### Primary and Secondary Inputs for Power Redundancy

- Offers remote power monitoring and enables redundant power for network devices with non-redundant power supply configurations
- IEC309 16A Blue(2P+E) inputs with 10 ft. cords connect to separate primary and secondary single-phase power sources
- Fault-tolerant, hot-swappable UPS protection when used with single UPS; fully redundant UPS protection when each cord is connected to a separate UPS

#### Built-In IEC309 16A Blue Outlet

- Powers a single device or indirectly powers equipment through a 0U 230V PDU with IEC309 16A Blue input(sold separately)

#### Automatic Transfer Switching

- Dynamic solid-state(TRIAC) automatic transfer switching



- Switches to secondary power source if primary source fails or becomes unstable
- 1–5 ms transfer time ensures uninterrupted operation of connected equipment
- Built-in processor monitors power sources and prevents switching if secondary source is unavailable or of lower quality than primary source

#### Multifunction Digital Display with LEDs

- Reports input status for primary and secondary power sources, power availability, line voltage, frequency, amps, kilowatts and power factor

#### Advanced Network Monitoring

- Built-in Ethernet network interface allows full remote access for power monitoring, configuration, control and notifications via web browser, SSH, telnet or SNMP
- Real-time load/current data with billing-grade accuracy(+/- 1 percent)
- Tiered access privileges allow both an administrator and guest to log in
- Optional [ENVIROSENSE](#) module(sold separately) monitors temperature and humidity

#### Broad Communications Compatibility

- Supports HTTP, HTTPS, PowerAlert® Network Management System, SMTP, SNMPv1, SNMPv2, SNMPv3, Telnet, SSH, FTP, DHCP, BOOTP and NTP
- 10/100 Mbps auto-sensing for communication with 10/100 Base-T networks

#### Mounts Horizontally in 1U of Rack Space

- Compatible with EIA-standard 19 in. 4-post racks and rack enclosures
- Optional [PDU4PKIT](#) rail kit(sold separately) adds rear mounting support

## Specifications

OVERVIEW	
PDU Type	Monitored; Auto-Transfer Switch
OUTPUT	
Output Capacity Details	3.8kW (240V); 3.7kW (230V); 3.5kW (220V); 3.3kW (208V); 3.2kW (200V); 16A maximum
Frequency Compatibility	50 / 60 Hz
Output Receptacles	(1) IEC309 16A BLUE (2P+E)
Output Nominal Voltage	240, 230, 220, 208, 200
Overload Protection	n/a
INPUT	
PDU Input Voltage	200; 208; 220; 230; 240
Recommended Electrical Service	16A 230V
Maximum Input Amps	16
PDU Plug Type	IEC-309 16A BLUE (2P+E)
Input Cord Length (ft.)	10



Input Cord Length (m)	3
Input Cord Details	Set of two input cables for separate PRIMARY and SECONDARY input connections
Input Phase	Single-Phase
<b>USER INTERFACE, ALERTS &amp; CONTROLS</b>	
Front Panel LCD Display	Digital display reports input current in amps (Source A, Source B), output kilowatts (total), input voltage (Source A, Source B), input frequency (Source A, Source B) and output power factor
Front Panel LEDs	Front panel LEDs confirm amp (A) / kilowatt (kW) / voltage (V) / frequency (Hz) and power factor (PF) reporting information; Additional set of LEDs indicate Source A and Source B inputs for preferred, available and in-use status
Switches	ENTER and MODE switches toggle the digital display to display all reported information
<b>PHYSICAL</b>	
Shipping Dimensions (hwd / in.)	7.48 x 21.65 x 20.67
Shipping Dimensions (hwd / cm)	19 x 55 x 52.5
Shipping Weight (lbs.)	17.36
Shipping Weight (kg)	7.89
Unit Dimensions (hwd / in.)	1.72 x 16.93 x 14
Unit Dimensions (hwd / cm)	4.4 x 43 x 35.6
Unit Weight (lbs.)	17.36
Unit Weight (kg)	7.88
Material of Construction	Metal
Form Factors Supported	1U rackmount
PDU Form Factor	Horizontal (1U, 2U, etc)
<b>ENVIRONMENTAL</b>	
Operating Temperature Range	32 to 122F (-15 to 50C)
Storage Temperature Range	5 to 140F (-15 to 60C)
Relative Humidity	5 to 95% (non-condensing)
Operating Elevation (ft.)	0-10,000
Operating Elevation (m)	0-3000
<b>CERTIFICATIONS</b>	
Certifications	Tested to CE (IEC60950-1+A1,A2; Class A)
<b>WARRANTY</b>	



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

Product Warranty Period (Worldwide)	2-year limited warranty
-------------------------------------	-------------------------

© 2016 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice.

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<http://www.tripplite.com/products/product-certification-agencies>