

Specifications



APC Smart-UPS On-Line, 5kVA, Rackmount 5U, 208V, 12 5-20R+2 L6-20R+2 L6-30R NEMA, Network Card+SmartSlot, W/ rail kit, W/ transformer 208V to 120V

SRT5KRMXLT-5KTF

Overview

Lead time

Usually in Stock

Main

main	
Main Input Voltage	208 V
product or component type	Uninterruptible power supply (UPS)
Main Output Voltage	120 V
Rated power in W	4800 W
Rated power in VA	5000 VA
Input Connection Type	NEMA L6-30P
output connection type	12 NEMA 5-20R 2 NEMA L6-20R 2 NEMA L6-30R
Number of rack unit	5U
Cable length	10 ft (3.05 m)
Number of cables	1
Provided equipment	Documentation CD Rack mounting hardware Rack mounting brackets Rack mounting support rails User manual USB cable Warranty card Web/SNMP management card

Batteries & Runtime

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph
Battery type	Lead-acid battery
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	1.5 h
Number of battery replacement quantity	1
Battery voltage	192 V
Battery charger power	556 W rated
Battery life	35 year(s)

Replacement battery	APCRBC140
Extended runtime	1

General

UPS type	Double conversion online
product web sub-family	High density
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

Colour	Black
Height	8.6 in (21.8 cm)
Width	17.008 in (43.2 cm)
Depth	28.3 in (71.9 cm)
net weight	217.99 lb(US) (98.88 kg)
mounting location	Front
Mounting preference	No preference
mounting mode	Rack-mounted
Two post mountable	0
USB compatible	Yes
Mounting position	Horizontal

Input

Network frequency	4070 Hz auto-sensing
Input voltage limits	100275 V adjustable (half load)

Output

5000 VA 4800 W
4800 W
4000 W
50/60 Hz +/- 3 Hz sync to mains
Sine wave
Less than 2 %
3:1
Internal bypass (automatic and manual)

Conformance

Product certifications	ENERGY STAR V2.0 (USA)

Environmental

Ambient air temperature for operation	32.000000000104.000000000 °F (040 °C)
Relative humidity	095 % non-condensing

Operating altitude	010000 ft
Ambient air temperature for storage	5.000000000113.000000000 °F (-1545 °C)
Storage Relative Humidity	095 % non-condensing
Storage altitude	050000 ft (0.00000000015240.000000000 m)
Acoustic level	55 dBA
heat dissipation	1047 Btu/h
IP degree of protection	IP20

Communications & Management

Free slots	1
Preinstalled device	Network management card 3 with environmental monitoring
Alarm	Audible and visible alarms : prioritized by severity
Emergency power off	Yes

Surge Protection and Filtering

Surge energy rate

480 J

Packing Units

U	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	23.0 in (58.4 cm)
Package 1 Width	37.8 in (96 cm)
Package 1 Length	24.5 in (62.2 cm)
Package 1 Weight	259.99 lb(US) (117.93 kg)

Contractual warranty

Warranty

3 years repair or replace (excluding battery) and 2 years for battery

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Resource performance

Energy Efficient Product

Take-Back Program Available

Well-being performance

Mercury Free

Rohs Exemption Information

Environmental Certifications

Energy Star®

ENERGY STAR UPS V2.0 (USA)

Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information