

Product data sheet

Specifications



APC NetShelter Rack PDU Advanced Gen 2, Metered, 5.0kW, 1Phase, 208V, 30A, L6-30P, 40 Outlet

APDU11151ME

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Colour	Black
Product or component type	PDU
PDU type	Metered
Cord length	9.8 ft (3 m)

Complementary

Input Voltage	208 V 1 phase
Height	58.7 in (1490 mm)
Width	2.2 in (56 mm)
Output Voltage	208 V
Depth	3.0 in (75 mm)
Net weight	14.6 lb(US) (6.6 kg)
Mounting location	Side
Mounting preference	No preference
Input Plug Type	NEMA L6-30P
Mounting mode	Rack-mounted
Rack units	0U
Mounting position	Vertical
Communication port protocol	1000BASE-T 10/100BASE-T
[In] rated current	24 A
Permissible voltage	200...240 V
Input current limits	30 A
Load capacity	4992 VA
Network frequency	50/60 Hz
Outlet type and quantity	20 C13/C15/C19/C21 20C13/C15

Environment

Product certifications	TAA compliance
------------------------	----------------

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Standards	UL 62368-1 CSA C22.2 No 62368-1 FCC part 15 Subpart B
IP degree of protection	IP44
Ambient air temperature for operation	23...140 °F (-5...60 °C)
Relative humidity	5...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-13...149 °F (-25...65 °C)
Storage Relative Humidity	5...95 %
Storage altitude	0...50000 ft (0.0000000000...15240.0000000000 m)

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	67.72 in (172 cm)
Package 1 Width	4.57 in (11.6 cm)
Package 1 Length	8.19 in (20.8 cm)
Package 1 Weight	19.0 lb(US) (8.6 kg)

Contractual warranty

Warranty	3 years repair or replace
----------	---------------------------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

 Materials and Substances	
EU RoHS Directive	Compliant with Exemptions
REACH Regulation	REACH Declaration
China RoHS Regulation	China RoHS declaration

Use Again

 Repack and remanufacture	
Take-back	No

Image of product / Alternate images

Alternative

