

PDU Power Cord, C19 to P-Lock Lite C20 - 20A, 250V, 12 AWG, 4 ft. (1.2 m), Black, 6 Pack

MODEL NUMBER: P036-EN4-6



Connect blade servers or network switches to a PDU or UPS system with P-Lock C19 or C39 power connectors.

Features

C20-to-C19 Power Cables for Network Devices That Require a Heavy-Gauge Connection

These UL-certified power extension cords feature 12 AWG wire suitable for high power connections, making them a reliable solution for large server applications that require a higher-rated, heavier-gauge cable. The P036-EN4-6 can be used to connect servers, routers, network switches or blade server enclosures to a UPS system or PDU. The four-foot (1.2-meter) length helps reduce cable clutter by providing a tailor-made fit between the devices and the PDU in a crowded rack enclosure.

Forms a Special Locking Connection with a P-Lock Outlet

The P-Lock Lite C20 power connectors with locking tab form a secure connection with a PDU with P-Lock outlets, including Eaton G4 and newer PDUs with C19 and C39 outlets. The P-Lock Lite connection helps reduce the risk of accidental cable disconnects that can cause costly equipment downtime. The P036-EN4-6 lets you replace non-locking C19/C20 cables or upgrade an entire PDU application by pairing them with a high-density Eaton PDU or other PDU with P-Lock outlets.

Highlights

- Recommended for powering servers, routers and other high-output network devices
- P-Lock Lite C20 connectors eliminate accidental cable disconnections in a crowded PDU
- Thick 12 AWG wire gauge manages high power levels required for larger equipment
- 4 ft. length allows flexibility in mounting devices within a rack while avoiding cable clutter
- Includes 6 black PDU power cables, ideal for large-scale rack equipment rollouts

Package Includes

(6) PDU Power Cords, C19 to P-Lock Lite C20, 4 ft. (1.2 m), Black

Specifications

OVERVIEW	
UPC Code	037332303295
Product Type	PDU Extension Power Cord
Device Compatibility	Computer; Monitor/HDTV; PDU; Printer; Server; Tablet; UPS
Country/Region	North America
INPUT	
Maximum Input Amps	20
Voltage Compatibility (VAC)	250



Powering Business Worldwide

TRIPP LITE
SERIES

CONNECTIONS	
Side A - Connector 1	IEC-320-C20
Side B - Connector 1	IEC-320-C19
Connector Style	Straight
PHYSICAL	
Color	Black
Plug Color	Black
Cable Jacket Color	Black
Connector Color	Black
Cable Jacket Material	PVC
Cable Jacket Rating	VW-1
Power Cord Jacket Type	SJT
Cable Outer Diameter (OD)	11.2mm
Number of Conductors	3
Wire Gauge (AWG)	12
Wire Gauge (OD - mm ²)	3.31
Power Cord Color	Black
Cable Length (ft.)	4
Cable Length (m)	1.22
Shipping Dimensions (hwd / in.)	18.11 x 14.17 x 0.50
Shipping Weight (kg)	2.19
Unit Dimensions (hwd / in.)	18.110 x 14.170 x 0.500
ENVIRONMENTAL	
Operating Temperature Range	14° to 140°F (-10° to 60°C)
Storage Temperature Range	23° to 158°F (-5° to 70°C)
Relative Humidity	35 TO 85% RH, Non-Condensing
FEATURES & SPECIFICATIONS	
Antibacterial	No
Angled Plug	No
High Voltage	Yes
Locking Plug	Yes
P-Lock Power Cord	Yes
Coiled Power Cord	No



Powering Business Worldwide

TRIPP LITE
SERIES

Locking Power Cord	Yes
Locking	Yes
STANDARDS & COMPLIANCE	
Product Certifications	CAN/CSA C22.2; UL Listed; cUL Listed
Product Compliance	REACH; RoHS
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	Lifetime limited warranty

1000 Eaton Boulevard
Cleveland, OH 44122
United States
<https://tripplite.eaton.com>

© 2026 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.