

MPN: LVN-1UMOUNT-48PORT-2SFP-1G

50 Port Gigabit Ethernet switch, provide 48* 10/100/1000M adaptive Ethernet ports+2* Gigabit SFP ports.

LVN-1UMOUNT-48PORT-2SFP-1G

, a high-performance 50-port Gigabit Ethernet switch designed to meet the demands of modern networking environments. This switch features 48 adaptive 10/100/1000Mbps Ethernet RJ45 ports and 2 Gigabit SFP ports, ensuring seamless integration with various devices and network configurations.



Engineered with top-notch, high-speed network integrated circuit solutions, the LVN-1UMOUNT-48PORT-2SFP-1G effectively addresses issues of noise often encountered with smaller switches in office settings, thanks to its innovative fan-free design, providing a silent yet powerful performance.

The switch's RJ45 ports support a versatile range of connection speeds, making it an ideal choice for network infrastructure in security video monitoring, hospitality settings, educational campuses, and small to medium-sized enterprises. Its user-friendly configuration, including two operational modes and intelligent one-click dialing for easy management, makes it a versatile tool for any networking professional.

- 48 Gigabit RJ45 ports + 2 Gigabit SFP optical ports.
- Each RJ45 port supports automatic adaptation to 10/100/1000Mbps speed.
- Automatic port flipping for simplified connections.
- Features a dial switch for easy VLAN mode setting.
- Integrated loop alarm system to enhance network reliability.

Spezifikationen

Certificates	NDAA Compliance	Yes
Data transmission	MAC-Adresstabelle	16000 Eintragungen
	Paketweiterleitung	Yes
	Schaltleistung	100 Gbit/s
	Speichern und weiterleiten	Yes
	Weiterleitungstarif	74,4 Mpps
Design	Anzahl Fans	0 Lüfter
	Ein / Aus Schalter	No
	Gehäusematerial	Metal
	LED-Anzeigen	Link, Loop, Power, WLAN
	RoHS-Konformität	Yes
Management features	Schaltertyp	Unmanaged
Network	Auto MDI/MDI-X	Yes
	Halbduplex	Yes
	Netzwerkstandards	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3x, IEEE 802.3i, IEEE 802.3z

Network	Unterstützung der Flusskontrolle	Yes
	Vollduplex	Yes
Operational conditions	Betriebstemperatur (TT)	0-40 °C
	Lagertemperatur (TT)	-40 - 70 °C
	Relative Luftfeuchtigkeit bei Lagerung (HH)	5 - 95 %
	Relative Luftfeuchtigkeit im Betrieb (HH)	10 - 90 %
Optical fiber	Glasfaser-Ethernet-Verkabelungstechnologie	1000Base-X
Other features	Ethernet-LAN-Anschlüsse (RJ-45)	48
	Ethernet-Schnittstellentyp	Gigabit Ethernet
	Material	Metal
	Montage	Rack mounting
	Power LED	Yes
Package dimensions	Depth (package,cm)	29 cm
	Gross Weight	3,371 kg
	Height (package,cm)	8,5 cm
	Width (package,cm)	50 cm
Packaging data	Enthaltene Netzsteckertypen	EU
	Handbuch	Yes
	Kabel enthalten	AC
	Montagehalterungen enthalten	Yes
	Rack-Montage-Kit	Yes
	Schrauben enthalten	Yes
Ports & interfaces	Anzahl der Glasfaser-Uplink-Ports	2
	Glasfaseranschluss	SFP
	Grundlegende Anzahl von RJ-45-Ethernet-Ports	48
	Grundlegender Switching-RJ-45-Ethernet-Porttyp	Gigabit Ethernet (10/100/1000)
Power	AC-Eingangsspannung	100-240 V
	DC-Eingangsspannung	12 V
	Eingangsstrom	2 A
	Überspannungsschutz	Yes
	Überspannungsschutzspannung	6 kV
Product dimensions	Height (product,cm)	4,4 cm
	Net Weight	2,826 kg
	Tiefe cm	20,5 cm
	Width (product,cm)	44 cm
Technical details	Garantiezeit	3 Jahr(e)

Vendor information

Brand Name	Lanview
Warranty	3 Jahre)

Weitere Bilder

