QuickSpecs

QuickSpecs

Models

PF996AA#ABA

HP Care Pack Services

Next Day Onsite Response, 3 years	H2754E
Next Day Onsite Response, 4 years	U7934E
Next Day Onsite Response, 5 years	U7935E
Basic 8-5, 4 Hour Onsite Response, 3 years	U8317E
Basic 8-5, 4 Hour Onsite Response, 4 years	U8318E
Basic 8-5, 4 Hour Onsite Response, 5 years	U8319E
Post Warranty Service, Next Day Onsite	U4925PE

NOTE: For additional information on HP Care Pack Services, please see http://www.hp.ca/hps/carepack/.

Technical Specifications

Tube Type Colour, flat-screen shadow mask, multi-frequency

Picture Tube Size 17 in (43.1 cm)

(diagonal)

Viewable Image Area 16 in (40.6 cm)

(diagonal)

Trio Dot Pitch 0.25 to 0.28 mm 0.22 to 0.24 mm Horizontal Dot Pitch 30 to 86 KHz

Horizontal Frequency

Vertical Frequency (Hz)

(kHz)

50 to 160 Hz

Maximum Pre-set

Resolution

1600 x 1200 @ 65 Hz

Preferred Flicker Free

Resolution

1024 x 768 @ 85 Hz

Preset Graphic Modes NOTE: All modes are

1600 x 1200 @ 65 Hz 1280 x 1024 @ 75 Hz

non-interlaced unless specified otherwise.

1024 x 768 @ 85 Hz and 75 Hz

800 x 600 @ 85 Hz and 75 Hz

720 x 400 @ 70 Hz

640 x 480 @ 85 Hz, 75 Hz and 60 Hz

User-Modes Yes, 8 modes

Anti-Glare/Anti-Static Yes **AssetControl** Yes Plug and Play Yes Icon Based On-Screen Yes

Display Controls

QuickSpecs

QuickSpecs

User Controls Brightness, Contrast Yes

Size and Positioning Yes
Pincushion (barrel) Yes
Trapezoid Yes
Tilt (rotation) Yes
Selectable Colour Yes

temperature

Parallelogram Yes
Pincushion Balance Yes
Moiré Yes
Degauss Yes
Factory Reset/Recall Yes
Current Display Mode Yes
UL/CSA/CUL Approval Yes

Approvals/ Certifications UL/CSA/CUL Approval Yes ISO9241-3, -7, -8 VDT Yes

Guidelines Approval

MPR-II Compliant
TCO 03
Yes, select models
Yes, select models

FCC Approval Yes
Microsoft® WHQL Yes

Certified

CE Yes
Energy Star Compliant No
TUV compliant Yes
Certified by the United Yes
States DHHS FDA Centre

for Devices and Radiological Health

Maximum Pixel Clock

Speed

180 MHz

Power Supply Universal; 100 to 240 V, 50 \pm 3Hz and 60 \pm 3Hz

Maximum Power Rating 75 watts
Typical Power 61 watts

Consumption

Low Power Sleep Mode < 3 watts

Signal Cable 15-pin miniature D-sub, attached, 4.9 ft (1.5 m)

Dimensions (H x W x D) Unpacked 16.2 x 16.2 x 17.0 in (41 x 41 x 43 cm)

Packaged 20.9 x 18 x 19.4 in (53 x 45.8 x 49.3 cm)

 Unpacked
 35.3 lb (16 kg)

 Packaged
 38 lb (17 kg)

Environmental Temperature – Operating 50° to 95° F (10° to 35° C)

(non-condensing)

Humidity – Operating 20% to 80%

(non-condensing)



QuickSpecs

QuickSpecs

Altitude – Operating, over 0 to 10,000 ft (0 to 3,048 m)

the entire operating temperature range

Altitude – Non-operating, 0 to 30,000 ft (0 to 9,144 m)

over the entire nonoperating temperature

range

Compatibility Recommended for use with HP products.

Options HP CRT Multimedia Base-integrated power supply, volume control, speakers, headphone, and

microphone jacks; optional; part number PM552AA. See product QuickSpecs for more information.

Software HP Display LiteSaver feature lets you schedule Sleep mode at preset times to help protect the display

against phosphor burn, drastically lower power consumption and energy costs, and extend the lifespan

of the monitor.

Warranty Three years parts, labour, and on-site service. 24-hour, 90-day, toll-free technical support. Replacement

options may include second business day on-site service, or next business day direct replacement, at HP's sole discretion. With direct replacement, HP will ship a replacement display product directly to you. Using the prepaid shipping labels provided, return your failed display to HP in the same packaging as the replacement. Certain restrictions and exclusions apply. For details see your product warranty or

contact HP Customer Support.

©2006 Hewlett-Packard Development Company, L.P.

Microsoft is a trademark or registered trademark of Microsoft Corporation in the U.S. and other countries.

All performance specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.

The information contained herein is subject to change without notice and is provided "as is" without warranty of any kind. The warranties for HP products and services are set forth in the express limited warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

