

Data sheet

HP 4.5 mm and USB-C Dock Adapter G2



Legacy connectivity and power

Use the HP 4.5 mm and USB-C Dock Adapter G2 to connect your legacy HP notebooks with a 4.5 mm barrel AC adapter and a USB port to your HP USB-C/A Universal Dock G2 for easy network, display, and device expansion and barrel charging.

Specifications

HP 4.5 mm and USB-C Dock Adapter G2

Part number	2NA11AA
Model number	HSA-Q001
Dimensions	without cable: 1.77 x 1.33 x 0.39 in (45 x 34 x 10 mm) with cable: 8.14 x 1.33 x 0.39 in (206.9 x 34 x 10 mm)
Weight	0.053 lb (0.024 kg)
Front components	1 x USB-A 3.0 Plug Port (USB Signal only) 1 x 4.5 mm DC Barrel Plug Connector (Power only)
Rear components	USB-C Receptacle (USB signal + PD power)
Input power	20V/3.3A (66W) max
Output power	20V/3.25A (65W) max
Operating systems	Windows 7 and above, Windows10 S4, Chrome
Normal operation voltage	20V
Average operation power	0.7W
Max operation power	1W
Temperature (operation)	32~104 °F (0~40 °C)
Temperature (non-operation)	-4~140 °F (-20~+60 °C)
Relative humidity (operation)	20%~90% RH, non-condensing
Relative humidity (non-operation)	20%~95% RH, non-condensing
Altitude (operation)	10000ft (3048m)
Altitude (non-operation)	30000ft (9144m)
Shock (operation)	40G, 2 ms, half-sine
Shock (non-operation)	240G, 2 ms, half-sine
Random vibration (operation)	~0.21Grms, 50~2000 Hz
Random vibration (non-operation)	~2.09Grms, 50~2000, non-operating
Option kit contents	HP 4.5mm and USB-C Dock Adapter G2
Dock compatibility	HP USB-C/A Universal Dock G2

Sign up for updates
hp.com/go/getupdated



Share with colleagues



Rate this document

