

CY53-E Two-Camera Multisensor

10MP of Detailed Coverage From a Single Install Point



Overview

The CY53-E two-camera multisensor features two independent and adjustable 5MP image sensors which together support expansive coverage from a single install point. A pair of 1 / 2.8" progressive CMOS image sensors, each with 2.55x optical zoom and 30 meters / 98 feet of IR range, enable clear and consistent image quality in varied lighting conditions. The CY53-E includes a CV72S Ambarella processor to support advanced analytics like [AI-powered search](#), [history player search](#), [Occupancy Trends](#), line crossing, loitering, and Person of Interest (POI) alerts. The camera is optimal for covering bidirectional hallways, warehouse aisles, wide entryways, and building lobbies – offering double the visibility of a single-sensor camera and, with configurable sensors, minimizing blind spots while only requiring a single PoE+ cable and IP address.

The CY53-E's robust metal housing, IP66/67 weather rating, and IK10 impact rating enable the device to withstand extreme temperatures and weather. Constructed with easy and efficient installation top-of-mind, the CY53-E features captive screws that remain attached to the mounting plate, a latch-based cable gland for easy PoE threading, a three-LED light status indicator, a built-in bubble level, and alignment presets that guide each lens into optimal positions for common viewing angles.

Key features

Excellent image quality

- Two 1 / 2.8" progressive CMOS image sensors
- 10MP (2 x 5MP) of collective resolution
- Two varifocal lenses with 2.55x optical zoom per lens
- 30 meters / 98 feet of IR range for nighttime viewing

Expansive coverage

- Individually adjustable and repositionable sensor heads
- Total field of view up to 176°

Streamlined installation

- Single PoE+ cable required
- Latch-based cable gland
- Alignment presets for optimal lens positioning
- Physical and digital mute switches to easily enable or disable audio

Durability and weather protection

- Robust metal housing
- IP66/67 weather rating
- IK10 impact rating
- Operability between -40°C to 50°C / -40°F to 122°F

Hybrid cloud architecture

- Onboard storage and processing for reduced bandwidth consumption and coverage at scale
- 30 - 120 days (512GB - 2TB) of onboard storage
- Redundant cloud backup and unlimited cloud-based archiving of footage

Advanced analytics

- Onboard CV72S Ambarella processor enables people and vehicle analytics
- AI-powered search and AI-powered alerts
- Occupancy Trends for operational insights



CY53-E

Tech Specs

Camera features

Image Sensor	2 x 1 / 2.8" Progressive CMOS	Shutter Speed	1 / 30 sec. to 1 / 10,000 sec
Sensor Resolution¹	2 x 5MP (2592 x 1944)	Day/Night	IR-cut filter for day and night function
Lens Type	Varifocal; motorized zoom	IR Cut Filter	Yes
Focal Length	3.18 - 8.12mm	IR Range	30m / 98ft; non-adjustable
Aperture	F1.9 - F3.24	Minimum Illumination	0.009 lux @ F1.9 (Color) 0 lux with IR illuminators on
Iris	N/A	Onboard Storage	Capacity: From 512GB to 2TB Card: MicroSD, SDXC
Field of View (after LDC²)	Horizontal: 97° - 38° (88° - 35°) Vertical: 69° - 28° (65° - 26°) Diagonal: 131° - 46° (111° - 43°)	CPU	1 x Ambarella CV72S66
Sensor Movement	Tilt: +0° to 60° for each lens from upright Pan: +/- 90° for each lens Rotation: +/- 90° for each lens		

Standard video settings

Compression	H.265, H.264	Historical Video Settings	Adaptive quality ¹
Frame Rate³	24fps / sensor	WDR Technology	True WDR, dual exposure
Live Streaming Settings (Per Head)	High quality (HQ): Up to 3,000 Kbps (default) Standard quality (SQ): Up to 600 Kbps		

Standard audio settings

Audio	Supported	Interface	Built-in microphone
Audio Capacity	One-way audio	Effective Range	5m / 16ft

Power and network

Power Input⁴	IEEE 802.3at Type 2 PoE+	Connectivity	RJ-45 cable connector for network/PoE connection; 10 / 100 / 1000 Mbps
Power Consumption⁴	With IR: 37-57V, 0.60-0.45A, 25.5W Without IR: 37-57V, 0.37-0.24A, 13.5W Extended temperature range: 37-57V, 0.60-0.45A, 25.5W	RTSP	RTSP 1.0 RFC 2326 Max concurrent streams: 4 (2 per camera head) Audio support: Yes

1. All our cameras record in "adaptive quality," capturing both standard (SQ) and high quality (HQ) streams. SQ video is stored up to the amount of retention specified by the customer. The amount of HQ video stored on the camera will depend on the amount of motion detected by the camera over time. To learn more, visit our website: <https://docs.verkada.com/docs/adaptive-quality-recording-whitepaper.pdf>

2. Lens Distortion Correction (LDC) crops the sensor field of view to deliver a rectified, undistorted output image.

3. Frame rate can be adjusted by support.

4. Extended temperature range includes operating temperatures below -10°C / 14°F and assumes IR will be enabled.






CY53-E Tech Specs

General

Operating Temperature	-40°C to 50°C / -40°F to 122°F	LED Indicator	System power, status indicator and debug indicator
Humidity	0 to 90%	Warranty	10 Years
Certifications	FCC, IC, CE, UL/CB, UKCA, AUS, NZ, IP66, IP67, IK10	Included Accessories	T10 Torx Security Screwdriver, Mount Plate with leveler, 4x Wall Mount Screws, 4x Wall Anchors, Desiccant, Conduit Adapter, Large Cable Gland

Mechanical

Weight	Camera: 2,000g / 70.55 oz Mount plate: 400g / 14.11 oz	Body	Aluminum
Dimensions	L: 253.0mm / 9.96in W: 143.0mm / 5.63in H: 115.0mm / 4.53in with mount plate H: 110.0mm / 4.33in without mount plate		



Software capabilities

Alerts⁵	Camera status, motion detection, people detection, vehicle detection, Person of Interest detection, crowd detection, line-crossing detection, loitering detection, AI-powered alerts	Streaming and Storage⁵	Cloud backup, configurable retention days, selectable storage location, low bandwidth mode, timelapse, RTSP
People Analytics⁵	People search, attribute search, face search, Occupancy Trends, motion search, trajectory analysis, selective face blurring, AI-powered search	Sharing and Privacy⁵	Live Links, live face blur, privacy regions, audit log
Vehicle Analytics⁵	Vehicle search, attribute search, motion search, trajectory analysis, Occupancy Trends, AI-powered search		

5. All the listed features can be enabled independently for each camera head.



Ordering Information

CY53-E pricing

Model Number	MP ¹	WDR	Lens	IR Range	Onboard Storage	Maximum SQ Onboard Retention ¹	People/Vehicle Analytics	Cost (MSRP) ^{USD}
CY53-512E-HW	2 x 5MP	✓	Zoom	30m / 98ft	512GB	30 Days	✓	\$2,199
CY53-1TBE-HW	2 x 5MP	✓	Zoom	30m / 98ft	1TB	60 Days	✓	\$2,999
CY53-2TBE-HW	2 x 5MP	✓	Zoom	30m / 98ft	2TB	120 Days	✓	\$4,599

1. All our cameras record in "adaptive quality," capturing both standard and high quality streams. Standard quality (SQ) video is stored up to the amount of retention specified by the customer. The amount of high quality video stored on the camera will depend on the amount of motion detected by the camera over time. To learn more, visit our website: <https://docs.verkada.com/docs/adaptive-quality-recording-whitepaper.pdf>



Ordering Information

Video Security Cloud License pricing (New/Capacity Increase)²

Model Number	Description	Cost (MSRP) USD
LIC-CAM-MLT2-1Y-CAP	1-Year Two-Camera Multisensor License, Capacity Increase	\$349
LIC-CAM-MLT2-3Y-CAP	3-Year Two-Camera Multisensor License, Capacity Increase	\$999
LIC-CAM-MLT2-5Y-CAP	5-Year Two-Camera Multisensor License, Capacity Increase	\$1,599
LIC-CAM-MLT2-10Y-CAP	10-Year Two-Camera Multisensor License, Capacity Increase	\$3,199

Video Security Cloud License pricing (Renewal)²

Model Number	Description	Cost (MSRP) USD
LIC-CAM-MLT2-1Y-RNW	1-Year Two-Camera Multisensor License, Renewal	\$349
LIC-CAM-MLT2-3Y-RNW	3-Year Two-Camera Multisensor License, Renewal	\$999
LIC-CAM-MLT2-5Y-RNW	5-Year Two-Camera Multisensor License, Renewal	\$1,599
LIC-CAM-MLT2-10Y-RNW	10-Year Two-Camera Multisensor License, Renewal	\$3,199

2. The CY53-E requires a separate license from other Verkada Cameras.



Ordering Information

Accessories pricing

Model Number	Description	Cost (MSRP) USD
ACC-MNT-ARM-1	Arm Mount	\$99
ACC-MNT-CORNER-1	Corner Mount	\$199
ACC-MNT-POLE-1	Pole Mount	\$209
ACC-MNT-XLARM-1	Large Arm Mount	\$159
ACC-MNT-YJBOX-1	Two-Camera Multisensor Junction Box Mount	\$149
ACC-MNT-YPEND-1	Two-Camera Multisensor Pendant Cap Mount	\$109
ACC-POE-90W-AU	90W PoE++ (802.3bt Type 4) Injector, GigE, Indoor, Australia Type I Plug	\$169
ACC-POE-90W-EU	90W PoE++ (802.3bt Type 4) Injector, GigE, Indoor, Europe Type F Plug	\$169
ACC-POE-90W-NA	90W PoE++ (802.3bt Type 4) Injector, GigE, Indoor, North America Type B Plug	\$169
ACC-POE-90W-UK	90W PoE++ (802.3bt Type 4) Injector, GigE, Indoor, United Kingdom Type G Plug	\$169
INJ-POE-PLUS	PoE Plus (802.3at) Injector, GigE	\$129



Ordering Information

Viewing Station pricing

Model Number	Description	Cost (MSRP) USD
VX52-HW	VX52 Viewing Station	\$499

Viewing Station License pricing (New/Capacity Increase)

Model Number	Description	Cost (MSRP) USD
LIC-VX-1Y-CAP	1-Year Viewing Station License, Capacity Increase	\$499
LIC-VX-3Y-CAP	3-Year Viewing Station License, Capacity Increase	\$1,299
LIC-VX-5Y-CAP	5-Year Viewing Station License, Capacity Increase	\$1,999
LIC-VX-10Y-CAP	10-Year Viewing Station License, Capacity Increase	\$3,999

Viewing Station License pricing (Renewal)

Model Number	Description	Cost (MSRP) USD
LIC-VX-1Y-RNW	1-Year Viewing Station License, Renewal	\$499
LIC-VX-3Y-RNW	3-Year Viewing Station License, Renewal	\$1,299
LIC-VX-5Y-RNW	5-Year Viewing Station License, Renewal	\$1,999
LIC-VX-10Y-RNW	10-Year Viewing Station License, Renewal	\$3,999