

ML750i

Mini-portable LED Hand-held Projection



- **Travel-ready big picture** – Up to 100" image from the palm of your hand
- **Seamless sharing & cloud access** – Mirror, cast, and control content stored on OneDrive, Google Drive and Dropbox
- **Instant setup** – Get a clear, aligned picture in seconds with auto keystone and focus
- **Compact & Lightweight** - Weighs less than one pound and fits anywhere



ML750i Mini-portable LED projector with HD resolution weighing less than 1lb. and fits in the palm of your hand for the professional on-the-go or discrete digital signage.

Specifications

EAN: 5055387668324, Colour: White+Gray

UPC: 796435 44 746 5, Colour: White+Gray



Display/image	
Display technology	DLP®
Resolution	WXGA (1280x800)
Brightness (HK/ANSI)	700/450
Contrast ratio	20,000:1
Native aspect ratio	16:10
Aspect ratio - compatible	4:3, 16:9
Keystone correction - vertical	+/-40°
Horizontal scan rate	15.375 ~ 91.146Khz
Vertical scan rate	24 ~ 85(120 for 3D)Hz
Uniformity	85%
Screen size	17" ~ 100" diagonal
Lamp info	
Light source type	LED
LED life	20,000 hours
Optical	
Throw ratio	1.5:1
Projection distance	21.65" - 127.17"
Zoom type	Fixed
Focal length (mm)	14.95
Native offset	100%
Connectivity	
Connections	Inputs 1 x HDMI 1.4b, 1 x microSD card, 1 x USB-A reader Outputs 1 x Audio 3.5mm Control 1 x RS232 (via mini USB connector)
General	
Noise level (min)	29dB
Noise level (max)	32dB
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz)
3D compatibility	SVGA 120Hz, XGA 120Hz
3D	3D ready
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	12 languages: Dutch, English, French, German, Greek, Italian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish
360° operation	Yes
Operating conditions	0°C ~ 40°C, Max. Humidity 85%, Max. Altitude 2500m
Remote control	Card style
Speaker count	1
Watts per speaker	2W
In the box	Carry bag Universal I/O cable AC power cord Remote control 1x CR2025 Battery Basic user manual 1x RS232 Mini-USB adaptor
Input lag	16.00ms
Optional wireless models	EZC-USB
Power	
Power supply	100 ~ 240V, 50 ~ 60Hz
Power consumption (standby)	0.5W
Power consumption (min)	23W
Power consumption (max)	67W
Weight and dimensions	
Dimensions (W x D x H)	4.13" x 4.17" x 1.54"
Gross weight	2.89 lbs
Net weight	0.94 lbs