

## HDMI over CAT5 HDBaseT Extender - RS232 - IR - Ultra HD 4K - 330 ft (100m)

Product ID: ST121UTPHD2



The StarTech.com HDBaseT extender kit, extends HDMI up to 330 feet (100 Meters) over a single CAT5e or CAT6 cable. The extender supports Ultra HD and Full HD resolutions (4K / 1080p) with support for 3D and the accompanying 7.1 digital audio. For added versatility the transmitter and receiver can be used to transmit IR and RS232 serial communication over the same cable. The versatility of this video extender makes it an ideal solution for digital signage applications.

HDBaseT is a standardized, zero latency, video distribution technology that's revolutionizing HDMI distribution. HDBaseT uses an advanced method of modulation that enables you to distribute uncompressed HDMI audio and video along with additional signals such as 100BaseT Ethernet, IR, RS-232 serial and power over cable.

The extender offers HDBaseT technology with HDMI, IR, and RS232 control in a single CAT 5 extender kit, for complete end-to-end control. Offering greater versatility than traditional HDMI extenders or HDMI cabling alone HDBaseT is the clear choice for every integrator and system designer. The IR extension enables you operate your display and an IR-enabled source device, such as a Blu-ray player or TV Set top box, from either end of your extension. While RS232 control let you to connect a serial I/O device at your display - an ideal solution for adding a serial touch screen interface to your remote display.

With the A/V industry quickly adopting 4K as the new high-resolution video standard, long range video distribution can be a challenge with standard HDMI cables beginning signal degradation at 30 feet. With support for 4K 30Hz you'll be amazed at how HDBaseT maintains your Ultra HD picture quality, four times the resolution of high-definition 1080p, even at 164 feet away from your video source. Plus, because the extender is still backward compatible with High-Definition 1080p displays and video sources, you can rest assured this extender will make your video source look great in any remote digital signage application.

This extender has been specially crafted for a smooth, tidy installation. HDBaseT technology allows for single cable installation, for seamless integration using existing CAT5e or CAT6 infrastructure, avoiding the hassle of running multiple cables, while reducing potential failure points. Mounting hardware is also built-in to both the extender and receiver for discrete, professional mounting.

The ST121UTPHD2 is backed by a 2-year StarTech.com warranty and free lifetime technical support.

## Certifications, Reports and Compatibility



## Applications

- Position a display/monitor in a convenient viewing area while the transmitting content over a CAT5 cable from a cleaner, more secure environment
- Ideal for digital signage applications in financial, educational, medical and business sectors
- Perfect for video conferencing solutions in boardrooms and office settings
- Optimize placement of your demo stations at trade-shows and in auditoriums

## Features

- Enastende bildkvalitet med std fr upplsningar p upp till UltraHD 4K (upp till 50 m)
- Hassle-free installation with a single CAT5e or CAT6 cable and built-in mounting hardware
- Stder ven HD-videoupplsningar som till exempel 1920x1200 eller 1080p vid avstnd p upp till 100m
- With HDBaseT extend HDMI, IR, and RS-232 through one CAT5e or CAT6 cable
- Supports unidirectional RS232
- Dolby TrueHD, DTS-HD MA Audio
- RS232 interface supports up to 115200bps full-duplex data rate
- No software or drivers required

|                  |                                |                                    |
|------------------|--------------------------------|------------------------------------|
| <b>Hrdvara</b>   | Warranty                       | 2 Years                            |
|                  | Portar                         | 1                                  |
|                  | Kablage                        | Cat 5 UTP or better                |
|                  | Audio                          | Yes                                |
|                  | Industristandarder             | High Speed HDMI and HDCP compliant |
|                  | Kedjekoppling                  | No                                 |
| <b>Prestanda</b> | Maximal dataverfringshastighet | HDMI - 3.4Gbps                     |
|                  |                                | RS232 - 115200bps baud             |
|                  | Maximalt avstnd                | 100 m / 330 ft                     |
|                  | Maximal digital upplsning      | 4K                                 |
|                  | Stdda upplsningar              | 3840x2160 (4K)                     |
|                  | Std fr widescreen              | 2560x1600                          |
|                  | Audio-specifikationer          | 1920x1200                          |
|                  | Allmnna specifikationer        | 1920x1080 (1080p)                  |
|                  |                                | 1280x720 (720p)                    |
|                  |                                |                                    |

Yes

Supports Dolby TrueHD, DTS-HD MA

IR Interface: unidirectional

38Khz / 10 / 5M

|                    |                        |                          |
|--------------------|------------------------|--------------------------|
| <b>Kontakt(er)</b> | Lokala enhetskontakter | HDMI (19 pin)            |
|                    | Lokala enhetskontakter | DB-9 (9 pin, D-Sub)      |
|                    | Lokala enhetskontakter | RJ-45                    |
|                    | Lokala enhetskontakter | IrDA (Infrared, SIR/FIR) |
|                    | Fjrrenhetskontakter    | HDMI (19 pin)            |
|                    | Fjrrenhetskontakter    | DB-9 (9 pin, D-Sub)      |
|                    | Fjrrenhetskontakter    | RJ-45                    |
|                    | Fjrrenhetskontakter    | IrDA (Infrared, SIR/FIR) |

|                 |                   |                |
|-----------------|-------------------|----------------|
| <b>Mjukvara</b> | OS-kompatibilitet | OS Independent |
|-----------------|-------------------|----------------|

|                                   |                       |                                                                                 |
|-----------------------------------|-----------------------|---------------------------------------------------------------------------------|
| <b>Srskilda anmärkningar/krav</b> | System- och kabelkrav | 1X Standard CAT5 cable</br>1X HDMI Cable for Remote Unit (Local Cable Included) |
|-----------------------------------|-----------------------|---------------------------------------------------------------------------------|

|                    |                 |                   |
|--------------------|-----------------|-------------------|
| <b>Indikatorer</b> | LED-indikatorer | Power (Green)     |
|                    | LED-indikatorer | RJ45 Link (Green) |
|                    | LED-indikatorer | Mode (Green)      |
|                    | LED-indikatorer | HDCP (Green)      |

|              |                     |                        |
|--------------|---------------------|------------------------|
| <b>Ström</b> | Power Source        | 2 AC Adapters Included |
|              | Inspänning          | 100 - 240 AC           |
|              | Inström             | 0.6                    |
|              | Utsppänning         | 12V DC                 |
|              | Utström             | 1.24A                  |
|              | Polaritet p mittpol | Positive               |
|              | Kontakttyp          | M                      |
|              | Strömförbrukning    | 12                     |

|              |                      |                           |
|--------------|----------------------|---------------------------|
| <b>Miljö</b> | Drifttemperatur      | 0C to 70C (32F to 158F)   |
|              | Förvaringstemperatur | -20C to 85C (-4F to 185F) |

|                         |                        |                                      |
|-------------------------|------------------------|--------------------------------------|
|                         | Luftfuktighet          | 0-95%                                |
| <b>Utseende</b>         | Frg                    | Black                                |
|                         | Kabinetttyp            | Steel                                |
|                         | Produktlängd           | 5.9 in [1.5 cm]                      |
|                         | Produktbredd           | 3.1 in [80 mm]                       |
|                         | Produkthjd             | 1.0 in [25 mm]                       |
|                         | Produktvikt            | 20.4 oz [579 g]                      |
| <b>Frpäckning</b>       | Package Length         | 10.0 in [2.5 cm]                     |
|                         | Package Width          | 12.2 in [3.1 cm]                     |
|                         | Package Height         | 2.6 in [67 mm]                       |
|                         | Fraktvikt (frpackning) | 3.4 lb [1.5 kg]                      |
| <b>Vad det r i ldan</b> | Ingr i paketet         | Local HDMI Extender Unit             |
|                         | Ingr i paketet         | Remote HDMI Receiver Unit            |
|                         | Ingr i paketet         | Universal Power Adapter NA / UK / EU |
|                         | Ingr i paketet         | User Manual                          |
|                         | Ingr i paketet         | HDMI Cable - 4 ft (1.2 Meters)       |
|                         | Ingr i paketet         | IR Receiver Cable                    |
|                         | Ingr i paketet         | IR Transmitter Cable                 |

***\*Product appearance and specifications are subject to change without notice.***

