



SPECIFICATIONS

Panel Size	32" (81.28 cm)
Active Display Area (mm)	708.48(H) x 398.52(V)
Curvature	Flat
Panel Type	Rapid IPS
Panel Resolution	3840 x 2160 (UHD)
Pixel Pitch (H x V)	0.1845(H) x 0.1845(V)
Aspect Ratio	16:9
Brightness (nits)	350 Nits (Typ.), 400 Nits (Peak)
Contrast Ratio	1000:1 (Typ.)
DCR	100000000:1
Signal Frequency	180~352 KHz (H) / 48~160 Hz(V)
ACTIVATED RANGE	48~160Hz
Refresh Rate	160Hz
Response time	1ms (GTG)
DYNAMIC REFRESH RATE TECHNOLOGY	AMD FreeSync™ Premium
HDR Support	VESA DisplayHDR 400
Video ports	1x DisplayPort (1.4a) 2x HDMI™ (2.1) 1 x Type-c (DP alt.) w/PD 90W
USB ports	3x USB 2.0 Type-A 1x USB 2.0 Type-B
Audio ports	1x Headphone out
Viewing Angle	178°(H) / 178°(V)
Adobe RGB / DCI-P3 / sRGB	93.6% / 95% / 125.7%
Surface Treatment	Anti-glare
Display Colors	1.07B (8bits + FRC)
Frameless Design	Yes
PIP / PBP Function	Yes
Power Type	Power Cable
Power Input	100~240V, 50~60Hz
Adjustment (Tilt)	-5° ~ 20°
Adjustment (Swivel)	-45° ~ 45°
Adjustment (Height)	0 ~ 100mm
Kensington Lock	Yes
VESA Mounting	100 x 100 mm
Weight (NW / GW)	10.6 / 13.5 kg

FEATURES



Rapid IPS

Provides 1ms GTG fast response time, optimizes screen colors and brightness.



Ultimate 4K gaming

Enjoy the extreme fluid gaming and astonishing details with 4K (3840 x 2160) resolution at 160Hz high refresh rate.



Fast Response Time

Eliminate screen tearing and choppy frame rates with 1ms GTG response time.



HDMI 2.1

Best solution for console users. 4K 120Hz with HDMI™ interface.



Gaming Intelligence APP

Customize and set the ultimate monitor modes with keyboard & mouse in a very easy way.



Less Blue Light PRO

Use a hardware solution to reduce the light emission in the blue-violet region of the blue light spectrum (wavelength 415 to 455 nm).




VESA Certified DisplayHDR 400

Provide eye-catching detail through contrast and shadows adjustment.

Dimension (W x D x H)	727.1 x 233.7 x 494.9 mm 727.1 x 72.9 x 432.4 mm (Without Stand)
Carton Dimension (W X D X H)	WW carton: 982 x 168 x 550 mm Outer: 1000 x 185 x 575 mm
Note	DisplayPort: 3840x2160 (Up to 160Hz) HDMI™: 3840x2160 (Up to 160z) Type C(DP alt.): 3840 x 2160 (Up to 160Hz) and 90W PD charging Adobe RGB, DCI-P3 and sRGB follow CIE1976 Standard

CONNECTIONS



1. 5-Way Joystick Navigator
2. AC Power Jack
3. 2 x HDMI™ (2.1)
4. DisplayPort (1.4a)
5. Type-C (1.4a)
6. USB 2.0 Type-B
7. 3 x USB 2.0 Type-A
8. Headphone Out