# Product data sheet

Specification





# ClimaSys forced vent. IP54, 300m3/h, 230V, with outlet grille and filter G2

NSYCVF300M230PF

Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 178.00 USD

#### Overview

Lead time

Main	
Range	ClimaSys
Product name	ClimaSys CV
Product or Component Type	Fan
Type of filter	Standard
Flow rate	Free flow rate with standard filter: 79253.03 Gal/hr(US) (300 m3/h) at 50 Hz Free flow rate with standard filter: 92461.9 Gal/hr(US) (350 m3/h) at 60 Hz
[Us] rated supply voltage	145253 V
Input voltage	230 V 50/60 Hz

Usually Ships within 4 Weeks

## Complementary

Absorbed power	36 W 50 Hz
	37 W 60 Hz
Line Rated Current	0.16 A 60 Hz
	0.17 A 50 Hz
Noise level < at	5556 dB
Bearing type	Ball
Height	External: 10.6 in (268 mm)
Width	External: 9.8 in (248 mm)
Depth	External : 4.6 in (116 mm)
Cut-out dimensions	223 x 223 mm
Net Weight	2.9 lb(US) (1.3 kg)
Material	Outlet grille injected thermoplastic (ASA PC)
color	Outlet grille Gray RAL 7035)
Ambient Air Temperature for Operation	14.0000000000158.0000000000 °F (-1070 °C)
Ambient Air Temperature for Storage	-40.0000000000158.0000000000 °F (-4070 °C)
Maximum pressure	158 Pa flow rate 0 m³/h
Connections - Terminals	Faston connector
IP degree of protection	IP54

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Device composition	1 axial motor 2 protective grille on the front and rear surfaces 1 filter front of axial motor 1 outlet grille front 1 cut-out template 1 power cord
Condition of use	Surrounding environment must be relatively clean Filter must be cleaned and replaced regularly Outside temperature must be 5 °C lower than inside temperature Overfrequent filter replacement should be avoided Flow rates depends on the work point, see ProClima software

## Ordering and shipping details

_	, ,   •
Category	US10ES180036
Discount Schedule	0ES1
GTIN	3606480151286
Returnability	No
Country of origin	FR

# **Packing Units**

## **Contractual warranty**

Warranty 18 months



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance



Mercury Free



Rohs Exemption Information

Yes

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information