

# Product data sheet

Specifications



## APC NetShelter SX, Server Rack Enclosure, 45U, Shock Packaging, 2000 lbs, Black, 2124H x 600W x 1070D mm

AR3105SP

### Overview

**Presentation** NetShelter SX cabinet and packaging system designed to safely integrate, transport, unload and deploy up to 2000 lbs (907 kg) of IT equipment. The cabinet is paired with a shock absorbing pallet, unloading ramp, and impact resistant shell. The system has been engineered, tested and approved for secure shipment of fully converged systems such as being certified with Cisco® for pre-racking and shipping Cisco Unified Computing System (UCS).

**Lead time** Usually Ships within 6 Weeks

### Main

<b>Product or Component Type</b>	Rack enclosure
<b>Number of rack unit</b>	45U
<b>Provided equipment</b>	Baying hardware Key(s) Keyed-alike doors and side panels Leveling feet Mounting Hardware Pre-installed casters Side Panels User Manual

### Physical

<b>Height</b>	83.6 in (212.4 cm)
<b>Width</b>	23.6 in (60 cm)
<b>Depth</b>	42.1 in (107 cm)
<b>Net Weight</b>	302.03 lb(US) (137 kg)
<b>Color</b>	Black
<b>Mounting preference</b>	No preference
<b>Mounting Mode</b>	Not rack-mountable
<b>Maximum Mounting Depth</b>	36.02 in (91.49 cm)
<b>minimum mounting depth</b>	7.5 in (19.1 cm)
<b>rack width</b>	19"
<b>Marking</b>	14 gauge EIA mounting rail 16 gauge front door 16 gauge post 18 gauge rear door 18 gauge roof 14 gauge side panels
<b>Permanent permissible load</b>	2250 lb(US) (1020.6 kg) dynamic 3750 lb(US) (1701.0 kg) static

### Conformance

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

---

<b>Standards</b>	UL 2416 UL 60950-1 EIA-310E
------------------	-----------------------------------

## Ordering and shipping details

---

<b>GTIN</b>	731304309864
-------------	--------------

## Packing Units

---

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	91.1 in (231.4 cm)
<b>Package 1 Width</b>	52.008 in (132.1 cm)
<b>Package 1 Length</b>	43.5 in (110.5 cm)
<b>Package 1 Weight</b>	546.00 lb(US) (247.66 kg)

## Contractual warranty

---

<b>Warranty</b>	5 year repair or replace
-----------------	--------------------------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Take-back Transparency RoHS/REACH

## Resource performance

 Take-Back Program Available

---

## Well-being performance

 Reach Free Of Svhc

---

 Toxic Heavy Metal Free

---

 Mercury Free

---

 Rohs Exemption Information Yes

---

## Certifications & Standards

**Reach Regulation** [REACH Declaration](#)

---

**Eu Rohs Directive** Pro-active compliance (Product out of EU RoHS legal scope)

[EU RoHS Declaration](#)

---

**Environmental Disclosure** [Product Environmental Profile](#)

---

**Circularity Profile** [End of Life Information](#)

---