

24" Full HD 1080p LED Monitor

Stunning Viewing Quality


VA2451m-LED / VA2451m-TAA



ViewSonic's new 24-inch eco-friendly monitor, the VA2451m, is cost effective and produces a Full HD 1080p viewing experience. Featuring a widescreen Full HD 1080p 1920 x 1080 resolution, the VA2451m series deliver immaculate images for work and home environments. An incorporated LED backlight as well as a power-saving ECO-mode produces higher levels of brightness and refines image details even in low light conditions. Reducing power consumption with three different brightness throughputs helps to save on energy and accommodate different environments. Built-in sRGB color correction technology and dynamic contrast ratio also manage pixel quality to the finest detail and produces a great viewing experience.

Full HD 1080p for Superlative Pixel Performance

The VA2451m features Full HD 1080p 1920 x 1080 resolution for unbelievable pixel-by-pixel image performance. You'll experience the most amazing clarity and detail whether it be for working, gaming, or enjoying the latest in multimedia entertainment. A 16:9 widescreen ratio minimizes eye fatigue even after hours of viewing and is perfectly compatible with multi-window viewing without toggling.



Full HD 1080p

Normal

Planet-Friendly Mercury-Free LED Backlighting

The LED backlight further conserves up to 50% more energy when compared to conventional displays and allows a slimmer panel profile for a most pleasing entertainment experience.

ECO-Mode Conserves More Energy

ViewSonic's proprietary ECO-mode function provides options to "Optimize" and "Conserve", which reduces display brightness and conserves up to 35%* energy. Especially in a low ambient light, ECO-mode adjusts brightness and improves visibility while reducing eye fatigue and prolonging display lamp lifetime.


24" Full HD 1080p LED Monitor

10,000,000 : 1 Dynamic Contrast Ratio

Dynamic contrast ratio detects the brightness of an image, and automatically adjusts the backlight to maximize the monitor's color range and contrast. Dynamic contrast ratio technology enables the accurate reproduction of images, producing vibrant and rich visual effects.



Normal




Dynamic Contrast Ratio

sRGB Color Correction Defines the Truest Color

Accurate and consistent color performance is essential for professionals in graphic design, video editing and other professional environments. With built-in sRGB color correction technology, the VA2451m can reproduce 100% sRGB rich color performance and capture the original and true colors from screen to print.



VA2451m-LED / VA2451m-TAA



Kensington Security Lock

VESA Wall Mount

Power

Audio In

D-Sub

DVI

Specifications

LCD Panel	Type	23.6" Wide Color TFT Active Matrix LCD
	Display Area	20.5" horizontal x 11.5" vertical; 23.6" diagonal
Optimum Resolution	Brightness	1920x1080
	Contrast Ratio	300 cd/m ² (typ)
Viewing Angles	Response Time	1000:1 static (typ), 10,000,000:1 dynamic
	Backlight	170° horizontal, 160° vertical
Backlight Life	Aspect Ratio	5ms (typ.)
	Panel Surface	White-light LED
INPUT	Frequency	30,000 hours (min)
	Panel Surface	16:9
Analog	Anti-glare, hard-coating (3H)	
	Digital	
Sync	H/V separated (TTL)	
	Frequency	Fh = 24 ~ 82 kHz ; Fv = 50 ~ 75 Hz
AUDIO OUTPUT	Speakers	1.5 watt (x2)
	PC	
COMPATIBILITY	Mac®	
	Power Mac (up to 1920x1080)	
CONNECTOR	Analog	15-pin mini D-sub (VGA)
	Digital	DVI-D (with HDCP)
POWER	Power	Internal Power Board, 3-pin plug (CEE22)
	Voltage	AC 100~240V (universal), +/-10% Wide Range
CONSUMPTION	Consumption	28W (typ)
	Optimize	18W (typ)
CONTROLS	Basic	Conserve: 14.5W (typ)
	OSD	Power, 1, down, up, 2
Auto Image Adjust	Contrast/Brightness, Input Select (D-SUB, DVI), Audio adjust (Volume mute), Color Adjust (sRGB, 9300K, 7500K, 6500K, 5000K, User Color [R, G, B]), Information, Manual Image Adjust (H/V Position, Horizontal Size, Fine Tune, Sharpness, Dynamic Contrast, Response Time, Aspect Ratio, Eco-mode), Setup Menu (Language, Resolution Notice, OSD Position, OSD Timeout, OSD Background, Auto Power Off), Memory Recall	

ERGONOMICS	Tilt	-5°~20°
	Temperature	32~104°F (0~40°C)
OPERATING CONDITIONS	Humidity	10~90% (non-condensing)
	Physical with stand	22.1 x 16.4 x 7.9 in. / 560.3 x 417.6 x 199.3 mm
DIMENSIONS (W x H x D)	Physical without stand	22.1 x 13.1 x 2.3 in. / 560.3 x 332.7 x 59.2 mm
	Packaging	24.8 x 18.5 x 5.4 in. / 629 x 469 x 136 mm
WEIGHT	Net with stand	8.8 lb. / 4.0 kg
	Net without stand	8.3 lb. / 3.8 kg
WALL MOUNT	Gross	11.8 lb. / 5.3 kg
	VESA®	100 x 100 mm
REGULATIONS	UL/cUL, FCC-B, ENERGY STAR®, EPEAT(silver), Mexico Energy, NOM, WEEE, RoHS, CE, CB	
	RECYCLE/DISPOSAL	Please dispose of in accordance with local, state or federal laws.
WARRANTY	Three-year limited warranty on parts, labor and backlight	
	COUNTRY OF ORIGIN	VA2451m-LED China
VA2451m-TAA		Mexico

What's in the box?

VA2451m LED Display, power cable, VGA Video Cable, Audio Cable, ViewSonic Wizard CD-ROM, Quick Start Guide



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by TUV NORD.

*Energy savings may vary based on cost, actual usage and other factors. Specifications and availability are subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2012 ViewSonic Corporation. All rights reserved. [16093-00B-04/12] VA2451m_LED