

# Product datasheet

Specifications



## APC Back-UPS, 350VA/210W, Tower, 230V, 4x IEC C13 Outlets , User Replaceable Battery

BK350EI

### Overview


Lead time Usually in Stock

### Main

Main Input Voltage	230 V
Main Output Voltage	230 V
Rated power in W	210 W
Rated power in VA	350 VA
Product or component type	Uninterruptible power supply (UPS)
Input Connection Type	IEC 60320 C14
output connection type	3 IEC 60320 C13 1 IEC 60320 C13 surge 2 IEC Jumpers
Cable length	1.16 m
Number of cables	2
Battery type	Lead-acid battery
Provided equipment	CD with software Documentation CD Installation manual in japanese Detachable IEC power cord Detachable 1.2 m IEC power cord Telephone cable USB cable Warranty card

### Batteries & Runtime

Run Time	<a href="#">View Runtime Graph</a>
Efficiency	<a href="#">View Efficiency Graph</a>
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	6 h
Number of battery replacement quantity	1
Battery voltage	12 V
Battery capacity	7.0 Ah
Battery charger power	14 W rated
Battery power in VAh	116 VAh capacity 84 VAh runtime

Battery life	4...6 year(s)
Replacement battery	<a href="#">RBC2</a> 
Battery graph comments	This graph is based on actual measured runtime data. All measurements were taken with new, fully charged batteries and a balanced resistive load (PF = 1.0). Actual runtimes may vary from the values of this graph. Actual runtimes are dependent on several v
Extended runtime	0

## General

Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

## Physical

Colour	Beige
Height	16.5 cm
Width	9.1 cm
Depth	28.4 cm
Net weight	6.32 kg
Mounting location	Front
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No

## Input

Network frequency	50/60 Hz +/- 3 Hz auto-sensing
Input voltage limits	180...266 V
Maximum input current	7 A
Switching current capacity	7 A

## Output

Maximum configurable power in W	210 W
Output frequency	47...63 Hz sync to mains 50/60 Hz +/- 1 Hz unsynchronised
UPS type	Standby
Maximum configurable power in VA	350 VA
Transfer time	6 ms typical : 10 ms maximum

## Conformance

Product certifications	C-Tick CE GOST VDE
------------------------	-----------------------------

<b>Standards</b>	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
------------------	--

<b>Equipment protection policy</b>	Lifetime : 100000 euros Lifetime : 50000 GBP
------------------------------------	---

## Environmental

<b>Ambient air temperature for operation</b>	0...40 °C
<b>Relative humidity</b>	0...95 %
<b>Operating altitude</b>	0...10000 ft
<b>Ambient air temperature for storage</b>	-15...45 °C
<b>Storage Relative Humidity</b>	0...95 %
<b>Storage altitude</b>	0.0000000000...15240.0000000000 m
<b>Heat dissipation</b>	19 Btu/h

## Communications & Management

<b>Free slots</b>	0
<b>Control panel</b>	LED status display with on line : on battery : replace battery and overload indicators
<b>Alarm</b>	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

## Surge Protection and Filtering

<b>Surge energy rate</b>	310 J
<b>Noise suppression</b>	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	24.000 cm
<b>Package 1 Width</b>	19.000 cm
<b>Package 1 Length</b>	41.500 cm
<b>Package 1 Weight</b>	6.435 kg
<b>Unit Type of Package 2</b>	PAM
<b>Number of Units in Package 2</b>	70
<b>Package 2 Height</b>	142.000 cm
<b>Package 2 Width</b>	100.000 cm
<b>Package 2 Length</b>	120.000 cm
<b>Package 2 Weight</b>	492.450 kg
<b>SCC14</b>	10731304016349

## Contractual warranty

<b>Warranty</b>	2 years repair or replace
-----------------	---------------------------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Energy Efficient Take-back Transparency RoHS/REACH

## Resource performance

Energy Efficient Product

Take-Back Program Available

## Well-being performance

Rohs Exemption Information Yes

## Certifications & Standards

**Reach Regulation** [REACH Declaration](#)

**Eu Rohs Directive** Compliant with Exemptions

**China Rohs Regulation** [China RoHS declaration](#)  
Product out of China RoHS scope. Substance declaration for your information

**Environmental Disclosure** [Product Environmental Profile](#)

**Weee** The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

**Circularity Profile** [End of Life Information](#)