

HDMI to USB-C Video Capture Device - 1080p 60fps

Product ID: USBC2HDCAPRO



This HDMI to USB-C video capture device records high-definition HDMI video to your USB-C, USB-A or Thunderbolt 3 computer. With an aluminum enclosure, this device is built strong for fixed-location or on-the-go capture. It offers a separate 3.5 mm audio input for accompanying audio or voice-overs, and a HDMI pass-through port for connecting a monitor to review the video as it's captured.

Capture HD video at 1080p 60fps

Record 1080p video at 60fps (frames per second), to save your content so it can be shared, stored, or edited. Capture meetings, presentations, conference calls and from security equipment directly to your computer.

Easy video recording on Windows and Mac

The included software makes recording easy. Using a widely adopted codec, videos saved in StreamCatcher™ work with almost any video player and require no converting or editing.

Live stream on Windows

On Windows, you can live broadcast your video over the internet, using Twitch™ or other third-party video streaming platforms, with the included software.

DirectShow compatibility on Windows

With this capture device, you're not tied to the included software. You can record raw/lossless video using any third-party DirectShow™ compatible software, such as Open Broadcaster Software (OBS).

The USBC2DVCAPRO is backed by a 2-year StarTech.com warranty and free lifetime technical support.

Certifications, Reports and Compatibility



Applications

- Record video for training and tutorial purposes from devices that output HDMI
- Great for video producers that may have a camera connected directly to the capture device
- Great for recording the output from your PC, server, or POS station
- Add your own independent audio source for voice-over commentary

Features

- Includes a USB-A and USB-C cable for connection to any Mac or PC host
- Seamless picture quality with USB 3.0 bandwidth enabling you to capture 1080p video at 60fps
- Wide device playback support with universally encoded video files
- Raw/lossless video capture ensuring DirectShow™ compatibility on Windows devices
- Separate 3.5 mm audio input, for adding voice commentary or audio tracks
- Features an HDMI pass-through port, for watching the video as it is captured

Hardware	Warranty	2 Years																		
	Audio	Yes																		
	Chipset ID	Mstar - MST3363CNK-170																		
	Converter Type	Format Converter																		
	Industry Standards	MPEG4 (H.264)																		
Performance	Audio Specifications	2-channel stereo audio																		
	Maximum Digital Resolutions	1920 x 1080 60 FPS																		
	Supported Resolutions	1920 x 1080, 1280 x 720, 1024 x 768, 800 x 600																		
	Wide Screen Supported	Yes																		
Connector(s)	Connector A	1 - VGA (15 pin, High Density D-Sub) Female Input 1 - 3.5 mm Mini-Jack (3 Position) Female Input																		
	Connector B	1 - USB Type-B (9 pin) USB 3.0 Female																		
	Software	OS Compatibility	Windows® 7, 8, 8.1, 10 MacOS® 10.11 to 10.13																	
<table border="1"> <thead> <tr> <th></th> <th>Windows</th> <th>macOS</th> </tr> </thead> <tbody> <tr> <td>AVI</td> <td>Video - H.264 Audio -PCM</td> <td>N/A</td> </tr> <tr> <td>MP4</td> <td>Video - H.264 Audio - aac</td> <td>Video - H.264 Audio - aac</td> </tr> <tr> <td>TS</td> <td>Video - H.264 Audio - aac</td> <td>MPEG TS Video: MPEG-1, MPEG-2-video Audio: MPEG Audio layer 1, 2</td> </tr> <tr> <td>FLV</td> <td>Video - H.264 Audio - aac</td> <td>N/A</td> </tr> <tr> <td>MPG</td> <td>N/A</td> <td>MPEG program stream MPEG-1, MPEG-2-video Audio: MPEG Audio layer 1, 2</td> </tr> </tbody> </table>				Windows	macOS	AVI	Video - H.264 Audio -PCM	N/A	MP4	Video - H.264 Audio - aac	Video - H.264 Audio - aac	TS	Video - H.264 Audio - aac	MPEG TS Video: MPEG-1, MPEG-2-video Audio: MPEG Audio layer 1, 2	FLV	Video - H.264 Audio - aac	N/A	MPG	N/A	MPEG program stream MPEG-1, MPEG-2-video Audio: MPEG Audio layer 1, 2
	Windows	macOS																		
AVI	Video - H.264 Audio -PCM	N/A																		
MP4	Video - H.264 Audio - aac	Video - H.264 Audio - aac																		
TS	Video - H.264 Audio - aac	MPEG TS Video: MPEG-1, MPEG-2-video Audio: MPEG Audio layer 1, 2																		
FLV	Video - H.264 Audio - aac	N/A																		
MPG	N/A	MPEG program stream MPEG-1, MPEG-2-video Audio: MPEG Audio layer 1, 2																		
Special Notes / Requirements	Note	This video capture device requires a USB 3.0 port (or higher). The video capture device does not work with USB 2.0 ports (or lower).																		
Power	Power Source	USB-Powered																		

Environmental	Humidity	20% to 80% (non-condensing)
	Operating Temperature	0°C to 40°C (32°F to 104°F)
	Storage Temperature	-5°C to 40°C (23°F to 105°F)
Physical Characteristics	Product Height	1 in [24.3 mm]
	Product Length	3.6 in [92.2 mm]
	Product Weight	3.6 oz [102 g]
	Product Width	2.4 in [61.1 mm]
Packaging Information	Shipping (Package) Weight	1 lb [0.5 kg]
What's in the Box	Included in Package	1 - USB-C capture device
		1 - 6ft [2m] USB-C to USB-B cable
		1 - 3.3 ft [1 m] USB-A to USB-B cable
		1 - 3.3 ft [1 m] HDMI cable

Product appearance and specifications are subject to change without notice.