



iSeries 5014-6 Case Double Rifle Case

SKU: 3i-5014-DR



Description

The iSeries 5014 Double Rifle Case interior cavity features a fabric lining with molded EPS lid and base liners for structural strength as well as rifle separation. Strategically placed compression foam pads in the bottom and lid of the case prevent rifle movement inside the case.

SKB iSeries Injection Molded Mil-Standard Waterproof Cases are molded of ultra high-strength polypropylene copolymer resin, featuring a gasket-sealed, water and dust tight, submersible design (MIL-STD 810H) that is resistant to corrosion and impact damage. Standard features include a molded-in hinge, padlock loops, Trigger Latch® System, snap-down rubber over-molded cushion grip handle, automatic ambient pressure equalization valve (MIL-STD 810H), and resistance to UV, solvents, corrosion, fungus and impact damage (MIL-STD 810H).

Features

- bunk-bed storage system with rigid foam dividers
- In-line skate style wheels for easy transport
- Trigger Latch® System can be retrofitted with TSA accepted key locking latches
- Padlock holes include stainless steel padlock protector clips
- Cushion grip handles on three sides for comfortable lifting and carrying
- Waterproof and dust tight design (MIL-STD 810H)
- Molded-in hinge for added protection
- Trigger Latch® System
- Snap-down rubber over-molded cushion grip handle
- Ambient pressure equalization valve (MIL-STD 810H)

- Resistant to UV, solvents, corrosion, fungus (MIL-STD 81G)
- Resistant to impact damage (MIL-STD 810H)
- Lifetime Warranty
- Proudly made in the U.S.A

Specifications

Exterior	Hard	
Built In Wheels or Casters	Yes	
Interior Length	49 in	124.46 cm
Interior Width	13.5 in	34.29 cm
Interior Lid Depth	1 in	2.54 cm
Interior Base Depth	2.625 in	6.67 cm
Product Weight	22.96 lb	10.41 kg
Exterior Length	53 in	134.62 cm
Exterior Width	17 in	43.18 cm
Exterior Height	6.75 in	17.14 cm
Carton Length	54 in	137.16 cm
Carton Width	17.5 in	44.45 cm
Carton Height	7.5 in	19.05 cm
Shipping Weight	25.7 lb	11.66 kg
Max Temp	0 °F	-17.8 °C
Min Temp	0 °F	-17.8 °C

AVAILABLE CONFIGURATIONS

3i-5014-DR	Black / Pre-Cut
3i-5014-DR-T	Desert Tan / Pre-Cut