

Product data sheet

Specifications



APC Smart-UPS Step-Down Transformer, 5kVA, rackmount, 2U, 12x NEMA 5-20R outlets

SRT5KRMTF

Product availability: Stock - Normally stocked in distribution facility

Overview

Lead time Usually in Stock

Main

Main Input Voltage	208 V
Product or Component Type	Uninterruptible power supply (UPS)
Main Output Voltage	120 V
Input Connection Type	NEMA L6-30P
number of rack unit	2U
Number of cables	1
Provided Equipment	Mounting Hardware Rack Mounting brackets User Manual Warranty card

Physical

Color	Black
Height	3.5 in (8.9 cm)
Width	17.008 in (43.2 cm)
Depth	25.08 in (63.7 cm)
Net Weight	95.00 lb(US) (43.09 kg)
Mounting Location	Front
Mounting preference	No preference
Mounting Mode	Rack-mounted
Mounting position	Horizontal

Input

Max line current	24 A
Input current limits	30 A
Load Capacity	5000 VA

Output

Maximum Total Current Draw per Phase	24 A
Number of power socket outlets	12

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Number of power socket outlets	12 NEMA 5-20R
--------------------------------	---------------

Conformance

Product Certifications	CSA
------------------------	-----

Standards	UL 1778
-----------	---------

Environmental

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
---------------------------------------	-------------------------

Relative Humidity	0...95 % non-condensing
-------------------	-------------------------

Operating altitude	0...10000 ft
--------------------	--------------

Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
-------------------------------------	--------------------------

Storage Relative Humidity	0...95 % non-condensing
---------------------------	-------------------------

Storage altitude	0...50000 ft (0.0000000000...15240.0000000000 m)
------------------	--

Ordering and shipping details

Category	80230-IG SEBA TO SEUSA
----------	------------------------

Discount Schedule	BMS1
-------------------	------

GTIN	731304318866
------	--------------

Returnability	No
---------------	----

Country of origin	PH
-------------------	----

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Height	10.0000000000 in (25.4 cm)
------------------	----------------------------

Package 1 Width	37.5 in (95.2 cm)
-----------------	-------------------

Package 1 Length	24.5 in (62.2 cm)
------------------	-------------------

Package 1 Weight	110.01 lb(US) (49.9 kg)
------------------	-------------------------

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)




Take-back Transparency RoHS/REACH

Resource performance

 Take-Back Program Available

Well-being performance

 Rohs Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information.

Environmental Disclosure [Product Environmental Profile](#)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Circularity Profile [End of Life Information](#)