

# Power Cord Splitter, C14 to 2x C13 PDU Style - 10A, 250V, H05VV-F, 2 m (6.6 ft.), Black

MODEL NUMBER: P004-02M-2C13EU



Allows 2 devices with C14 inlets to share one AC power input cord and one C13 outlet on a PDU or UPS system.

## Features

### C14-to-C13 Y-Style Splitter Cord Connects 2 Devices with C14 Inlets to One C13 Outlet

This VDE-compliant splitter allows two devices with C14 power inlets to share one AC input cord and one C13 outlet. The P004-02M-2C13EU features an IEC-320-C14 end for connecting to an AC power source and two IEC-320-C13 ends for connecting to devices. By connecting two devices to one outlet, the power cord splitter frees up space in a PDU, UPS system or surge protector and helps reduce cable clutter. The 6.6-foot (2-meter) cable measures 24 inches (610 millimeters) from each C13 connector to the split.

### IEC Cable Powers a Wide Variety of Essential Electronics

With this PC power splitter, a single C13 outlet can power two devices, such as computers, monitors, printers, scanners, instrument amplifiers and other equipment compatible with a C13 connector. Ideal for areas where AC outlets are limited, such as rack cabinets, this IEC cable is compatible with power and extension cords of all brands.

### H05VV-F Jacket Is Fully VDE-Compatible for European Applications

The 0.75mm<sup>2</sup> enhanced PVC jacket complies with VDE, CE and UKCA standards for data centers, racks, workstations and other IT applications in Europe.

## Highlights

- Connects 2 devices to one AC outlet to save space and reduce cable clutter
- Recommended for powering multiple computers, monitors or other peripherals
- C14 end connects to PDU or UPS power; C13 ends connect to devices' C14 inlets
- Ideal replacement for worn-out or missing C13-to-C14 PDU-style extension cord
- VDE-compliant H05VV-F jacket allows use in European IT applications

## Package Includes

P004-02M-2C13EU C14 to C13 Power Cord Splitter, PDU Style, 2 m (6.6 ft.), Black

## Specifications

OVERVIEW	
UPC Code	037332280985
Product Type	Splitter
Device Compatibility	Computer; Monitor/HDTV; PDU; Printer; Scanner; UPS
Country/Region	Europe
INPUT	



Powering Business Worldwide

TRIPP LITE  
SERIES

Maximum Input Amps	10
Voltage Compatibility (VAC)	250
<b>CONNECTIONS</b>	
Side A - Connector 1	IEC-320-C14
Side B - Connector 1	(2) IEC-320-C13
<b>PHYSICAL</b>	
Plug Color	Black
Cable Jacket Color	Black
Cable Jacket Material	PVC
Power Cord Jacket Type	H05VV-F
Cable Outer Diameter (OD)	6.7 mm
Number of Conductors	3
Conductor Gauge	24/0.20AS
Wire Gauge (AWG)	18
Wire Gauge (OD - mm <sup>2</sup> )	0.75
Power Cord Color	Black
Cable Length (ft.)	6.56
Cable Length (m)	2.00
Shipping Dimensions (hwd / in.)	10.00 x 7.99 x 0.50
Shipping Dimensions (hwd / cm)	25.40 x 20.29 x 1.27
Shipping Weight (lbs.)	0.56
Shipping Weight (kg)	0.25
Unit Dimensions (hwd / in.)	10.000 x 7.990 x 0.500
Unit Packaging Type	Polybag
Unit Weight (lbs.)	0.54
Unit Weight (kg)	0.24
<b>ENVIRONMENTAL</b>	
Operating Temperature Range	5° to 158° F (-15° to 70° C)
Storage Temperature Range	5° to 140° F (-15° to 60° C)
Operating Humidity Range	20% TO 80% RH, NON-CONDENSING
Storage Humidity Range	20% TO 80% RH, NON-CONDENSING
<b>FEATURES &amp; SPECIFICATIONS</b>	
Antibacterial	No



Powering Business Worldwide

TRIPP LITE  
SERIES

Armored Cable	No
Angled Plug	No
High Voltage	Yes
Locking Plug	No
Coiled Power Cord	No
<b>STANDARDS &amp; COMPLIANCE</b>	
Product Compliance	CE (Europe); REACH; RoHS; UKCA
<b>WARRANTY &amp; SUPPORT</b>	
Product Warranty Period (Worldwide)	Lifetime limited warranty

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.