# **Product datasheet**

Specifications



Rack PDU, Basic, 0U/1U, 220-240V, 63A, (3) C19

AP6038A

### Overview

Lead time

Usually in Stock

### Main

Colour	Black
Product or component type	PDU
PDU type	Basic
Cord length	3.7 m
Provided equipment	Installation guide Safety guide

### Complementary

Input Voltage	230 V
	240 V
Height	4.4 cm
Width	38.8 cm
Depth	12.6 cm
Net weight	5.4 kg
Mounting location	Front
Mounting preference	No preference
Input Plug Type	IEC 60309 63 A 2P + PE
Mounting mode	Not rack-mountable
Rack units	1U
Mounting position	Horizontal
Permissible voltage	200240 V
Max line current	48 A
Input current limits	48 A
Load capacity	14500 VA
Network frequency	50/60 Hz
Outlet type and quantity	3 IEC 60320 C19

## Environment

## **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	39.5 cm
Package 1 Width	19.5 cm
Package 1 Length	50 cm
Package 1 Weight	8.3 kg

### Logistical informations

Country of origin

# **gin** IN

## **Contractual warranty**

Warranty

2 years repair or replace

## Sustainability Screen Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



#### **Resource performance**

Energy Efficient Product

Take-Back Program Available

### Well-being performance

Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes

### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information