

MICROLINE 4410



18 (2X9) Pin

MICROLINE 4410

18 (2X9) Pin

General Printing Characteristics

Print speed:	1066 cps	High speed draft
(max)	800cps	Utility
	200cps	NLQ
Throughput:	280 lines per minute sustained printing, (136 col. continuous text)	
Paper slew speed:	15 inches per second	
Number of pins :	18 (2 x 9)	
Graphics resolution:	Up to 288 (H) x 144 (V)	
Flash ROM:	8Mbit for code pages, emulations and macros	

Font and Print Features

Fonts:	NLQ Courier NLQ Gothic Utility High speed draft
Font sizes:	10, 12, 15, 17.1. 20 cpi and proportional to 216Pt. (Not HSD)
Font styles:	Emphasised, enhanced, Italics, underline, super/sub script, overscore, x2 height, x2 width, 272
Max. characters per line:	272
Bar codes:	Code 39, UPC A, UPC E, EAN 8, EAN 13, Interleaved 2 of 5, Code 128, Postnet

Interfaces and Emulations

Control panel:	2 x 16 backlit LCD, 13 button with configuration memories
Emulations:	IBM Proprinter, Epson FX, Oki Microline Flash ROM to store other emulations
Standard interfaces:	Centronics Parallel - IEEE1284 Serial RS232C (25 Pin, 38.4Kbps)
Optional interfaces:	Oki HSP Network Interface Card Coax/Twinax (Via optional HSP adapter board)

Major Applications

The ML 4410 is the flagship model in Oki's Microline range. It has been designed to handle multi-part listings at extremely high speeds, with reliability and superior throughput. With low cost of ownership it is ideal.

- Purchasing/distribution - up to 10 multi-part forms
- Accounts/finance/IT departments - superb speed for listings, computer printouts
- Administrations - high volume, data intensive printing tasks

Paper Handling

No. of multipart copies:	10 (one original + nine copies)
Max. paper thickness:	0.79mm (0.031")
Paper feed paths:	Front (straight) push tractor Rear push tractor Auto bail arm, auto thickness sense (switchable), software selectable paper paths

Reliability

Print head life:	400M characters
Ribbon life:	15M characters
MTBF:	12,000 hours @ 25% duty cycle, 35% page density
MTTR:	15 minutes
Noise (ISO 7779):	NLQ 52dBA (Quiet mode) Utility 55dBA (Quiet mode)

Other Options

Dedicated stand/cabinet (see picture above) with paper storage and output tray

Specifications/Operating conditions

Operating conditions:	5° to 35°C (41 to 95F) 20 to 80% RH
Storage conditions:	-10° to 43°C (14 to 109F) 5 to 95% RH

Approvals/Compatibility

Novell Netware certified	
Microsoft Plug & Play	
PostNet	
Energy Star	
European safety:	EN55022 Class B (CE) EN 60950 (CE) TUV IEC950



Oki strongly recommend the use of original Oki ribbons.
Inferior ribbons are less durable and can damage your print head.

Specifications subject to change without notice. All trademarks acknowledged.

Oki Systems (UK) Ltd
550 Dundee Road
Slough Trading Estate
Berkshire SL1 4LE
United Kingdom

Tel: +44 (0)1753 819819
Fax: +44 (0)1753 819899
www.oki.co.uk



*Professional high speed
printers you can rely on*