

Product data sheet

Specifications



Power Cord, C19 to C20, 4.5m

AP9887



Overview

| | |
|---------------------|---|
| Presentation | Rack PDU power cords for a variety of IT equipment. The output and input connections are C19 to C20. The cord length is 4.5m. The Nominal Output Voltage is 230V. |
| Lead time | Usually in Stock |

Main

| | |
|----------------------------------|---------------|
| Product or Component Type | Power cord |
| Main Output Voltage | 230 V |
| Input Connection Type | IEC 60320 C20 |
| Cable length | 15 ft (4.6 m) |
| Number of cables | 1 |

Physical

| | |
|----------------------------|-----------------------|
| Color | Black |
| Net Weight | 3.51 lb(US) (1.59 kg) |
| Mounting preference | No preference |
| Mounting Mode | Not rack-mountable |

Input

| | |
|---------------------------------|-------------|
| Acceptable Input Voltage | 200...240 V |
| Input current limits | 16 A |

Output

| | |
|---|-----------------|
| Maximum Total Current Draw per Phase | 16 A |
| Number of power socket outlets | 1 IEC 60320 C19 |

Conformance

| | |
|-------------------------------|-----|
| Product Certifications | VDE |
|-------------------------------|-----|

Ordering and shipping details

| | |
|--------------------------|-----------------------------|
| Category | 11309 - APC RESALE PRODUCTS |
| GTIN | 731304204138 |
| Returnability | No |
| Country of origin | US |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Packing Units

| | |
|------------------------------|-----------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 22.5 in (57.2 cm) |
| Package 1 Width | 4.5 in (11.4 cm) |
| Package 1 Length | 18.5 in (47 cm) |
| Package 1 Weight | 4.01 lb(US) (1.82 kg) |

Contractual warranty

| | |
|----------|---------------------------|
| Warranty | 2 years repair or replace |
|----------|---------------------------|

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)




Take-back Transparency RoHS/REACH

Resource performance

 Take-Back Program Available

Well-being performance

 Lead Free

Certifications & Standards

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Compliant

[EU RoHS Declaration](#)

Environmental Disclosure

[Product Environmental Profile](#)

Weee

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Circularity Profile

[End of Life Information](#)

California Proposition 65

WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov