

4XEM Thunderbolt 3 4K Display Universal Docking Station Model 2

4XEM Part- 4XUTD03H



Sleek and compact 4XEM's powerful Thunderbolt 3 Universal Docking Station, is offering single-cable connectivity to large high-resolution monitors or multiple monitors. The station also allows the user to gain access to faster Ethernet connectivity. As well as connectivity to any headset, microphone, or memory card reader regardless of the laptop they have.

Compatible with Mac or Windows, connect single display up to 4K 60Hz via the integrated DisplayPort output or an HDMI display by using provided active DisplayPort to HDMI Adapter. Access dual display by adding one more USB-C to DP/HDMI adapter connected to Thunderbolt 3 port.

The dock is two times faster than Thunderbolt 2 and eight times faster than USB 3.0, transferring of a full 4K movie in under 30 seconds, delivering speeds up to 40Gbps. With this unprecedented speed, you can continuously transfer large files to external backup storage or retrieve data from other storage devices quickly without compromising bandwidth from your 4K displays.

Connect displays, improve resolution, and transfer with new speed all with 4XEM's Thunderbolt 3 Universal Docking Station.

**4XEM Products Are Available At Your Favorite Online Retailers**

**WWW.4XEM.COM**

Contact Todd Schaus 4XEM sales Rep  
1-866-999-4936 Ext.104    [tschaus@4xem.com](mailto:tschaus@4xem.com)



## Features

- Thunderbolt 3 4K Universal Docking Station provides USB power delivery up to 100W maximum of upstream charging to compatible Thunderbolt 3 host systems and also, power to the other peripherals simultaneously with 180Watt Power Adapter.
- Integrated DisplayPort support 4K 60Hz (4096×2160@60Hz) or an HDMI display using the included accessories Active DisplayPort to HDMI 2.0 adapter.
- The second Thunderbolt 3 port placed at the front supports up to 5 daisy chained Thunderbolt 3 devices or a single USB 3.1 Gen 2 (up to 10Gbps) device.
- One USB3.0 port placed at the front and three USB3.0 port placed at the back to give more USB devices connectivity.
- Integrated RJ45 Gigabit Ethernet provide secure, reliable high speed wired networks
- Integrated SD/Micro SD Card Reader easy for copy any photos or movies from your media memory card backup to your PC directly.
- Integrated a combo audio headset, microphone port
- Mechanic security lock

## Application

- Home theatre
- Small business
- Multi-Screen Display
- Business Presentations

**4XEM Products Are Available At Your Favorite Online Retailers**



Warranty Information	Warranty	2 Years
Features/Hardware	4K Support Displays Supported USB Ports Fast-Charge Port(s) Network SD Card Reader Audio Power Delivery Lock Slot Industry Standards  Chipset ID	Yes 2 4 No Yes Yes Yes 85W Upstream + 60W Downstream No DisplayPort 1.2 (HBR2) HDMI 2.0 HDCP (Version depends on host GPU) Power Delivery (PD3.0) Secure Digital (SD v3.01) Battery Charging (BC 1.2) Alpine Ridge - JHL6540 Texas Instruments - TPS65983 Fresco Logic - FL1100 Fresco Logic - FL5000 Realtek - RTL8153 Genesys Logic - GL3224 Realtek - ALC4040
Connector(s)	Host Bus Type Host Connector Host Connector Cable Connector Type(s)/Rate(s)	Thunderbolt 3 (40Gbps) USB Type-C Detachable 1x DisplayPort 1.2 (HBR2: 5.40Gbps x4) 1x Thunderbolt 3 (40Gbps - DP Alt Mode - USB Mode: Max 10Gbps) 1x USB 3.0 Type-A (5Gbps - Quick Charge: 2.4A) 3x USB 3.0 Type-A (5Gbps) 1x RJ45 (10/100/1000/Mbps) 1x SD Card Reader (104 MB/s) 1x MicroSD Card Reader (104 MB/S) 1x 4-pole TRRS 3.5mm Phono Jack (Stereo/Mic Combo)
Performance	Maximum Digital Resolutions  Audio Specifications	Single Monitor: 5K (5120 x 2880 @ 60Hz) Dual Monitors: 4K UHD (3840 x 2160 @ 60Hz) Each Up to 8-ch via DP/HDMI 2-ch Stereo via 3.5mm Phono Jack
Software	OS Compatibility	Windows 10 Mac OSX
Power	Power Source Power Adapter Style Power Consumption Input Voltage Power Delivery	AC Adapter Included (100-240VAC, 50/60Hz, 2A Max , CLASS II) Brick 180W 20V DC @ 9A 85W Upstream (to Host) 60W Downstream (to Peripheral)
Physical Characteristics	Color Shell Material Host Cable Length Buttons/Switches LED Indicators Power Cable Length  Product Height Product Width Product Length Weight of Product	Grey and Black Aluminum and Plastic 24.02 in [610 mm] Power Button Power: Blue AC In: 4.58 ft [1.40 m] DC Out: 3.83 ft [1.17 m] 1.28 in [31.9 mm] 8.50 in [216 mm] 3.65 in [92.8mm] 12.63 oz [358 g]
Environmental	Operating Temperature Storage Temperature	32°F to 104°F [0°C to 40°C] @ 10%-90% RH (Non-Condensing) 14°F to 158°F [-10°C to 70°C] @ 10%-90% RH (Non-Condensing)
Packaging Information	Package Type Package Height Package Width Package Length Shipping (Package) Weight	Box 3.12 in [81 mm] 10.24 in [260 mm] 7.56 in [192 mm] 2.96 lbs [1.34 kg]
What's in the Box	Included in Package	1 x Thunderbolt™ 3 Universal Docking Station 1 x Thunderbolt™ 3 40Gbps cable 0.6 meter 1 x User Manual 1 x Active DP to HDMI Adapter 1 x DC20V/9A 180W Power Adapter 1x NEMA 5-15P to IEC 320 C13 Power Cable
Notes / Special Requirements	Notes	To display 5K resolution, both DP & TB3 connection are required.

\* Product appearance and specifications are subject to change without notice.

\* Same day shipping is only available for orders shipping within the United States.

