

## 4-Port USB Charging Station, 5V 6A/30W USB Charger Output, UK Version

MODEL NUMBER: **U280-004-UK**



Charges up to 4 electronic devices at the same time via USB connection. Ideal for quick-charging tablets, cell phones, laptops and other mobile devices.

### Description

Whether you're at home or in the office, this U280-004-UK 4-Port USB Charging Station provides enough ports and power to keep your devices at 100-percent capacity. No more peering behind furniture to find an available outlet or unplugging one device to charge another. You can charge up to four tablets, cell phones, laptops and other devices at the same time. The U280-004-UK doesn't require a computer, so you can take it anywhere AC power is available.

The U280-004-UK simultaneously provides up to 5V 1.5A of power per port at maximum capacity. Each individual port supports USB Battery Charging (BC) v1.2 and is capable of delivering up to 5V 2.4A, which is enough for charging even battery-intensive devices.

To charge your USB devices, simply connect the 1.2-meter power cord's BS-1363 plug to an AC power outlet, and connect your devices to the available USB ports. The unit protects against overheating, overcurrent and overcharging—in fact, it stops charging as soon as your devices' batteries are at full capacity. A front LED indicates the unit is turned on and receiving AC power.

### Features

**Charges Up to 4 Devices at the Same Time** Ideal for charging tablets, cell phones, laptops and other devices at home or work Connect devices to unit's USB ports for proficient charging Functions anywhere AC power is available—no computer required

**Provides Plenty of Juice for Charging** Each individual port supports USB Battery Charging (BC) v1.2 and is capable of delivering up to 5V, 2.4A, enough for charging battery-intensive devices like the Apple iPad Simultaneously provides up to 5V, 1.5A of power per port at maximum capacity Protects against overheating, overcurrent and overcharging

**Easy to Use** 1.2 m power cord with BS-1363 plug connects to AC outlet Front LED indicates when unit is turned on and receiving AC power

### Highlights

- 5V, 2.4A per port for charging battery-intensive devices
- 5V, 1.5A per port simultaneously when at maximum capacity
- All four ports support USB Battery Charging (BC) specification v1.2
- Internal dual-voltage power supply with BS-1363 plug
- Protects against overheating, overcurrent and overcharging
- No computer required

### Package Includes

- U280-004-UK 4-Port USB Charging Station
- C7 to BS-1363 power cord, 1.2 m
- Quick Start Guide

## Specifications

OVERVIEW	
UPC Code	037332192080



Powering Business Worldwide

TRIPP LITE  
SERIES

Product Type	Plug in Charger
Charging Form Factor	Charging Hub
Device Compatibility	Phone; Tablet; Amazon Kindle
<b>INPUT</b>	
Nominal Input Voltage(s) Supported	120V AC; 230V AC
Voltage Compatibility (VAC)	100; 110; 120; 125; 127; 200; 208; 220; 230; 240
Input Frequency	50 / 60 Hz
Input Plug Type	NEMA 1-15P (NON-POLARIZED)
Input Current	120V (0.8A) / 230V (0.4A)
<b>OUTPUT</b>	
Frequency Compatibility	50 / 60 Hz
Overload Protection	Yes
<b>POWER</b>	
Power Consumption (Watts)	38
Power Consumption Detail	38W (Operating) 0.26W (Standby)
<b>CONNECTIONS</b>	
Number of Ports	4
Side A - Connector 1	BS1363 UK PLUG
Side B - Connector 1	(4) USB A (FEMALE)
<b>USER INTERFACE, ALERTS &amp; CONTROLS</b>	
LED Indicators	Blue (Power)
<b>CHARGING</b>	
Number of Charging Ports	4
Total Charging Amps	6A
Total Charging Watts	30
Charging Method	USB
Charging Method Detail	5V - 1.5A (7W)
Charging Port Type	(4) USB A (FEMALE)
Charging Ports Details	USB-A: 5V/6A
Charging Ports / Amps	(4) 2.4A
<b>PHYSICAL</b>	
Color	White



Powering Business Worldwide

TRIPP LITE  
SERIES

Shipping Dimensions (hwd / in.)	2.00 x 5.20 x 7.30
Shipping Dimensions (hwd / cm)	5.08 x 13.21 x 18.54
Shipping Weight (lbs.)	0.87
Shipping Weight (kg)	0.39
Unit Dimensions (hwd / in.)	1.200 x 4.200 x 4.000
Unit Dimensions (hwd / cm)	3.1 x 10.6 x 10.1
Unit Packaging Type	Box
Unit Weight (lbs.)	0.46
Unit Weight (kg)	0.21
<b>ENVIRONMENTAL</b>	
Operating Temperature Range	41° to 95°F (5° to 35°C)
Storage Temperature Range	-4° to 122°F (-20° to 50°C)
Relative Humidity	20% to 80% RH, Non-Condensing
<b>FEATURES &amp; SPECIFICATIONS</b>	
GaN Technology	No
Overcurrent Protection	Yes
Overvoltage Protection	Yes
IP68 Rated	No
IP20 Rated	No
<b>STANDARDS &amp; COMPLIANCE</b>	
Product Compliance	RoHS; CE (Europe); REACH; FCC (USA)
<b>WARRANTY &amp; SUPPORT</b>	
Product Warranty Period (Worldwide)	2-year limited warranty

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.