

Yield Reporting Form

HP LaserJet Pro M118-M119 and HP LaserJet Pro MFP M148-M149 cartridge model CF294A

Declared ISO yield

Toner cartridge yield

Average cartridge yield **1,200** standard pages¹

Declared yield value in accordance with ISO/IEC 19752 based on continuous printing

| | |
|---|------------------------|
| Average ¹ | 1,265 |
| Standard Dev. | 52 |
| 90% lower confidence limit ¹ | 1,247 |
| Test date: beginning | 11/5/2018 |
| Test dates: ending | 11/27/2018 |
| Number of cartridges used in testing | 24 |
| Number of cartridges used in calculations | 24 |
| Type of cartridge | HP CF294A |
| Shake procedure used? | No |
| Print mode | Continuous |
| Job size | 100 pages per job |
| Number of engines used in testing | 8 |
| Media | Double A 80g |
| Paper size | A4 |
| Paper feed orientation | Short edge |
| Computer model | HP 346 G3 |
| Operating system | Microsoft Windows 10 |
| Application software | Adobe Reader 9 |
| Print driver version | W2G51-60101 V46.2.2636 |
| Connection type | network |
| Test page version* | Version 4.0 pdf |
| Power on/off every day | No |

Engine serial numbers:

Engine Firmware Version:

| | |
|------------|----------|
| VNF3K03916 | 20180726 |
| VNF3K03298 | 20180726 |
| VNF3K03914 | 20180726 |
| VNF3K05393 | 20180726 |
| VNC4701630 | 20180726 |
| VNC4701680 | 20180726 |
| VNC4701641 | 20180726 |
| VNC4701640 | 20180726 |

*filename: Download_Free___19752_Test_Chart___pdf from ISO SC28 website

Cartridge testing data

| Test environmental limits: | Temperature | Humidity |
|----------------------------|-------------|----------|
| | °C | %RH |
| Max running average | 24.4 | 56 |
| Min running average | 21.4 | 44 |
| Average | 23.1 | 52 |

| CF294A | | HP LJ Pro M118dw and M148fdw | |
|--------------|----------|------------------------------|-----------------|
| Cartridge | Lot Code | Engine SerNo | Cartridge Yield |
| CF294A_AM_1 | 8J11H1Aa | VNF3K03916 | 1325 |
| CF294A_AM_2 | 8J11H1Aa | VNF3K03298 | 1338 |
| CF294A_AM_3 | 8J11H1Aa | VNF3K03914 | 1292 |
| CF294A_AM_4 | 8J11H1Aa | VNF3K05393 | 1335 |
| CF294A_AM_5 | 8J11H1Aa | VNC4701630 | 1350 |
| CF294A_AM_6 | 8J11H1Aa | VNC4701680 | 1325 |
| CF294A_AM_7 | 8J11H1Aa | VNC4701641 | 1322 |
| CF294A_AM_8 | 8J11H1Aa | VNC4701640 | 1300 |
| CF294A_AM_9 | 8J23H1Aa | VNF3K03916 | 1196 |
| CF294A_AM_10 | 8J23H1Aa | VNF3K03298 | 1211 |
| CF294A_AM_11 | 8J23H1Aa | VNF3K03914 | 1245 |
| CF294A_AM_12 | 8J23H1Aa | VNF3K05393 | 1275 |
| CF294A_AM_13 | 8J23H1Aa | VNC4701630 | 1300 |
| CF294A_AM_14 | 8J23H1Aa | VNC4701680 | 1275 |
| CF294A_AM_15 | 8J23H1Aa | VNC4701641 | 1261 |
| CF294A_AM_16 | 8J23H1Aa | VNC4701640 | 1238 |
| CF294A_AM_17 | 8J29H1Aa | VNF3K03916 | 1237 |
| CF294A_AM_18 | 8J29H1Aa | VNF3K03298 | 1167 |
| CF294A_AM_19 | 8J29H1Aa | VNF3K03914 | 1194 |
| CF294A_AM_20 | 8J29H1Aa | VNF3K05393 | 1242 |
| CF294A_AM_21 | 8J29H1Aa | VNC4701630 | 1245 |
| CF294A_AM_22 | 8J29H1Aa | VNC4701680 | 1235 |
| CF294A_AM_23 | 8J29H1Aa | VNC4701641 | 1217 |
| CF294A_AM_24 | 8J29H1Aa | VNC4701640 | 1225 |

¹ In an ISO report two values are commonly listed: declared ISO yield and calculated test values. Generally, the calculated test values are higher than the declared ISO yield. Actual cartridge yields vary considerably based on content of images printed and other factors. For more information visit www.hp.com/go/learnaboutsupplies.