Specifications



APC NetShelter Switched Rack PDU, 1U, 1PH, 3.7kW 230V 16A or 3.3kW 208V 16A, 8 C13 outlets, C20 cord

AP7921B

Presentation	This APC Switched Rack PDU power distribution unit has a wide range of standardized PDU features that increase network efficiency, manageability and functionality. The output and input connections are (8)C13. Network management capabilities allow you to configure and manage rack PDUs from remote locations. It has has a local current monitoring display that gives a visible warning in case of an overload. The remote individual outlet control provides real-time monitoring of connected loads. It has a multi-tier user access that enables you to restrict unauthorized use of outlets. This rack has a single input power source making it easy to install.
Lead time	Usually in Stock

wan .		
Colour	Black	
Product or component type	PDU	
PDU type	Switched	
Cord length	2.5 m	
Number of cables	1	
Provided equipment	Installation guide Rack mounting brackets User manual	

Complementary

Input Voltage	200 V	
	208 V	
	230 V	
Height	4.4 cm	
Width	44.5 cm	
Output Voltage	208 V	
	230 V	
Depth	10.8 cm	
Net weight	2.27 kg	
Mounting location	Front	
	Rear	
Mounting preference	No preference	
Input Plug Type	IEC 60320 C20	
Mounting mode	Rack-mounted	
Rack units	1U	
Mounting position	Horizontal	

[In] rated current	16 A	
Permissible voltage	200240 V	
Input current limits	20 A	
Load capacity	3680 VA	
Network frequency	50/60 Hz	
Outlet type and quantity	8 IEC 60320 C13	

Environment

Product certifications	cUL listed CE CSA GOST IRAM MIC UL listed VDE VCCI
Standards	EN 55022 class A EN 55024 EN 61000-3-2 EN 61000-3-3 UL 60950
Ambient air temperature for operation	045 °C
Relative humidity	095 %
Operating altitude	010000 ft
Ambient air temperature for storage	-2565 °C
Storage Relative Humidity	095 %
Storage altitude	0.00000000015240.000000000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7 cm
Package 1 Width	34.3 cm
Package 1 Length	47 cm
Package 1 Weight	3.45 kg

Logistical informations

Country of origin

IN

Contractual warranty

Warranty

2 years repair or replace

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Energy Efficient Take-back Transparency RoHS/REACh

Resource performance

Energy Efficient Product

Take-Back Program Available

Well-being performance

Mercury Free

Rohs Exemption Information

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Yes