

# VA1906a-LED

**19" (18.5" VIEWABLE)  
WIDESCREEN LED MONITOR**

**WITH ENERGY STAR® 5.0**

## LED Backlight Monitor

ViewSonic's new VA1906a-LED is an ENERGY STAR® 5.0 certified, environment friendly 19" (18.5" viewable) widescreen monitor that features LED backlight providing energy savings\* up to 40%. With 1366x768 resolution, 10,000,000:1 MEGA dynamic contrast ratio and VESA® mountable glossy finish design, VA1906a-LED is ideal for both homes and offices. It also has an automatic aspect ratio adjustment so when your input is a 4:3 signal, the image will not be stretched but instead it will be positioned in the middle of the screen with side bars. 3-year limited warranty, the industry's best pixel performance policy and energy saving Eco-mode make VA1906a-LED the best choice for both corporate and education customers as well.



### PRODUCTIVE AND ENTERTAINING

- > **19" (18.5" viewable) widescreen LED**  
Displays crisp detail and fully saturated color with up to 40% energy savings\*.
- > **1366x768 native resolution**  
Incredible image detail for sharp text and graphics.
- > **10,000,000:1 MEGA dynamic contrast ratio**  
Provides for darker black levels and better overall front-of-screen performance.
- > **Stylish slim-bezel design**  
The thin bezel lets you see more without taking up valuable desktop real estate.
- > **OSD/power lock secures your settings**  
Prevents changes to monitor settings and maintains an optimized image.
- > **VESA® compliant**  
100mm x 100mm VESA® mountable design.
- > **Certified green**  
Environmentally-friendly with ENERGY STAR® 5.0 and EPEAT-Silver certifications.
- > **PC and Mac® compatible**



**ViewSonic®**  
See the difference® 

# VA1906a-LED

19" (18.5" VIEWABLE) WIDESCREEN LED MONITOR WITH ENERGY STAR® 5.0



<b>LCD</b>	Type	19" (18.5" viewable) Wide Color TFT Active Matrix LED
	Display Area	16.1" horizontal x 9.0" vertical; 18.5" diagonal
	Optimum Resolution	1366x768
	Contrast Ratio	1000:1 (typ); 10,000,000:1 (dynamic)
	Viewing Angles	160° horizontal, 160° vertical
	Response Time	5ms (typ)
	Light Source	Long life, 30,000 hrs. (typ)
	Brightness	250 cd/m <sup>2</sup> (typ)
Panel Surface	Anti-glare	
<b>VIDEO INPUT</b>	Analog	RGB analog (75 ohms, 0.7 Vp-p)
	Frequency	F <sub>H</sub> : 24~82kHz, F <sub>V</sub> : 50~75Hz
<b>COMPATIBILITY</b>	PC	VGA up to 1366x768 non-interlaced
	Mac <sup>®†</sup>	Power Mac <sup>™</sup> G3/G4/G5 up to 1366x768
<b>CONNECTOR</b>	Analog	15-pin mini D-sub (VGA)
	Power	3-pin AC plug (CEE22)
<b>POWER</b>	Voltage	AC 100–240V (universal), 50/60Hz (auto switch)
	Consumption	18W (typ)
<b>CONTROLS</b>	Basic	Power, 1, down, up, 2
	OSD	Auto image adjust, contrast, brightness, ViewMatch <sup>®</sup> color adjust (sRGB, 9300K, 6500K, default 5400K, RGB), information (resolution, H/V frequency, pixel clock, model number, serial number), manual image adjust (H/V position, H size, fine tune, sharpness), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), memory recall
<b>ERGONOMICS</b>	Tilt	Down 5°, Up 20°
<b>OPERATING</b>	Temperature	32–104° F (0–40° C)
<b>CONDITIONS</b>	Humidity	10–90% (non-condensing)
<b>DIMENSIONS</b> <b>(W x H x D)</b>	Physical with stand	17.4" x 13.5" x 7.7" (422mm x 342mm x 175mm)
	Physical without stand	17.4" x 10.9" x 2.3" (422mm x 278mm x 59mm)
	Packaging	19.4" x 15.6" x 5.4" (492mm x 395mm x 138mm)
<b>WEIGHT</b>	Net with stand	6.0 lb. (2.7 kg)
	Net without stand	5.4 lb. (2.5 kg)
	Gross	8.9 lb. (4.0 kg)
<b>WALL MOUNT</b>		VESA 100mm x 100mm
<b>REGULATIONS</b>		UL, cUL, FCC-B, CB, CE, NOM, TUV-S, GS, BSMI, CCC, PSB, C-TICK, RoHS, WEEE, GOST-R, SASO, ENERGY STAR <sup>®</sup> 5.0, EPEAT-Silver, REACH, SVHC, CEL, SEPRO
<b>RECYCLE/DISPOSAL</b>		Please dispose of in accordance with local, state or federal laws.
<b>PACKAGE CONTENTS</b>		LCD display, video cable, power cable, Quick Start Guide, ViewSonic Wizard CD (User Guide & drivers).
<b>WARRANTY</b>		Three-year limited warranty on parts, labor and backlight.



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by TUV NORD.

Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

<sup>†</sup>Adapter may be required. Analog adapter available from ViewSonic. \*Energy savings may vary based on actual usage and other factors. Specifications and availability are subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2011 ViewSonic Corporation. All rights reserved. [15713-00B-06/11] VA1906a-LED

**ViewSonic<sup>®</sup>**  
See the difference<sup>®</sup>

For more product information, visit us on the web at ViewSonic.com