

## Xerox® VersaLink® C400 Colour Printer



System Specification	VersaLink C400N	VersaLink C400DN
One-Sided Speed 8.5 x 11 in. A4 / 210 x 297 mm 8.5 x 14 in. / 216 x 356 mm	Up to 36 ppm colour and black-and-white Up to 35 ppm colour and black-and-white Up to 30 ppm colour and black-and-white	
Two-Sided Speed 8.5 x 11 in. A4 / 210 x 297 mm 8.5 x 14 in. / 216 x 356 mm	Up to 24 ppm colour and black-and-white Up to 23 ppm colour and black-and-white Up to 21 ppm colour and black-and-white	
Monthly Duty Cycle <sup>1</sup>	Up to 80,000 pages / month	
Recommended Average Monthly Print Volume <sup>2</sup>	Up to 5,000 pages	
Processor	1.05 GHz Dual-Core	
Memory	2 GB	
Connectivity	Ethernet 10/100/1000 Base-T High-speed USB 3.0 Wi-Fi 802.11n and Wi-Fi Direct with optional Wi-Fi Kit NFC Tap-to-Pair	
Controller Features	Unified Address Book, Configuration Cloning, Xerox Extensible Interface Platform®, Xerox® App Gallery, Xerox® Standard Accounting, Role Based Permissions, Convenience Authentication Enabled, Online Support (accessed from the user interface and print driver)	
Paper Handling	VersaLink C400N	VersaLink C400DN
Bypass Tray		
Capacity <sup>3</sup>	150 sheets	
Sizes	Custom Sizes: 3 x 5 in. to 8.5 x 14 in. / 76.2 x 127 mm to 216 x 356	mm
Weights	16 lb. bond to 80 lb. cover / 60 – 220 gsm	
Media Types	Plain Lightweight Cardstock Cardstock Hole Punched Recycled Pre-Printed Letterhead Bond Lightweight Glossy Cardstock Glossy Cardstock Labels Envelopes Custom	
Tray 1		
Tray 1 Capacity <sup>3</sup>	550 sheets	

Tray 1		
Weights	16 lb. bond to 80 lb. cover / 60 – 220 gsm	
Media Types	Plain Lightweight Cardstock Cardstock Hole Punched Recycled Pre-Printed Letterhead Bond Lightweight Glossy Cardstock Clossy Cardstock Custom	
Optional Tray 2		
Capacity <sup>3</sup>	550 sheets	
Sizes	Custom Sizes: 5.8 x 8.3 in. to 8.5 x 14 in. / 148 x 210 mm to 216 x 356 mm	
Weights	16 lb. bond to 80 lb. cover / 60 – 220 gsm	
Media Types	Plain Lightweight Cardstock Cardstock Hole Punched Recycled Pre-Printed Letterhead Bond Lightweight Glossy Cardstock Glossy Cardstock Custom	
Total Capacity		
Device Standard Capacity <sup>3</sup>	700 sheets	
Device Total Capacity <sup>3</sup>	1,250 sheets	
Paper Output		
Output Capacity <sup>3</sup>	250 sheets	
Automatic 2-Sided	NA NA	Standard
Device Specification	VersaLink C400N	VersaLink C400DN
Electrical Requirements		
North America	Voltage: 110-127 VAC+/- 10 % Frequency: 50/60 Hz+/- 3Hz, 10 A	
Europe	Voltage: 220-240 VAC+/- 10 % Frequency: 50/60 Hz+/- 3Hz, 6 A	
Power Consumption		
Continuous Printing <sup>4</sup>	705 watts or less	
Ready (Standby) Mode	76 watts or less	
Energy Saver (Sleep) Mode <sup>4</sup>	4 watts or less	
Operating Environment		
Required Temperature Range Storage Operating	32° F to 95° F / 0° C to 35° C 50° F to 90° F / 10° C to 32° C	
Required Reletive Humidity	10% to 85%	
Sound Power Levels	Operating: 6.88 B(A) or less; Standby 5.0 B(A) or less	
Sound Pressure Levels	Operating 53.1 dB(A) or less, Standby 29.2 dB(A) or less	
Boot Time (from Off to UI Ready)	As fast as 60 seconds	
Warm-Up Time (from Power Save)	As fast as 6 seconds	

Providence AWC-Life and a second			
Dimensions and Weight (unpackaged)			
VersaLink C400N	Width: 19.3 in. / 491 mm  Depth: 19.2 in. / 488 mm  Height: 15.7 in. / 399 mm  Weight: 57 lb. / 26 kg		
550-sheet Paper Tray	Width: 16.8 in. / 427 mm  Depth: 19.1 in. / 485 mm  Height: 5.4 in. / 138 mm  Weight: 8.6 lb. / 3.9 kg		
Dimensions and Weight (packaged)	Dimensions and Weight (packaged)		
VersaLink C400N	Width: 24.7 in. / 627 mm Depth: 25.1 in. / 638 mm Height: 20.7 in. / 526 mm Weight: 67.13 lb. / 30.45 kg		
550-sheet Paper Tray	Width: 23.2 in. / 590 mm Depth: 21.4 in. / 544 mm Height: 9.5 in. / 241 mm Weight: 11.7 lb. / 5.3 kg		
System Certification/Regulatory Con	mpliance		
Certifications	To view the latest list of certifications, go to www.xerox.com/OfficeCertifications.		
Print	VersaLink C400N VersaLink C400DN		
First-Page-Out Time	As fast as 13 seconds Colour / 12 seconds Black and White		
Resolution	Up to 600 x 600 x 8 dpi (enhanced)		
Page Description Languages	PCL® 5e, 6 PDF XPS TIFF JPEG HP-GL Adobe® PostScript® 3™		
Maximum Print Area	4 mm from edge of paper		
Print Features	Application Defaults Bi-directional Real-time Status Booklet Creation Draft Mode Job Identification Job Monitoring Personal Print Print from USB Sample Set Saved Job Scaling Secure Print Skip Blank Pages Store and Recall Driver Settings Two-sided Printing (as default - DN only) Xerox® Earth Smart Driver Settings		
Print from USB	Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS, PDF/A		
Operating Systems	Windows®, 7, 8, 10, Server 2000, Server 2008, Server 2008 R2 Server 2012  Mac OS® version 10.10, 10.11 & 10.12  Citrix  Redhat® Enterprise  Linux®  IBM® AIX® 7.2  HP-UX® 11iv3  Oracle® Solaris 11.3  Fedora Core 24  SUSE® 13.2		

Print	VersaLink C400N VersaLink C400DN	
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6,WSD LDAP Bonjour® / AirPrint™ Secure FTP Most protocols not in use can be disabled	
Administrative Protocols	DHCP, SNMP, WINS, HTTP, HTTPS, TLS, SNTP, MDNS	
Font Capability	PostScript fonts: 144 PCL fonts: 82	
Mobile Solutions and Mobile Device A	Apps	
Xerox® Mobile Express Driver®	Makes it easy for mobile users to find, use and manage Xerox® and non-Xerox® devices in every new location. Plug into a new network, and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of "favorite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.	
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox® devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.	
Apple® AirPrint®	Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.	
Google Cloud Print™	Google Cloud Print connects print devices to the web, enabling users to print the applications they use every day from smartphones, tablets, Chromebook $^{\text{M}}$ notebook computers and any other web-connected device.	
Xerox® Print Service Plug-in for Android™ (Free at Google Play™ Store)	The Xerox® Print Service Plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, Web pages and documents when your mobile device is connected to multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play™ store.	
Software Solutions		
Xerox® ConnectKey® Apps (Found at the Xerox® App Gallery	Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, serverless ConnectKey Apps to the device.	
Security	VersaLink C400N VersaLink C400DN	
Security Features	256-bit Encryption Access Controls Audit Log Automatic Self-Signed Certificate Creation Certificate Path Validation Certificate Revocation Settings Cisco® TrustSec Identity Services Engine (ISE) Integration Domain Filtering FIPS 140-2 Firmware Verification Immediate Disc Overwrite (with optional HDD) IP Address Filtering Network Authentication Port Filtering Role Based Permissions Secure Print Security Certificates Smart Card Enablement (CAC/PIV/.NET) SNMPv3 TLS	
Xerox® PrintSafe Software (Optional)	This authentication software integrates with trusted industry cards and readers and provides PIN access to nearly any printer in a customer's secured print environment. It works with both Xerox® devices and devices from other vendors. This software is open to work with a variety of industry standard secure readers and cards.	
Device Management		
Xerox® CentreWare® Web		
	A Web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system Works with any SNMP-managed printer from any manufacturer Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management.	
Xerox® Embedded Web Server - Integ	rated Device Web Page	
Device Status	Web server embedded  • Tray status/contents  • Consumables status	
Print Queue Viewing	Complete job print queue management—hold, release, promote and delete	

## Xerox® VersaLink® C400 Colour Printer

Xerox® Embedded Web Server - Integrated Device Web Page			
Job Submission	Print-ready files (PS, PCL, PDF, XPS, JPEG)		
	Output feature selection		
Device Administration	Allows simple, remote installation setting of configuration options and mand	agement of the device	
Browsers	Microsoft® Internet Explorer® 11 Microsoft Edge™ 38 Mozilla™ Firefox® 48 Apple® Safari® 9.1 Google Chrome™ 52 Opera™ 39		
Remote Print Services			
Xerox® MeterAssistant® Service	Automates the process of collecting and submitting meter reads for tracking and involvement and ensures that meter reads are submitted to Xerox on time.	d billing of Xerox® device usage. Eliminates the need for time-consumingend-user	
Xerox® SuppliesAssistant® Service	Automatically orders supplies for Xerox output devices based on actual usag	e, eliminating the need to manually manage supplies inventory.	
Maintenance Assistant	Offers a fast (and free) way to resolve potential issues and receive assistance Xerox®, allowing for problems to be solved faster with increased uptime.	and automate the troubleshooting/repair process. Diagnostic data is sent to	
Accounting			
Xerox® Standard Accounting (Standa	ard)		
Tracking	Print usage		
Accounting	Up to 9999 User Accounts with HHD installed Up to 1000 User Accounts without HHD installed (User ID) Up to 500 General accounts (Client)		
Features	<ul> <li>Administrator can manage the feature via the Web User Interface or device control panel in tools.</li> <li>Administrator has the ability to import or export user accounts, Group Accounts, General Accounts and User limits via an industry standard CSV file.</li> </ul>		
Accounting Options – Network Acco	unting (Allows central server to manage all accounting)		
	Enhanced network accounting with up to the minute data on how the system is being used     Comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and server fax     Numerous solutions are available through Xerox Alliance Partners. For details visit www.xerox.com     Security enhancements with the addition of HTTPS protocol support     Device requests account authentication from third party server enabling larger databases of users and accounts     Accept Authentication Login at control panel and pass to third party Networking Account     Interface with third party accounting terminal for accounting user interface		
What's In The Box			
	VersaLink C400 Color Printer Starter Capacity Print Cartridge: One of each (Cyan, Magenta, Yellow: 2,000 print capacity <sup>6</sup> , Black: 3,000 print capacity <sup>6</sup> Software and Documentation CD (Safety, Regulatory, Recycling and Disposal Guides, Print Drivers, and Warranty Statement) Installation Guide Quick Use Guides Power cord		
Supplies and Accessories	Quantity	Part Number	
Supplies			
Standard Capacity Toner Cartridges	Cyan: 2,500 standard pages <sup>5</sup> Magenta: 2,500 standard pages <sup>5</sup> Yellow: 2,500 standard pages <sup>5</sup> Black: 2,500 standard pages <sup>5</sup>	106R03510 106R03511 106R03509 106R03508	
High Capacity Toner Cartridges	Cyan: 4,800 standard pages <sup>5</sup> Magenta: 4,800 standard pages <sup>5</sup> Yellow: 4,800 standard pages <sup>5</sup> Black: 5,000 standard pages <sup>5</sup>	106R03522 106R03523 106R03521 106R03520	
Extra-High Capacity Toner Cartridges	Cyan: 8,000 standard pages <sup>5</sup> Magenta: 8,000 standard pages <sup>5</sup> Yellow: 8,000 standard pages <sup>5</sup> Black: 10,500 standard pages <sup>5</sup>	106R03534 106R03535 106R03533 106R03532	

## Xerox® VersaLink® C400 Colour Printer

Supplies and Accessories	Quantity	Part Number	
Supplies			
Drum Cartridge	Cyan: 60,000 standard pages <sup>6</sup> Magenta: 60,000 standard pages <sup>6</sup> Yellow: 60,000 standard pages <sup>6</sup> Black: 60,000 standard pages <sup>6</sup>	108R01121	
Waste Cartridge	30,000 standard pages <sup>6</sup>	108R01124	
Accessories			
550-sheet Paper Tray		097S04400	
Productivity Kit with 320 GB HDD		097S04914	
Stand		497K13660	
Wireless Network Adapter		497K16750	

<sup>&</sup>lt;sup>1</sup> Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling programme.

For more information, visit www.xerox.com/about-xerox/recycling.

For more information, visit us at www.xerox.com/office

Configurations vary by geography.



<sup>&</sup>lt;sup>2</sup> Expected regular monthly throughput.
<sup>3</sup> Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.
<sup>4</sup> Power states defined per ENERGY STAR® Programme requirements for Imaging Equipment.

<sup>&</sup>lt;sup>5</sup> Average standard pages. Declared Yield in accordance with ISO/IEC19752. Yield will vary based on image, area coverage and print mode.

<sup>6</sup> Approximate pages. Declared Yield based on 3 letter-/A4-size 20 lb. (75 gsm) pages. Yield will vary based on media type, size, weight, orientation, and usage patterns.