



Logitech G Yeti Studio Active Dynamic XLR Broadcast Microphone



Yeti Studio reinvents the traditional dynamic XLR mic with advanced tech and a gamer-first design for a true studio-quality stream experience. With ClearAmp active preamp technology built-in and an innovative dual-diaphragm dynamic capsule that minimizes noise and vibration, Yeti Studio takes Blue's legendary broadcast sound to the next level.

WHAT'S IN THE BOX

- Yeti Studio Active-Dynamic XLR Microphone
- Additional Windscreen
- 3/8" Mic Stand Adapter
- Quick Start Guide

FEATURES

- **The Quintessential Gaming Mic:** The Yeti Studio gaming microphone reinvents the traditional dynamic XLR microphone with advanced tech and a gamer-first design for a pro-quality gaming experience
- **ClearAmp Active Preamp Inside:** Built-in ClearAmp technology delivers +25dB additional gain for exceptional audio sound quality for your audience - no external mic booster required
- **Command the Stage:** An advanced dual-diaphragm dynamic microphone capsule delivers smooth low-end and superb detail while blocking out unwanted background noise and equipment hum
- **Look the Part:** This streaming microphone features a sleek design and interchangeable windscreens that give your game a custom aesthetic, helping you elevate your streaming
- **Remove Distractions:** Precise supercardioid pickup pattern zeroes in on your voice, so clicks and room noise don't make it into the game
- **Designed for Gamers:** Innovative 290-degree swivel mount gives gamers the freedom to place this streaming mic at virtually any angle for optimum play and streaming
- **Pro XLR Connection:** This wired microphone features an XLR connection that easily integrates with your audio interface or external mixer
- **Internal shockmount:** Built-in shockmount isolates the mic capsule and protects your game from bumps and vibrations



PACKAGE SPECIFICATIONS

	Primary pack	Master shipper carton
Part #	988-000563	N/A
Bar code	097855189462 (EAN-13)	10097855189469 (SCC-14)
Weight gr	1100	4960
Length cm	21.4	34.1
Width cm	8	23.2
Height/depth cm	22.2	26.2
Volume	3.8 dm ³	0m ³
1 primary pack	1	N/A
1 master shipper carton	4	1
1 pallet EURO	240	60
1 container 20 ft	5184	1296
1 container 40 ft	10880	2720
1 container 40 ft HQ	13600	3400

SYSTEM REQUIREMENTS

- Audio interface and XLR cable sold separately
- +48V phantom power required

TECHNICAL SPECS

- Transducer Type: Dynamic
- Polar Pattern: Supercardioid
- Frequency Response: 40Hz–18kHz
- Sensitivity: 20.97 mV/Pa @ 1kHz
- THD+N: 0.06% @ 1kHz, 94 dBSPL
Signal-to-Noise: 69.9 dB A-wt.
- Max SPL: 129 dBSPL @ 1% THD, 138 dBSPL @ 5% THD
- Power Requirement: +24V or +48V phantom power required
- Dimensions
- Length: 7.3 in (185 mm)
- Height: 6.5 in (165 mm)
- Width: 2.65 in (67 mm)
- Weight: 1.35 lbs (615 g)