Product data sheet

Specification





APC Smart-UPS X, Line Interactive, 750VA, Rack/tower convertible 2U, 120V, 8x 5-15R NEMA, SmartConnect port, Extended runtime

SMX750C

Overview

Lead time	Usually Ships within 2 Weeks
Main	
Main Input Voltage	120 V
Main Output Voltage	120 V
Kw Rating	675 W
Rated power in VA	750 VA
Product or Component Type	Uninterruptible power supply (UPS)
Input Connection Type	NEMA 5-15P
output connection type	8 NEMA 5-15R
Number of rack unit	2U
Cable length	8 ft (2.4 m)
Number of cables	1
Battery Type	Lead-Acid battery
Provided equipment	Warranty card Cat 5 ethernet cable USB cable Smart UPS signalling RS-232 cable Removable support feet Rack Mounting brackets Installation guide
Range of Product	Smart-UPS

Complementary

Software package SmartConnect software for remote power monitoring feature availability varies by terms of use

Batteries & Runtime

Run Time	View Runtime Graph ☐
Efficiency	View Efficiency Graph ☐
Extendable Run Time	1
Included Battery Modules	1
Battery Slots Empty	1
Typical recharge time	3 h

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

RBC Quantity	1
DC Overcurrent Protection	60 A
Battery life	35 year(s)
Replacement battery	APCRBC116 ☐
Battery Charge Power (Watts)	104 W rated

General

Number of power module filled slots	0
Number of power module free slots	0
product web sub-family	Extended run
Redundant	No

Physical

color	Black
Height	17.008 in (43.2 cm)
Width	3.5 in (8.9 cm)
Depth	19.3 in (49 cm)
Net Weight	48.61 lb(US) (22.05 kg)
Mounting preference	Lower
Mounting Mode	Rack-mounted with kit
Two post mountable	1
USB compatible	Yes

Input

Maximum Input Current per Phase	12 A
Maximum Short Circuit Withstand (Icw)	1000 kA
Switching current capacity	15 A
Efficiency at full load	75154 V adjustable 82143 V
Input Frequency	50/60 Hz +/- 3 Hz auto-sensing

Output

Harmonic distortion	Less than 5%
Maximum configurable power in VA	750 VA
Max Configurable Power (Watts)	675 W
Topology	Line Interactive
Waveform Type	Sine wave
Full load runtime	00:11:30 660 W
Half load runtime	00:27:00 330 W
Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz sync to mains

Conformance

Product Certifications	cUL Listed ENERGY STAR V2.0 (USA)
Equipment protection policy	Lifetime : \$150000

Environmental

Acoustic level	40 dBA
Online Thermal Dissipation	69 Btu/h
Operating altitude	010000 ft
Ambient Air Temperature for Operation	32.0000000000104.0000000000 °F (040 °C)
Ambient Air Temperature for Storage	5.0000000000113.0000000000 °F (-1545 °C)
Storage altitude	050000 ft (0.000000000015240.0000000000 m)
Relative Humidity	095 %
Storage Relative Humidity	095 %

Communications & Management

Emergency Power Off (EPO)	Yes
Free slots	1
Communication port support	SmartConnect Ethernet port: for cloud monitoring feature availability varies by terms of use
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rating	645 J
Filtering	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : mee

Ordering and shipping details

GTIN	731304401100
Country of origin	PH

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	23.2 in (58.9 cm)
Package 1 Width	24.4 in (62 cm)
Package 1 Length	9.7 in (24.6 cm)
Package 1 Weight	58.4 lb(US) (26.5 kg)

Contractual warranty

Warranty	3 years repair or replace for hardware. 2 years for battery, plus 1 additional year if

customers registers device to SmartConnect

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO2 products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Environmental Certifications



Energy Star®

ENERGY STAR UPS V2.0 (USA)

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	End of Life Information