

# Product data sheet

Specifications



APC Back-UPS Pro, 1500VA/  
865W, Tower, 120V, 10x NEMA  
5-15R outlets, AVR, LCD, User  
Replaceable Battery

BR1500G

## Overview

Lead time Usually in Stock

## Main

Main Input Voltage	120 V
Main Output Voltage	120 V
Rated power in W	865 W
Rated power in VA	1500 VA
product or component type	Uninterruptible power supply (UPS)
Input Connection Type	NEMA
output connection type	5 NEMA 5-15R 5 NEMA 5-15R surge
Cable length	6 ft (1.8 m)
Battery type	Lead-acid battery

## Batteries & Runtime

Run Time	<a href="#">View Runtime Graph</a>
Efficiency	<a href="#">View Efficiency Graph</a>
Number of battery filled slots	1
Number of battery free slots	0
Battery recharge time	8 h
Number of battery replacement quantity	1
Battery voltage	24 V
Battery capacity	9.0 Ah
Battery charger power	23 W rated
Battery life	3...5 year(s)
Replacement battery	<a href="#">APCRBC124</a>
Battery graph comments	This graph is based on actual measured runtime data. All measurements were taken with new, fully charged batteries and a balanced resistive load (PF = 1.0). Actual runtimes may vary from the values of this graph. Actual runtimes are dependent on several v
Extended runtime	0

## General

Provided equipment	user manual USB cable
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

## Physical

Height	11.9 in (30.1 cm)
Width	4.4 in (11.2 cm)
Depth	15.04 in (38.2 cm)
net weight	26.7 lb(US) (12.1 kg)
Mounting preference	No preference
mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	Yes

## Input

Network frequency	50/60 Hz +/- 3 Hz auto-sensing
-------------------	--------------------------------

## Output

Maximum configurable power in W	865 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
UPS type	Line interactive
Wave type	Stepped approximation to a sinewave
Maximum configurable power in VA	1500 VA
Transfer time	8 ms typical : 12 ms maximum

## Conformance

Product certifications	NOM TÜV ENERGY STAR V2.0 (USA)
Equipment protection policy	Lifetime : \$150000

## Environmental

Ambient air temperature for operation	32.0000000000...104.0000000000 °F (0...40 °C)
Relative humidity	0...95 %
Operating altitude	0...30000 ft
Ambient air temperature for storage	5.0000000000...113.0000000000 °F (-15...45 °C)
Storage Relative Humidity	0...95 %
Storage altitude	0...50000 ft (0.0000000000...15240.0000000000 m)
Acoustic level	45 dBA

## Communications & Management

---

<b>control panel</b>	Multifunction LCD status and control console
----------------------	--

---

<b>Alarm</b>	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
--------------	--

---

## Surge Protection and Filtering

---

<b>Surge energy rate</b>	354 J
--------------------------	-------

---

<b>Noise suppression</b>	Full time multi-pole noise filtering : 5% of IEEE surge let-through : zero clamping response time: instantaneous
--------------------------	--

---

<b>Let through voltage rating</b>	300 V
-----------------------------------	-------

---

## Packing Units

---

<b>Unit Type of Package 1</b>	PCE
-------------------------------	-----

---

<b>Number of Units in Package 1</b>	1
-------------------------------------	---

---

<b>Package 1 Height</b>	15.2 in (38.7 cm)
-------------------------	-------------------

---

<b>Package 1 Width</b>	19.2 in (48.8 cm)
------------------------	-------------------

---

<b>Package 1 Length</b>	9.4 in (23.8 cm)
-------------------------	------------------

---

<b>Package 1 Weight</b>	29.43 lb(US) (13.35 kg)
-------------------------	-------------------------

---

<b>SCC14</b>	10731304268779
--------------	----------------

---

## Contractual warranty

---

<b>Warranty</b>	3 years repair or replace
-----------------	---------------------------

---

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.


[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)




Energy Efficient Take-back Transparency RoHS/REACH


## Resource performance

 Energy Efficient Product

 Take-Back Program Available

## Well-being performance

 Mercury Free

 Rohs Exemption Information [Yes](#)

## Environmental Certifications

 Energy Star® [ENERGY STAR UPS V2.0 \(USA\)](#)

## Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive [Compliant with Exemptions](#)

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)