


VX2718-P-MHD - 27" OMNI 1080P 1MS 165HZ GAMING MONITOR WITH ADAPTIVE SYNC

Key Features


- 27 Inch Full HD (1920x1080p) gaming monitor with thin bezels
- 165Hz refresh rate 1ms MPRT response time (with DisplayPort) for ultimate gaming experience
- Adaptive Sync technology enables fluid and tear-free gameplay
- Flicker-Free technology and Blue Light Filter for reduced eye fatigue
- An arsenal of pre-set customizable visual modes keeps you ready for any FPS, RTS, or MOBA games
- The VX2718-P-MHD supports laptops, PCs, and Macs with HDMI and DisplayPort inputs




FULL HD (1920 x 1080P) RESOLUTION




**27
DISPLAY**



**MVA
PANEL**



**1920x1080
RESOLUTION**



68.98 cm | 27 in
45.8 cm | 18 in
61.5 cm | 24.2 in
22.6 cm | 8.9 in

Product Description

The ViewSonic® VX2718-P-MHD is a 27" 1080p gaming monitor built for gaming and entertainment. With a sleek frameless design, the VX2718-P-MHD provides a seamless viewing experience for multi-monitor gaming setups. Featuring a 165Hz* refresh rate, 1ms (MPRT) response time and adaptive sync technology, this monitor virtually eliminates screen tearing and stuttering for a fluid gaming experience. The VX2718-P-MHD also comes equipped with ViewSonic exclusive ViewMode™ presets, which offer optimized screen performance for different home entertainment applications such as watching movies, editing files, or playing video games. Two HDMI (v1.4) inputs, and one DisplayPort (v1.2) input offers flexible connectivity for both general use and entertainment. *165Hz refresh rate with DisplayPort

Specifications

More Information	
Screen Size	27

Viewable Area (in.)	27
Panel Type	MVA
Display Resolution	1920 x 1080
Display Resolution	Full HD (1920x1080)
Static Contrast Ratio	4,000:1
Dynamic Contrast Ratio	80,000,000:1
Light Source	LED
Brightness	250 cd/m2
Colors	16.7M
Color Space Support	8 bit (6 bit + FRC)
Aspect Ratio	16:9
Response Time (Typical GTG)	5ms
Response Time (MPRT)	1ms
Viewing Angles	178° horizontal, 178° vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-Glare type, Hard-coating (3H), Haze 25%
Refresh Rate	165Hz
PC Resolution (max)	1920x1080
Mac® Resolution (max)	1920x1080
3.5mm Audio Out	1
HDMI 1.4 In	2
DisplayPort	1
Internal Speakers	2W (x2)
Eco Mode (Conserve)	26W
Eco Mode (optimized)	28W
Consumption (typical)	32W
Consumption (max)	37W
Voltage	AC 100-240V (universal), 50-60Hz
Stand-by	0.5W
Power Supply	Internal
Cable Organization	No
Kensington Lock Slot	1
Physical Controls	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power)
On Screen Display	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu
Temperature	32-104° F (0 - 40° C)
Humidity (non-condensing)	20-90%

VESA Compatible	100 x 100 mm
Frequency Horizontal	HDMI (v1.4): 24 ~ 166.4 KHz, DisplayPort (v1.2): 24 ~ 183 KHz
Frequency Vertical	HDMI (v1.4): 50 ~ 144 Hz, DisplayPort (v1.2): 50 ~ 165 Hz
Tilt (Forward/Back)	5° / 25°
Net (lbs)	4.4
Net Without Stand (lbs)	4.0
Gross (lbs)	6.0
Net (kg)	9.7
Net Without Stand (kg)	8.8
Gross (kg)	13.2
Packaging (in.)	27.4 x 18.1 x 5.7
Physical (in.)	24.2 x 18.0 x 8.9
Physical Without Stand (in.)	24.2 x 14.3 x 1.8
Packaging (mm)	695.0 x 460.0 x 145.0
Physical (mm)	615.0 x 458.0 x 226.0
Physical Without Stand (mm)	615.0 x 364.0 x 46.0
Regulations	cTUVus, FCC-B, ICES003, CEC, NOM, Mexico Energy
PACKAGE CONTENTS	VX2718-P-MHD, Power Cable, DisplayPort Cable, Quick Start Guide
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.



Contact Sales
ViewSonic.com
 888.881.8781
 email:
salesinfo@viewsonic.com