

## High-Speed HDMI Cable, Digital Video with Audio, UHD 4K (M/M), Blue, 10 ft. (3.05 m)

MODEL NUMBER: **P568-010-BL**



High-speed premium cable connects two Ultra HD HDMI-enabled devices, including computers, Blu-ray™ players, video game systems, DVRs, video cameras, A/V receivers, monitors, projectors and televisions.

### Description

The P568-010-BL High-Speed HDMI Cable is ideal for digital signage, video presentations, point-of-sale displays, classrooms and other applications that display Ultra High Resolution (UHD) video and multi-channel audio. It connects HDMI-enabled source devices, such as computers and Blu-ray™ players, to HDMI-enabled displays, such as monitors, projectors and high-definition televisions.

This cable supports UHD video resolutions up to 3840 x 2160 (4K x 2K), including full 1080p, and data transfer speeds up to 18 Gbps—the fastest bandwidth currently available over HDMI. When used with an Apple® digital AV adapter, it supports iPad2® video mirroring for playing games, watching videos or displaying presentations. Backward compatible with previous HDMI generations, the P568-010-BL works in all HDMI cabling scenarios.

The 10-ft. (3.05 m) molded 30 AWG cable features premium foil and braid shielding to deliver top-of-the-line signal quality and protection from EMI/RFI interference. Gold-plated blue connectors ensure excellent conductivity. Integral strain relief ensures the cable and connectors last a long time. A flexible PVC jacket makes the HDCP-compliant cable easy to install in tight spaces.

### Features

#### Connects HDMI Source to 4K TV, Projector or Monitor

- Ideal for digital signage, video presentations, point-of-sale displays, classrooms and other applications that display Ultra High Resolution (UHD) video and multi-channel audio

#### High Performance and Wide Compatibility

- Supports UHD video resolutions up to 4K
- Supports iPad2 video mirroring when used with Apple digital AV adapter
- Backward compatible with previous HDMI generations

#### Superior Quality Ensures a Flawless Signal

- Corrosion-resistant gold-plated blue connectors for optimal signal transfer
- Fully molded 30 AWG construction with integral strain relief for durability and long life
- Premium foil and braid shielding for EMI/RFI noise protection
- Flexible PVC jacket easy to install in tight spaces

### Highlights

- Supports UHD video resolutions up to 4K
- Backward compatible with previous HDMI generations
- Premium foil and braid shielding protects against EMI/RFI noise
- Gold-plated blue connectors for optimal signal transfer

### Package Includes

- P568-010-BL High-Speed HDMI Cable with Digital Video and Audio (M/M), Blue, 10-ft. (3.05 m)



Powering Business Worldwide

TRIPP LITE  
SERIES

## Specifications

| OVERVIEW                          |                         |
|-----------------------------------|-------------------------|
| UPC Code                          | 037332197115            |
| Product Type                      | Passive Cable           |
| Technology                        | HDMI                    |
| Cable Type                        | Passive                 |
| VIDEO                             |                         |
| Max Supported Video Resolution    | 3840 x 2160 (4K) @ 30Hz |
| Max Supported Color Depth         | 48-bit Deep Color       |
| HDR Support                       | No                      |
| 3D Video Supported                | Yes                     |
| Chroma Sub Sampling               | 4:4:4                   |
| EDID Support                      | Yes                     |
| Signal Transmission               | Bidirectional           |
| AUDIO                             |                         |
| Audio Specification               | ARC                     |
| CONNECTIONS                       |                         |
| Side A - Connector 1              | HDMI (MALE)             |
| Side B - Connector 1              | HDMI (MALE)             |
| Connector Plating                 | Gold                    |
| Contact Plating                   | Gold                    |
| Connector Style                   | Straight                |
| Latching or Gripping Connector    | No                      |
| USER INTERFACE, ALERTS & CONTROLS |                         |
| LED Indicators                    | 0                       |
| PHYSICAL                          |                         |
| Color                             | Blue                    |
| Material of Construction          | ABS                     |
| Cable Jacket Color                | Blue                    |
| Connector Color                   | Blue                    |
| Cable Jacket Material             | PVC                     |



Powering Business Worldwide

TRIPP LITE  
SERIES

|                                              |                              |
|----------------------------------------------|------------------------------|
| Cable Jacket Rating                          | VW-1                         |
| Cable Outer Diameter (OD)                    | 6.0 mm                       |
| Wire Gauge (AWG)                             | 30                           |
| Cable Length (ft.)                           | 10                           |
| Cable Length (m)                             | 3.05                         |
| Cable Length (in.)                           | 120                          |
| Ferrite Core                                 | No                           |
| Minimum Bend Radius                          | 30mm                         |
| Shipping Dimensions (hwd / in.)              | 10.00 x 8.00 x 0.50          |
| Shipping Dimensions (hwd / cm)               | 25.40 x 20.32 x 1.27         |
| Shipping Weight (lbs.)                       | 0.40                         |
| Shipping Weight (kg)                         | 0.18                         |
| <b>ENVIRONMENTAL</b>                         |                              |
| Operating Temperature Range                  | 14° to 122°F (-10° to 50°C)  |
| Storage Temperature Range                    | 5° to 140°F (-15° to 60°C)   |
| Operating Humidity Range                     | 0% to 90% RH, Non-Condensing |
| Storage Humidity Range                       | 0% to 90% RH, Non-Condensing |
| <b>COMMUNICATIONS</b>                        |                              |
| EDID Compatible                              | Yes                          |
| Consumer Electronics Control (CEC) Supported | Yes                          |
| <b>FEATURES &amp; SPECIFICATIONS</b>         |                              |
| EMI/RFI Line Noise Protection                | No                           |
| MST Support                                  | No                           |
| Antibacterial                                | No                           |
| IP68 Rated                                   | No                           |
| IP20 Rated                                   | No                           |
| Armored Cable                                | No                           |
| Ethernet Support                             | No                           |
| HDCP Specification                           | 1.4; 2.2                     |
| <b>STANDARDS &amp; COMPLIANCE</b>            |                              |
| Product Compliance                           | RoHS; REACH                  |
| <b>WARRANTY &amp; SUPPORT</b>                |                              |



Powering Business Worldwide

TRIPP LITE  
SERIES

|                                        |                           |
|----------------------------------------|---------------------------|
| Product Warranty Period<br>(Worldwide) | Lifetime limited warranty |
|----------------------------------------|---------------------------|

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.