Poly VVX 250 4-Line IP Phone and PoE-enabled

For today's office

Quality sound is standard on the Poly VVX 250 IP desk phone. You'll appreciate all the smart features on non-stop call days, but equally love the color display. It's a win-win for today's office environments.



*Product image may differ from actual product

Conversations stay on track

Hear every nuance on the Poly VVX 250 IP desk phone with quality audio featuring Poly HD Voice. And reduce distracting background noise at the source with Poly Acoustic Fence technology.

Integrated protection 1

Your phones stay cleaner for longer with integrated Microban® antimicrobial product protection ¹ actively reducing the growth of bacteria 24/7.

Lines

Stay productive with 4-line keys supporting up to 34-line key appearances with pagination for autodials and contacts.

LCD color display

A 2.8-inch backlight color display offers an engaging experience with all the information you need at a glance.

Neys

4-way navigation cluster with a center select key and a 12-key dial pad with controls for mute, speaker, and headset volume.

Add a Poly headset

Multiple Poly headset options are available to suit your style — in addition to the traditional handset.²

Datasheet



Poly VVX 250 4-Line IP Phone and PoE-enabled

Specifications







Display

Native resolution: 320 x 240 Panel technology: Color LCD Display size (diagonal, metric): 7.1 cm (2.8")

Connectivity and communications

1USB 2.0 Type-A (for media, storage applications, headset, optional Wi-Fi adapter) 2 RJ-45 (10/100/1000BASE-TX Mbps)

Battery

Power features:

Built-in auto sensing IEEE 802.3af Power over Ethernet (Class 2) 4.5 W (maximum)³

User interface features

Arabic; Chinese; Czech; Danish; Dutch; English; French; German; Hungarian; Italian; Japanese; Korean; Norwegian; Polish; Management software; Portuguese; Romanian; Russian; Slovenian; Spanish; Swedish

Audio

Audio features:

Poly HD Voice

Poly A coustic Clarity technology provides full duplex conversations, acoustic echo cancellation, and background noise

Poly Acoustic Fence technology eliminates background noise when using a handset or wired headset Poly Computer Audio Connector app installed on your PC (Windows only) enables selecting your phone for PC audio

in/out to use the phones handset, optional headset and handsfree speakerphone with PC applications

Individual volume settings with visual feedback for each gudio path

Voice activity detection

Comfort noise generation

DTMF tone generation (RFC 2833 and in-band)

Low delay audio packet transmission

Adaptive jitter buffers

Frequency response (microphone): $150\,\text{Hz}$ to $7\,\text{kHz}$

Audio codecs:

G.711 (A-law and μ -law)

G.729AB

iLBC **OPUS**

Environmental

Certifications and compliances: Australia RCM; Brazil ANATEL; CAN/CSA C22.2 No. 62368-1-14EN 60950-1; EN 60950-1 & EN 62368-1; EN55024; EN55032 Class B; EN61000-3-2; EN61000-3-3; FCC Part 15 (CFR 47) Class B; ICES-003 Class B; IEC 609501 & IEC 623681; NZ Telepermit; ROHS compliant; So. Korea KC; So. Africa ICASA; Saudi Arabia CITC; UAE TRA; UL 60950-1 and UL 62368-1; VCCI Class B; Indonesia SDPPI; ISPR32 Class B; Korea KCC; LLDP-MED for VLAN discovery; Mexico NOM ANCE; RTP support; Russia CU

Operating humidity range: 5 to 95%

Operating Temperature Range (Celsius) / Operating Temperature Range (Fahrenheit): 0 to 40°C / Storage temperature range (Celsius) / Storage temperature range (Fahrenheit): -40 to 70°C / Energy star certified: ENERGY STAR® certified

Certifications

Special features:

Adjustable desk stand (2 positions) Unicode UTF-8 character support²

Applications supported

Poly Lens

Poly Zero Touch Provisioning

Polycom Device Management Service for Service Providers (PDMS-SP) Cloud Management

Display features

Digital picture frame

Security

Security management:

8021X Authentication and EAPOL Media encryption via SRTP

Digest authentication Encrypted configuration files

HTTPS secure provisioning

Password loain

Support for signed software executables

Support for URL syntax with password

Transport Layer Security (TLS)

SRTP media encryption using AES 256 bits

Network

Supported network protocols:

10/100/1000 Base-TX across LAN and PC ports

Conforms to IEEE802.3-2005 (Clause 40) for physical media attachment Conforms to IEEE802.3-2002 (Clause 28) for link partner auto-negotiation

Manual or dynamic host configuration protocol (DHCP) network setup

Up to 16 SIP line registrations with pagination key IETF SIP (RFC 3261 and companion RFCs)

Poly VVX 250 4-Line IP Phone and PoE-enabled

Specifications







Headset and handset compatibility

Headset ports:

1 Electronic Hook Switch (EHS) port for optional adapter

Headset and handset compatibility:

Compatible with commercially available TTY adapter equipment Compliant with ADA Section 508 Subpart B 1194.23 (all)

Hearing aid compatibility to ITU-TP.370 and TIA 504A standards

Hearing aid compatible (HAC) handset for magnetic coupling to hearing aids

Telephony and call handling features

Telephony and call handling features:

4 line kevs

Up to 16 line key assignments for lines, contacts, and features supported with pagination

Busy Lamp Field (BLF)

Call timer and call waiting

Call transfer, hold, divert (forward), park, pickup

Called, calling, connected party information

 $Calling\ Party\ Identification\ (RFC8225\ classifications-Trusted, Unknown, SPAM)$

Distinctive incoming call treatment/call waiting

Do not disturb function

Electronic hook switch capable

Enhanced Feature Keys make powerful feature shortcuts online key appearances or soft keys

Local three-way audio conferencing

Local configurable digit map/dial plan

One-touch speed dial, redial

Remote missed call notification Reverse number lookup via LDAP

Shared call/bridged line appearance

Flexible line appearance (one or more line keys can be assigned for each line extension) 1

Weight and dimensions

Product Primary Color: Black

Package dimensions (metric): 23.5 x 23.3 x 5.6 cm

Package Weight (metric): 890 g UPC number: 196188445471 Product number: 89B62AA

Warranty

Poly standard one-year limited warranty

What is in the box

Desk stand/wall mount hardware

Handset with handset cord

Network (LAN) cable-CAT-5E

Setup sheet

Key Selling Points Footnotes

¹Microban antimicrobial product protection is a built-in active ingredient that enables products to resist the growth of microbes such as bacteria, mold, and mildew. Microban protection helps products stay cleaner, fresher, and last longer than products with untreated surfaces. ² Poly headsets sold separately. Poly Electronic Hook Switch (EHS) sold separately.

Technical Specifications Footnotes

1 Most software enabled features must be supported by the service provider platform. Please contact your IP PBX/softswitch vendor or service provider for a list of supported features. 2 Optional wall mount kit can be ordered separately. 3 External universal AC/DC adapter, 5 VDC, 3 A, 15 W (sold separately).



