

4XEM USB 3.0 Universal Docking Station Deluxe

4XEM Part- 4XUG39DK3



Upgrade your productivity and organization with our Universal Deluxe Docking Station. This powerful device provides a Super Speed USB 3.0 (5 Gbps) link from your PC to video, microphone, 2 USB 3.0 ports, 2 USB 2.0 ports, in addition to two USB charging red color ports, HDMI port, DVI port, and wired Ethernet port that supports 10/100/1,000 Mbps speeds.

This docking station is the ultimate solution for connecting all your devices and peripherals in one place, allowing you to easily switch between your laptop and desktop, while still having access to all your peripherals and charging your devices. The red color charging ports, provide a visual indication for charging your devices.

This Universal Deluxe Docking Station is designed to improve your productivity and organization, making it the perfect addition to any workspace.

4XEM Products Are Available At Your Favorite Online Retailers

WWW.4XEM.COM

Contact Todd Schaus 4XEM sales Rep
1-866-999-4936 Ext.104 tschaus@4xem.com



Features

- USB 3.1 Gen 1 Host Connector - Detachable
- 1x HDMI 1.2 (4.95 Gbps)
- 1x DVI-SL (Single Link)
- 2x USB Type-A (5 Gbps)
- 2x USB Type-A (480 Mbps)
- 2x USB Type-A (No Data – 2.4A Fast Charge Only)
- 1x RJ-45 (10/100/1000 Mbps)
- 1x 3-pole TRS 3.5mm Phono Jack Audio In
- 1x 3-pole TRS 3.5mm Phono Jack Audio Out
- 4K Support through both DVI and HDMI ports
- Windows 7, 8, 10 and Mac OSX compatibility
- AC Adapter Included



Application

- Home theatre
- Small business
- Home Office
- Business Presentations



4XEM Products Are Available At Your Favorite Online Retailers





DATA SHEET

| | | |
|--------------------------|--|--|
| Warranty Information | Warranty | 2 Years |
| Features/Hardware | 4K Support Displays Supported USB Ports Fast-Charge Port(s) Network SD Card Reader Audio Power Delivery Lock Slot Industry Standards Chipset ID | Yes 2 6 2 Yes No Yes No Yes HDMI 1.2 HDCP 1.4 Battery Charging (BC 1.2) DisplayLink - DL3900 VIA - VL812B2 FE1.1S |
| Connector(s) | Host Bus Type Host Connectors Host Connector Cable Connector Type(s)/Rate(s) | USB 3.1 Gen 1 (5Gbps) USB Type-B (SuperSpeed) Detachable 1x HDMI 1.2 (4.95Gbps) 1x DVI-I SL (4.95Gbps) 2x USB Type-A (5Gbps) 2x USB Type-A (480Mbps) 2x USB Type-A (No Data - 2.4A Fast Charge Only) 1x RJ-45 (10/100/1000Mbps) 1x 3-pole TRS 3.5mm Phono Jack Audio In 1x 3-pole TRS 3.5mm Phono Jack Audio Out |
| Performance | Maximum Digital Resolutions Maximum Analog Resolutions Audio Specification | HDMI: 2560 x 1440 @ 30Hz DVI: 2048 x 1152 @ 60 Hz DVI: 2048 x 1152 @ 60 Hz (via DVI to VGA Adapter) 2-ch Stereo |
| Software | OS Compatibility | Windows 7, 8, 10 Mac OSX |
| Power | Power Source Power Adapter Style Power Consumption Input Voltage Power Delivery | Included AC Adapter (100-240VAC, 50/60Hz, 0.1A Max , CLASS II) Brick 48W 12V DC @ 4A N/A |
| Physical Characteristics | Color Shell Material Host Cable Length Buttons/Switches LED Indicators Power Cable Length Product Height Product Width Product Length Weight of Product | Black & Grey ABS Plastic 2.33 ft [0.71 m] None Power: Red AC In: 4.50 ft [1.37 m] DC Out: 3.58 ft [1.09 m] 2.48 in [63.0 mm] 5.12 in [130.0 mm] 4.06 in [103.0 mm] 13.05 oz [370 g] |
| Environmental | Operating Temperature Storage Temperature | 32°F to 104°F [0°C to 40°C] @ 10%-90% RH (Non-Condensing) 14°F to 158°F [-10°C to 70°C] @ 10%-90% RH (Non-Condensing) |
| Packaging Information | Package Type Package Height Package Width Package Length Shipping (Package) Weight | Box 4.72 in [120 mm] 6.57 in [167 mm] 4.96 in [126 mm] 2.19 lbs [0.99 kg] |
| What's in the Box | Included in Package | 1x Universal Dock 1x USB 3.0 Type-A to Type-B cable 1x DVI to VGA Adapter 1x DC12V/4A Power Adapter 1x NEMA 5-15P to IEC 320 C13 Power Cord 1x Operating Manual |

* Product appearance and specifications are subject to change without notice.

* Same day shipping is only available for orders shipping within the United States.

